



## Tableaux

- 25"
- Powered by Android

25BDL4050I/00

# Power free digital display boards

Technology for a brighter future

From confidently coloured menu boards to paper free POS posters, Philips Tableaux bring new era display potential to life. Digitise paper-based signage or swap out current digital models with ultra clear, easily updatable, ePaper displays.

## Benefits

### Operational flexibility

- Run your content at all times

### Brilliant performance

- Android SoC processor
- Full color e-paper display
- Sunlight readable

### Cost-effective system solution

- Low power consumption, power free operation

### Versatile system solution

- Technology for the future

## Features

### Easy content loading

Displaying 60,000 colours, including blue, for clear and confident messaging, and with 16GB internal memory. Plug into a power source to upload new static content for instant play, via USB, LAN or WiFi connections.

### Low to no power consumption

Perfect for environments without close access to power. Philips Tableaux can be positioned and repositioned, displaying colourful static content in the same way as paper posters, requiring a power connection only when loading new content.

# PHILIPS

## Technology for the future

Developing technology for your sustainable future – power free, waste free colourful paper poster replacements.

## Powered by Android

Android-powered Philips professional displays are flexible and secure, ensuring display specs stay up to the moment for longer.

## Specifications

[field not found 'disclaimer\_text']

### Picture/Display

|                             |                        |
|-----------------------------|------------------------|
| Diagonal screen size (inch) | 25.3 inch              |
| Panel resolution            | 3200 x 1800            |
| Aspect ratio                | 16:9                   |
| Display colors              | 60 000                 |
| Operating system            | Android 11             |
| Response time (typical)     | 36 sec to update image |

|                             |             |
|-----------------------------|-------------|
| Temperature range (storage) | -25 ~ 50 °C |
| Relative humidity           | 30 ~ 80 %   |
| Altitude                    | 0 ~ 3000 m  |

### Power

|             |                   |
|-------------|-------------------|
| Mains power | 20V/2.25A adapter |
|-------------|-------------------|

### Accessories

|                      |  |
|----------------------|--|
| Included Accessories | AC power adapter<br>Quick start guide (x1) |
|----------------------|--|

### Miscellaneous

|                      |                 |
|----------------------|-----------------|
| Regulatory approvals | CE<br>FCC       |
| Warranty             | 3 year warranty |

### Internal Player

|         |               |
|---------|---------------|
| CPU     | Rockchip PX30 |
| Memory  | 2GB LPDDR3    |
| Storage | 16GB EMMC     |

### Dimensions

|                |              |
|----------------|--------------|
| Set Width      | 602.4 mm     |
| Set Height     | 357.4 mm     |
| Set Depth      | 37.5 mm      |
| Wall Mount     | 100 x 100 mm |
| Product weight | 2.4 kg       |

### Connectivity

|                   |                                      |
|-------------------|--------------------------------------|
| Other connections | micro SD<br>micro USB<br>USB, type A |
| WiFi              | Wifi 2,4GHz and 5GHz                 |
| Audio output      | Speaker output (earphone jack)       |

### Communication

|             |                                |
|-------------|--------------------------------|
| Ethernet    | 10M/100M                       |
| Wi-Fi/ WLAN | WiFi 2.4G(802.11 b/g/n) + 5GHz |

### Convenience

|                      |   |
|----------------------|---|
| Placement            | Landscape (24/7)<br>Portrait (24/7)             |
| Network controllable | LAN (RJ45)                                      |
| Battery bay          | 4pcs 18650 batteries (>2600mAh)<br>not included |

### Operating conditions

|                               |              |
|-------------------------------|--------------|
| Temperature range (operation) | 15° ~ 35° °C |
|-------------------------------|--------------|



data subject to change  
2023, June 20

Version: 1.0.1  
EAN: 8712581801076

© 2023 Koninklijke Philips N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

[www.philips.com](http://www.philips.com)