



Philips
LCD widescreen monitor

51 cm (20.1") wide
WSXGA

200XW7EB

Wide screen enjoyment plus great convenience

View all your favourite entertainment on a single wide screen display with the Philips 200XW7 featuring a bigger, high resolution screen, fast response time, dual input options and great viewing comfort in an easy-to-use package.

Outstanding front of screen performance

- Empowered for Windows Vista
- Big, wide screen: IM, write mail, watch videos on one screen
- Fast 8 ms On/off response time: Great text and graphics display

Ergonomic design

- 90-degree screen rotation and smart cable management
- Tilt and swivel adjustment for the ideal viewing angle

Green design

- For your safety: Aerospace composite fire retardant case
- Lead-free design safeguards our environment

Great convenience

- Dual input accepts both analogue VGA and digital DVI signals
- USB port for convenient peripheral connections
- Easy to adjust display settings with Philips SmartControl
- Convenient built-in holder for notes, cards or photos

PHILIPS

Highlights

Windows Vista-ready

Philips Vista-ready monitors are empowered for vibrant, exciting display of this new, visually sophisticated and demanding Windows operating system, designed to enhance your entertainment experience, make you more productive and help you control your computing experience at home and in the office, making viewing, finding and organising information for work or play quick, efficient and easy.

Widescreen design

A wide screen has a wider aspect ratio for displaying more entertainment or information to have more fun and get more done.

8 ms response time (On/Off)

On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and, therefore, results in fewer visible image artefacts in the display of transition of text and graphics. On-Off response time is a more important measure in the display of business content such as documents, graphs and photos.

Super Ergo Base

The Super Ergo base is a monitor base that delivers ergonomic display comfort and provides intelligent cable management. The

base's people-friendly height, swivel, tilt and rotation angle adjustments position the monitor for maximum comfort that can ease the physical strains of a long working day; intelligent cable management reduces cable clutter and keeps the workspace neat and professional.

Screen tilt and swivel

Screen tilt and swivel mechanism built into the base permits the monitor to swivel and tilt backwards or forwards.

Flame retardant cabinet

PC/ABS plastic composite is the industry's best and toughest flame-retardant casing material; it is a space-age compound deployed in the aerospace and automotive industries, as well as in fire detectors, that is compliant with most stringent fire safety standards.

Lead-free

Lead-free display products are designed and produced in compliance with strict European Community directives on Restriction of Hazardous Substances (RoHS) standards that restrict lead and other toxic substances that can harm the environment.

Dual input

Dual input provides connectors to accommodate input of both analogue VGA and digital DVI signals.

USB 2.0 port

The USB port allows the user to conveniently connect their plug and play multimedia devices such as USB memory devices, camera, portable HDD, Web camera, PDA, Printer and many other devices that use USB connection. The conveniently located USB 2.0 port on the monitor allows USB 2.0 signals to pass through to the computer. Note that many devices like cameras and HDD may need to be powered on independently, as they have higher power requirements than the monitor USB port can provide.

SmartControl

PC software for fine-tuning display performance and settings. Philips offers users two choices for display setting adjustment. Either navigate the multilevel On Screen Display menu through buttons on the display itself or use the Philips SmartControl software to easily adjust the various display settings in a familiar way.

FlexiHolder

FlexiHolder is a slim groove on the top of the monitor that neatly and conveniently stores favourite photos, reminders, to-do lists or phone numbers in your line of vision.



Specifications

Picture/Display

- LCD panel type: 1680 x 1050 pixels, Anti-glare polariser, RGB vertical stripe
- Panel Size: 20.1"/51 cm
- Effective viewing area: 433.4 x 270.9 mm
- Pixel pitch: 0.258 x 0.258 mm
- Brightness: 300 cd/m²
- Contrast ratio (typical): 600:1
- Display colours: 16.2 M
- Viewing angle: 160° (H) / 145° (V), @ C/R > 5
- Response time (typical): 8 ms
- Maximum Resolution: 1680 x 1050 @ 60 Hz (digital input)
- Optimum resolution: 1680 x 1050 @ 60 Hz (digital input)
- Video Dot Rate: 205 MHz
- Horizontal Scanning Frequency: 30–98 kHz
- Vertical Scanning Frequency: 56 - 76 Hz
- Aspect ratio: 16:10
- sRGB

Connectivity

- Signal Input: VGA (Analogue), DVI-D
- USB: USB 2.0 x 1
- Sync Input: Composite Sync, Separate Sync, Sync on Green
- Video input impedance: 75 ohm
- Sync input impedance: 2.2k ohm
- Video input signal levels: 0.7 Vpp

Convenience

- User convenience: On-screen Display, SmartManage enabled
- Monitor Controls: Auto, Brightness Control (Up/Down), Left/Right, Menu (OK), Power On/Off
- OSD Languages: English, French, German, Italian, Russian, Spanish
- Other convenience: Kensington lock compatible
- Plug and Play Compatibility: DDC/CI, sRGB, Windows 98/ME/2000/XP/Vista
- Regulatory approvals: CE Mark, Energy Star, FCC-

- B, UL, CSA, SEMKO, TCO '03, TÜV/GS, TÜV Ergo
- Swivel: +/- 45°
- Tilt: -5° to 25°
- Height Adjustment: 130 mm
- Pivot: 90° (clockwise)
- VESA Mount: 100 x 100 mm

Accessories

- Included accessories: AC Power Cord, DVI-D cable, USB cable, VGA cable
- User Manual

Dimensions

- Box dimensions (W x H x D): 579 x 513 x 267 mm
- Box dimensions in inch (W x H x D): 22.8 x 20.2 x 10.5 inch
- Set dimensions (W x H x D): 483 x 338.5 x 68.7 mm
- Set dimensions in inch (W x H x D): 19 x 13.3 x 2.7 inch
- Set dimensions with stand (W x H x D): 483 x 402 x 215.3 mm
- Set dimensions with stand in inch (W x H x D): 19 x 15.8 x 8.5 inch
- MTBF: 50,000 hrs
- Relative humidity: 20% - 80%
- Temperature range (operation): 0°C to 35°C
- Temperature range (storage): -20°C to 60°C
- Product weight (+stand): 8.6 kg
- Product weight (+stand) (lb): 18.9 lb
- Weight incl. Packaging: 10.7 kg
- Weight incl. Packaging (lb): 23.6 lb

Power

- Complies with: Energy Star
- Consumption (On mode): 48 W (Typical)
- Consumption (Off Mode): < 1 W
- Power LED indicator: Operation - green, Standby/sleep - Amber
- Power supply: Built-in, 100-240 VAC, 50/60 Hz



Issue date 2022-05-18

Version: 3.0.4

12 NC: 8670 000 28349
EAN: 87 12581 32479 7

© 2022 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com