

PHILIPS

32:9 SuperWide curved
monitor with USB-C

Curved Business
Monitor

6000 series

45 (44.5" / 113 cm diag.)

5120 x 1440 (Dual QHD)

45B1U6900C



Beyond well-equipped

This Philips USB-C multi-purpose monitor offers clutter-free setup. With a single cable you can view smooth, high-resolution video, transfer data and charge your laptop. The headphone holder brings cable management to the next level.

Superb Picture Quality

- VA display delivers awesome images with wide viewing angles
- DisplayHDR 400 for more lifelike and outstanding visuals

Designed for the way you work

- Built-in stereo speakers for multimedia
- Tilt, swivel and height-adjust for an ideal viewing position
- Eyesafe-certified blue light protection and colour accuracy
- Curved display design for a more immersive experience
- 32:9 SuperWide: for replacing multi-screen setups

Optimal Connectivity

- Built-in KVM switch to easily switch between sources
- RJ-45 to USB-C gives easy network connection with security
- USB 3.2 high-speed data transfer

Designed for sustainability

- PowerSensor saves up to 80% energy costs

Curved Business Monitor

32:9 SuperWide curved monitor with USB-C

45B1U6900C/01

Highlights

USB-C Docking with RJ45




Simplify all peripherals from monitor to PC using one-cable docking USB Type-C connector, including networking, high-resolution video output from PC to monitor, and surfing on the Internet without an additional network cable, even without a LAN port on your notebook. RJ45 connection through USB-C offers a fast and secure connection when needed. Getting the fastest data speeds allows you to transfer data from a HDD to your PC faster than ever. Additionally, USB-C with power delivery can even enable you to power and charge your notebook from the monitor, eliminating the need for extra power cables.

MultiClient Integrated KVM




With the MultiClient Integrated KVM switch, you can control two separate PCs with one monitor-keyboard-mouse setup. A convenient button allows you to quickly switch between sources. Handy with setups that require dual PC computing power or sharing one large monitor to show two different PCs.

VA display




The Philips VA LED display uses an advanced multi-domain vertical alignment technology that gives you super-high static contrast ratios for extra-vivid and bright images. While standard office applications are handled with ease, it is especially suitable for photos, web browsing, films, gaming and demanding graphical applications. Its optimised pixel management technology gives you a 178/178 degree extra-wide viewing angle, resulting in crisp images.

DisplayHDR 400




VESA-certified DisplayHDR 400 delivers a significant step up from normal SDR displays. Unlike other 'HDR-compatible' screens, true DisplayHDR 400 produces astonishing brightness, contrast and colours. With global dimming and minimum 400 nits of brightness, images come to life with notable highlights while featuring deeper, more nuanced blacks. It renders a fuller palette of rich new colours, delivering a visual experience that engages your senses.

Curved display design




Desktop monitors offer a personal user experience, which suits a curved design very well. The curved screen provides a pleasant yet subtle immersion effect, which focuses on you at the centre of your desk.

PowerSensor



PowerSensor is a built-in 'people sensor' that transmits and receives harmless infrared signals to determine if the user is present and then automatically reduces monitor brightness when then user steps away from the desk, cutting energy costs by up to 80 percent and prolonging monitor life

32:9 SuperWide



This monitor's 32:9 SuperWide screen provides users with the ultimate replacement for a multi-screen desktop. With a singular 44.5 inch screen that is equivalent to two 23.8 inch 16:9 QHD monitors, it allows users to work seamlessly without having to daisy chain and increases productivity by offering users a large screen to open complex spreadsheets and view videos in their full form.



Curved Business Monitor

32:9 SuperWide curved monitor with USB-C

45B1U6900C/01

Highlights

TUV Rheinland Eyesafe




Philips display meets the TUV Rheinland Eyesafe® standard to truly protect you from long exposure to blue light. The always-on blue light filter not only helps reduce digital eye strain, but also guarantees colour integrity.

Built-in stereo speakers



A pair of high-quality stereo speakers built into a display device. They may be visible front firing, or invisible down firing, top firing, rear firing etc. depending on model and design.

Compact Ergo Base



The Compact Ergo Base is a people-friendly Philips monitor base that tilts, swivels and height-adjusts so each user can position the monitor for maximum viewing comfort and efficiency.



Specifications

Picture/Display

Panel Size: 44.5 inch / 113 cm
Aspect ratio: 32:9
LCD panel type: VA LCD
Backlight type: W-LED system
Pixel pitch: 0.2124 x 0.2124 mm
Brightness: 450 cd/m²
Display colours: 16.7 M (8 bit)
Colour gamut (typical): NTSC 107%*, sRGB 123%*
Contrast ratio (typical): 3000:1
SmartContrast: 80,000,000:1
Response time (typical): 4 ms (Grey to Grey)*
Viewing angle: 178° (H)/178° (V), @ C/R > 10
Picture enhancement: SmartImage
Maximum resolution: 5120 x 1440 @ 75 Hz
Effective viewing area: 1087.488 (H) x 305.856 (V) - at a 1500R curvature*
Scanning Frequency: 30–114 kHz (H)/48–75 Hz (V)
sRGB
Delta E: < 2
Flicker-free
Pixel Density: 120 PPI
LowBlue Mode
Display Screen Coating: Anti-Glare, 2H, Haze 25%
SmartUniformity: 93 ~ 105%
EasyRead
Adaptive sync
HDR: DisplayHDR 400 certified

Connectivity

Signal Input: HDMI 2.0 x 2, DisplayPort 1.4 x 1, USB-C x 1 (upstream, DP Alt mode, Data, PD up to 100 W)
Sync Input: Separate Sync
Audio (In/Out): Audio out
RJ45: Ethernet LAN up to 1 G*, Wake on LAN
HDCP: HDCP 1.4 (HDMI/DisplayPort/USB-C), HDCP 2.2 (HDMI/DisplayPort/USB-C)
HBR3: HBR3 (USB-C/DisplayPort)
USB Hub: USB 3.2 Gen 1/5 Gbps, USB-B upstream x 1, USB-A downstream x 4 (with 1 for fast charge B.C 1.2), USB-C downstream x 1 (Data, PD 15 W)

Power Delivery

Max power delivery: Up to 100 W* (5 V/3 A, 7 V/3 A, 9 V/3 A, 10 V/3 A, 12 V/3 A, 15 V/3 A, 20 V/4.8 A)
Version: USB PD version 3.0

Convenience

Built-in Speakers: 5 W x 2
Plug and Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 11/10/8.1/8
User convenience: KVM, SmartImage, Input, User, Menu, Power On/Off
OSD Languages: Brazil Portuguese, Czech, Dutch, English, French, Finnish, German, Greek, Hungarian, Italian, Japanese, Korean, Portuguese, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
Other convenience: Kensington lock, Earphone hook, VESA mount (100 x 100 mm)
Control software: SmartControl
MultiView: PIP/PBP mode, 2 x devices
KVM: Yes (USB-C/USB-B)

Stand

Height adjustment: 150 mm
Swivel: +/-45 degree
Tilt: -5/15 degree

Power

ECO mode: 36.5 W (typ.)
Power supply: Built-in, 100–240 VAC, 50–60 Hz
Off mode: Zero watts with AC switch
On mode: 46.3 W (typ.) (EnergyStar test method)
Standby mode: 0.3 W (typ.)
Power LED indicator: Operation - White, Standby mode - White (flashing)
Energy Label Class: G

Dimensions

Packaging in mm (W x H x D): 1180 x 235 x 535 mm
Product without stand (mm): 1085 x 337 x 158 mm
Product with stand (max height): 1085 x 515 x 238 mm

Weight

Product with packaging (kg): 17.11 kg
Product with stand (kg): 12.81 kg
Product without stand (kg): 9.75 kg

Operating conditions

Altitude: Operation: +12,000 ft (3658 m), Non-operation: +40,000 ft (12,192 m)
Temperature range (operation): 0°C to 40 °C
Relative humidity: 20%-80 %
Temperature range (storage): -20°C to 60 °C
MTBF (demonstrated): 70,000 hrs (excluded backlight)

Sustainability

Environmental and energy: PowerSensor, LightSensor, Energy Star 8.0, EPEAT*, RoHS, TCO Certified Edge
Post-consumer recycled plastic: 85%
Recyclable packaging material: 100 %
Specific Substances: Mercury free, PVC/BFR free housing

Compliance and standards

Regulatory Approvals: CB, CE Mark, FCC Class B, ICES-003, CU-EAC, EAEU RoHS, TUV Ergo, TUV/GS, eyesafe[®] CERTIFIED 2.0, cETLus, TÜV Rheinland Low Blue Light (Hardware Solution)

Cabinet

Finish: Texture
Foot: Black
Front bezel: Black
Rear cover: Black

What's in the box?

Cables: HDMI cable, DisplayPort cable, USB-C to C cable, Power cable
Monitor with stand
User Documentation

- * Radius of the arc of the display curvature in mm
- * Response time value equal to SmartResponse
- * NTSC Area based on CIE 1976
- * sRGB Area based on CIE1931
- * For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mode
- * Activities such as screen sharing and online streaming over the Internet can impact your network performance. Your hardware and network bandwidth will determine the overall audio and video quality.
- * For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more details.
- * If your Ethernet connection seems slow, please enter the OSD menu and select USB 3.0 or a higher version that can support the LAN speed up to 1G.
- * The USB-C power delivery of this display is up to 100 W (96 W in typical). The maximum power delivery will depend on your device.
- * When calculating energy costs saving from PowerSensor, both USB and Power delivery are excluded.
- * EPEAT rating is valid only where Philips registers the product. Please visit <https://www.epeat.net/> for registration status in your country.
- * The monitor may look different from feature images.

