[field not found 'leaflet_type'] (2021, May 20)



LCD monitor with SmartImage lite

- Ultra Narrow Bezel • 21 5" (54.6 cm)
- 21.5" (54.6 cm) • MHL
-

224E5QHAW/00

Vibrant images with AH-IPS display

with Ultra Narrow Bezel, MHL

This attractive Philips display with ultra narrow bezel and AH-IPS screen gives you awesome, vibrant color images. Mobile HD link allows you to connect your Smartphone.

Benefits

Entertainment with Mobile HD Link (MHL)

- MHL technology for enjoying mobile content on big screen
- Built-in stereo speakers for multimedia
- HDMI-ready for Full HD entertainment
- · Charge your mobile device while watching movie
- Optional MHL cable allows for HD video audio playback

Awesome picture quality

- AH-IPS display gives awesome images with wide viewing angles
- SmartImage Lite for an enhanced LCD viewing experience

- 16:9 Full HD display for best viewing experience
- TrueVision ensures lab quality images

Stylish design

- Minimalistic looks with Ultra Narrow Bezel
- Superb glossy and texture finish
- VESA mount for convenience

PHILIPS

Features

MHL technology



Mobile High Definition Link (MHL) is a mobile audio/video interface for directly connecting mobile phones and other portable devices to highdefinition displays. An optional MHL cable allows you to simply connect your MHL capable mobile device to this large Philips MHL display, and watch your HD videos come to life with full digital sound. Now not only you can enjoy your mobile games, photos, movies, or other apps on its big screen, you can simultaneously charge your mobile device so you never run out of power half way.

AH-IPS technology



AH-IPS displays use an advanced technology which gives you extra wide viewing angles of 178/178 degree, making it possible to view the display from almost any angle. Unlike standard TN panels, AH-IPS displays gives you remarkably crisp images with vivid colors, making it ideal not only for Photos, movies and web browsing, but also for professional applications which demand color accuracy and consistent brightness at all times.

Ultra Narrow Bezel

Utilizing latest technology panels, the new Philips displays are designed with minimalistic approach by limiting the outer bezel thickness to about 2.5mm. Combined with in-panel black matrix strip of around 9mm, the overall bezel dimensions are reduced significantly allowing for minimal distractions and maximum viewing size. Especially suited for multi-display or tiling setup like gaming, graphics design and professional applications, the Ultra narrow bezel display gives you the feeling of using one large display.

SmartImage Lite

SmartImage Lite is an exclusive, leading edge Philips technology that analyzes the content displayed on your screen. Based on a scenario you select, SmartImage Lite dynamically enhances the contrast, color saturation and sharpness of images and videos for ultimate display performance - all in real time with the press on a single button.

Built-in stereo speakers



A pair of high quality stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables highquality digital video and audio all transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

16:9 Full HD



The Full HD screen has the widescreen resolution of 1920 x 1080p. This is the highest resolution of HD sources for the best possible picture quality. It is fully future proof as it supports 1080p signals from all sources, including the most recent like Blu-ray and advanced HD game consoles. The signal processing is extensively upgraded to support this much higher signal quality and resolution. It produces brilliant flicker-free progressive scan pictures with superb brightness and colors.

TrueVision



TrueVision is a proprietary Philips technology that uses advanced algorithm for testing and aligning monitor display which gives you the ultimate display performance. Philips ensures TrueVision monitors leave the factory fine-tuned with this process giving you consistent color and picture quality.

Specifications

[field not found 'disclaimer_text']

Picture/Display

LCD panel type Backlight type Panel Size Effective viewing area Aspect ratio Optimum resolution SmartResponse (typical) Brightness Contrast ratio (typical) SmartContrast Pixel pitch Viewing angle

Picture enhancement Display colors Scanning Frequency MHL sRGB

Connectivity

Signal Input

Sync Input

Audio (In/Out)

Convenience

Built-in Speakers User convenience

OSD Languages

Other convenience

Plug & Play Compati-

bility

AH-IPS LCD W-LED system 21.5 inch / 54.6 cm 476.1 (H) x 267.8 (V) 16:9 1920 x 1080 @ 60Hz 5 ms (Grey to Grey)

250 cd/m²

1000:1 20,000,000:1 0.248 × 0.248 mm 178° (H) / 178° (V) @ C/R > 10 SmartImage Lite 16.7 M 30 -83 kHz (H) / 56 -75 Hz (V) 1080p@30Hz Yes

HDMI (digital, HDCP) MHL-HDMI (digital, HDCP) VGA (Analog) Separate Sync Sync on Green PC audio-in Headphone out

5Wx2 Power On/Off Menu Volume Input SmartImage lite **Brazil Portuguese** Czech Dutch English Finnish French German Greek Hungarian Italian Japanese Korean Polish Portuguese Russian Simplified Chinese Spanish . Swedish Traditional Chinese Turkish Ukranian Kensington lock VESA mount (100x100mm) DDC/CI Mac OS X sRGB Windows 7

Windows 8 Stand Tilt -5/20 degree Power On mode 26.5 W (typ.) 0.5 W (typ.) Standby mode 0.3 W (typ.) Off mode Power LED indicator Operation - White Standby mode- White (blinking) Power supply External 100-240VAC, 50-60Hz Dimensions Product with stand 500 x 394 x 213 mm (mm) Product without 500 x 306 x 47 mm stand (mm) Packaging in mm 562 x 466 x 106 mm (WxHxD) Weight Product with stand 3.14 kg (kg) Product without 2.82 kg stand (kg) Product with pack-5.01 kg aging (kg) **Operating conditions** Temperature range 0°C to 40°C °C (operation) -20°C to 60°C °C Temperature range (storage) Relative humidity 20%-80 % Altitude Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m) MTBF 30,000 hour(s) Sustainability Environmental and RoHS Mercury Free energy Recyclable packaging 100 % material Compliance and standards **Regulatory Approvals** BSMI

CE Mark cETLus FCC Class B GOST SASO SEMKO TUV/ISO9241-307 WEEE

Cabinet

Color Finish White Glossy

* Requires optional MHL certified mobile device and MHL cable. (not included) Please check with your MHL device vendor for compatibility. * Standby/Off energy saving of ErP is not applicable for the MHL charging functionality * "IPS" word mark / trademark and related patents on technologies belong to their respective owners.



data subject to change 2021, May 20 Version: 5.0.1

EAN: 8712581701895

© 2021 Koninklijke Philips N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com