

Philips Signage Solutions LED-backlit LCD Display

32 (viewable 31.5" / 80 cm) 1920 × 1080 (Full HD)

BDM3201FC

Expand your experience

Expand your viewing experience with this big Philips display. With this expansive 32" class full HD display you can really immerse yourself into the game, or even give yourself needed space to spread out your work.

Greener everyday

· Eco-friendly materials that meets international standards

Design to enhance the looks

• VESA mount allows for the perfect setup

Expand your viewing experience

- Expansive 31.5-inch brilliant display
- Full 1080p HD display, with a 1920x1080p resolution
- SmartImage presets for easy optimized image settings
- SmartContrast for rich black details
- IPS-ADS wide-view technology for image and color accuracy



Highlights

IPS-ADS technology



IPS-ADS displays use an advanced technology which gives you extra wide viewing angles of 178/178 degree, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS-ADS displays give you remarkably crisp images with vivid colors, making it ideal not only for Photos, movies and web browsing, but also for professional applications which demand color accuracy and consistent brightness at all times.

Expansive 31.5-inch brilliant

Expansive 31.5-inch brilliant display

Full 1080p HD display



The Full HD screen has the widescreen resolution of $1920 \times 1080p$. This is the highest resolution of HD sources for the best possible picture quality. It is fully future proof as it supports 1080p signals from all sources, including the most recent like Blu-ray and

advanced HD game consoles. The signal processing is extensively upgraded to support this much higher signal quality and resolution. It produces brilliant flicker-free progressive scan pictures with superb brightness and colors.

SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

SmartImage



SmartImage is an exclusive leading edge Philips technology that analyzes the content displayed

on your screen and gives you optimized display performance. This user friendly interface allows you to select various modes like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, Smartlmage dynamically optimizes the contrast, color saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time with the press of a single button!

VESA mount

VESA pattern guarantees compatibility hundreds of innovative mounting solutions.

Eco-friendly materials

"Philips is committed to use sustainable, eco-friendly materials across its display range. All body plastic parts, metal chassis parts and packing materials use 100% recyclable materials. In some selected models we utilize upto 65% post consumer recycled plastics. Strict adherence to RoHS standards ensure substantial reduction or elimination of toxic substances like Lead, for example. Mercury content in displays with CCFL backlight has been reduced significantly, while eliminated in displays with LED backlight completely. Visit Philips @ http://www.asimpleswitch.com/global/ to learn more.

















Specifications

Connectivity

- Signal Input: VGA (Analog), DVI-D (digital, HDCP)
- Sync Input: Separate Sync, Sync on Green

Picture/Display

- Panel Size: 31.5 inch / 80 cm
- Aspect ratio: 16:9
- LCD panel type: IPS-ADS LCD
- Backlight type: W-LED system
- Pixel pitch: 0.364 x 0.364 mm
- Optimum resolution: 1920 x 1080 @ 60Hz
- Brightness: 300 cd/m²
- Display colors: 16.7M
- Contrast ratio (typical): 1,200:1
- SmartContrast: 20,000,000:1
- Response time (typical): 6.5 (Gray to Gray) ms
- Viewing angle: 178° (H) / 178° (V), @ C/R > 20
- Picture enhancement: SmartImage
- Effective viewing area: 698.4 (H) x 392.85 (V)
- Scanning Frequency: 30 83 kHz (H) / 56 75 Hz
- sRGB
- SmartResponse (typical): 3 ms (Gray to Gray)

Convenience

- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 7, Windows 8
- User convenience: Power On/Off, 4:3 / Wide, Input, Menu, SmartImage
- OSD Languages: Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian, Brazil Portuguese, Czech
- Other convenience: Kensington lock, VESA mount (100x100mm)

Power

• ECO mode: 22.21 W (typ.)

- Power supply: Built-in, 100-240VAC, 50-60Hz
- Off mode: <0.5 W (typ.)
- On mode: 46.72 W (typ.)
- Standby mode: <0.5 W (typ.)
- Power LED indicator: Operation White, Standby mode- White (blinking)

Dimensions

- Packaging in mm (WxHxD): 863 x 581 x 186 mm
- Product without stand (mm): 726 x 435 x 88 mm
- Product with stand(max height): 726 x 495 x 180 mm

Weight

- Product with packaging (kg): 8.29 kg
- Product with stand (kg): 6.00 kg
- Product without stand (kg): 4.90 kg

Operating conditions

- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- Temperature range (operation): 0°C to 40°C °C
- MTBF: 30,000 hour(s)
- Relative humidity: 20%-80 %
- \bullet Temperature range (storage): -20°C to 60°C °C

Sustainability

- Environmental and energy: EnergyStar 6.0, RoHS
- Recyclable packaging material: 100 %
- Specific Substances: Mercury free

Compliance and standards

• Regulatory Approvals: CCC, WEEE, CEL, BSMI

Cabinet

- Finish: Texture
- Foot: Black
- Front bezel: Black
- Rear cover: Black



Issue date 2024-03-24

© 2024 Koninklijke Philips N.V. All Rights reserved.

Version: 1.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 73914 0 www.philips.com

* Smart response time is the optimum value from either GtG or GtG (BW) tests.