



Philips Evnia Gaming
Monitor
4K UHD gaming monitor

Evnia 5000

32 (31.5" / 80 cm diag.)
3840 x 2160 (4K UHD)

32M1N5800A

Feel your game

This Philips gaming monitor brings games to life with its 4K IPS display and DisplayHDR 400. Rapid 144Hz refresh rate, 1ms response time and Sync technology guarantee smooth visuals.

Features designed for you

- MultiView enables simultaneous dual connection and view
- 1ms (MPRT) fast response for crisp image and smooth gameplay
- SIAA certified antibacterial treatment to keep sanitary

Best synchronization between GPU and monitor

- AMD FreeSync™ Premium; tear free, stutter free, fluid gaming
- Certified NVIDIA® G-SYNC® compatible for smooth fast gaming

Meet the most recent update of HDMI specification

- Low input lag reduces time delay between devices to monitor
- 144Hz refresh rates for ultra-smooth, brilliant images
- SmartImage HDR gives optimal viewing from your HDR content
- UltraClear 4K UHD (3840x2160) resolution for precision

Immersive visuals

- IPS LED wide view technology for image and color accuracy
- Ultra Wide-Color wider range of colors for a vivid picture

E V N I A

PHILIPS

4K UHD gaming monitor
Evnia 5000 32 (31.5" / 80 cm diag.), 3840 x 2160 (4K UHD)

Highlights

AMD FreeSync™ Premium



Gaming shouldn't be a choice between choppy gameplay or broken frames. AMD FreeSync™ Premium equips serious gamers with a fluid, tear-free gameplay experience at peak performance. There are no compromises, game confidently with a high refresh rate, low framerate compensation, and low latency.

NVIDIA® G-SYNC® compatible



When playing intense games with high refresh rates, screen tearing may appear without optimal graphics synchronization. This Philips display is certified as NVIDIA® G-SYNC® compatible, reducing screen tearing and syncing your monitor's refresh rate with your graphic card's output for a smoother gaming experience. Scenes appear instantly, objects look sharper, and gameplay is smooth, giving you a stunning visual experience and a serious competitive edge.

UltraClear 4K UHD resolution



These Philips displays utilize high performance panels to deliver UltraClear, 4K UHD (3840 x 2160) resolution images. Whether you are demanding professional requiring extremely detailed images for CAD solutions, using 3D graphics applications or a financial wizard working on huge spreadsheets, Philips displays will make your images and graphics come alive.

144Hz Gaming



You play intense, competitive gaming. You demand display with lag free, ultra-smooth images. This Philips display redraws the screen image up-to 144 times per second, effectively 2.4x faster than a standard display. A lower frame rate can make enemies appear to jump from spot to spot on the screen, making them difficult targets to hit. With 144Hz frame rate, you get those critical missing images on the screen which shows enemy movement in ultra-smooth motion so you can easily target them.

32M1N5800A/27


With ultra-low input lag and no screen tearing, this Philips display is your perfect gaming partner

1ms MPRT fast response



MPRT (motion picture response time) is more intuitive way to describe the response time, which directly refers the duration from seeing blurry noise to clean and crisp images. Philips gaming monitor with 1 ms MPRT effectively eliminates smearing and motion blur, delivers shaper and precise visuals to enhance gaming experience. Best choice for playing thrilling and twitch-sensitive games.

Low Input Lag



Input lag is the amount of time that elapses between performing an action with connected devices and seeing the result on screen. Low input lag reduces the time delay between entering a command from your devices to monitor, greatly improve on playing twitch-sensitive video games, particularly important to whom plays fast-paced, competitive games.

AMD
FreeSync
Premium

NVIDIA
G-SYNC

144Hz

1ms
Fast Response
1ms MPRT

Low Input Lag

SIAA
ISO 22196
Anti Bacteria

Ultra Wide Color

144Hz

Flicker-free

VESA CERTIFIED
DisplayHDR 400

Specifications

Connectivity

- Signal Input: HDMI 2.1 x 2, DisplayPort 1.4 x 2
- Sync Input: Separate Sync
- Audio (In/Out): Audio out
- USB: USB-B x 1 (upstream), USB 3.2 Gen 1 x 4 (downstream with 2 fast charge B.C 1.2)
- HDCP: HDCP 1.4 (HDMI / DP); HDCP 2.2 (HDMI / DP)

Picture/Display

- Panel Size: 31.5 inch / 80 cm
- Aspect ratio: 16:9
- LCD panel type: IPS technology
- Backlight type: W-LED system
- Pixel pitch: 0.181 x 0.181 mm
- Brightness: 500 cd/m²
- Display colors: Color support 1.07 billion colors
- Color gamut (typical): NTSC 113%*, sRGB 124%*, Adobe RGB 87.5%*
- Contrast ratio (typical): 1000:1
- SmartContrast: Mega Infinity DCR
- Response time (typical): 1 ms (Gray to Gray)*
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- Picture enhancement: SmartImage game
- Maximum resolution: 3840 x 2160 @ 144 Hz
- Effective viewing area: 697.344 (H) x 392.2344 (V)
- Scanning Frequency: 30 - 255 kHz (H) / 48 - 144 Hz (V)
- sRGB
- Delta E: < 2 (sRGB)
- Flicker-free
- Pixel Density: 139.87 PPI
- LowBlue Mode
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
- SmartUniformity: 93 ~ 105%
- MPRT: 1 ms
- Low Input Lag
- EasyRead
- AMD FreeSync™ technology: Premium
- G-SYNC: Compatible (DP)*
- HDR: DisplayHDR 400 certified

Convenience

- Built-in Speakers: 5 W x 2
- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7
- User convenience: Power On/Off, Menu/OK, Input/Up, Game Settings/Down, SmartImage game/Back
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian
- Other convenience: Kensington lock, VESA mount (100x100mm)
- MultiView: PBP (2x devices)

Stand

- Height adjustment: 130 mm

- Pivot: +/- 90 degree
- Swivel: +/- 45 degree
- Tilt: -5/20 degree

Power

- Power supply: Internal, 100-240VAC, 50-60Hz
- Off mode: 0.3 W (typ.)
- On mode: 64.0 W (typ.)
- Standby mode: 0.5 W (typ.)
- Power LED indicator: Operation - White, Standby mode- White (blinking)

Dimensions

- Packaging in mm (WxHxD): 930 x 526 x 186 mm
- Product without stand (mm): 715 x 420 x 60 mm
- Packaging in inch (WxHxD): 36.3 x 20.7 x 7.3 inch
- Product without stand in inch: 28.1 x 16.5 x 2.4 inch
- Product with stand(max height): 715 x 640 x 297 mm
- Product with stand(max height): 28.1 x 25.2 x 22.7 inch

Weight

- Product with packaging (kg): 15.37 kg
- Product with stand (kg): 10.55 kg
- Product with packaging (lb): 33.81 lb
- Product with stand (lb): 23.21 lb
- Product without stand (kg): 7.74 kg
- Product without stand (lb): 17.03 lb

Operating conditions

- Altitude: Operation: +12,000ft (3,658m), Non-operation: +40,000ft (12,192m)
- Temperature range (operation): 0°C to 40 °C
- MTBF: 50,000 (Excluded backlight) hour(s)
- Relative humidity: 20%-80 %
- Temperature range (storage): -20°C to 60 °C

Sustainability

- Environmental and energy: RoHS
- Recyclable packaging material: 100 %
- Specific Substances: Mercury free, PVC / BFR free housing, SIAA

Compliance and standards

- Regulatory Approvals: CB, CE Mark, FCC Class B, ICES-003, CU-EAC, EAEU RoHS, TUV/ISO9241-307, TUV-BAUART, cETLus

Cabinet

- Color: Black
- Finish: Textured

What's in the box?

- Cables: HDMI cable, DisplayPort cable, USB upstream cable, Power cable
- Monitor with stand
- User Documentation

Issue date 2024-03-25

© 2024 Koninklijke Philips N.V.
All Rights reserved.

Version: 6.0.1

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

UPC: 6 09585 25516 6

www.philips.com

* "IPS" word mark / trademark and related patents on technologies belong to their respective owners.

* For best output performance, please always ensure that your graphic card is capable of achieving the maximum resolution and refresh rate of this Philips display.

* Response time value equal to SmartResponse

* MPRT is to adjust brightness for blur reduction, so cannot adjust brightness while MPRT is turned on. To reduce motion blur, LED backlight will strobe synchronously with screen refresh, which may cause noticeable brightness change.

* MPRT is gaming-optimized mode. Turn on MPRT may cause noticeable screen flickering. It is recommended to turn off when you are not using the gaming function.

* NTSC Area based on CIE1976

* sRGB Area based on CIE1931

* Adobe RGB Coverage based on CIE1976

* NVIDIA® G-SYNC® support interface: DisplayPort

* Make sure to update NVIDIA® G-SYNC® driver to the latest version, see more information on NVIDIA website: <https://www.nvidia.com/>

* Make sure your graphic card supports NVIDIA® G-SYNC®

* 2020 Advanced Micro Devices, Inc. All rights reserved. AMD, the AMD Arrow logo, AMD FreeSync™ and combinations thereof are trademarks of Advanced Micro Devices, Inc. Other product names used in this publication are for identification purposes only and may be trademarks of their respective companies.

* The monitor may look different from feature images.