Philips LCD monitor with LED backlight



V Line 15.6" / 39.6 cm

163V5LSB2

Great LED images in vivid colors

Enjoy vivid LED pictures on this Philips display. Compact design and VESA mount allow your workspace flexibility, it's a great choice!

Vivid pictures every time

• LED technology for vivid colors

Great choice

- Compact design saves space
- VESA mount allows for flexibility
- Mercury Free eco-friendly display



Specifications

Picture/Display

- LCD panel type: TFT-LCD
- Backlight type: W-LED system
- Panel Size: 15.6 inch / 39.6 cm
- Effective viewing area: 344.2 (H) x 193.5 (V)
 Display Screen Coating: Glare, 3H
- Aspect ratio: 16:9
- Optimum resolution: 1366 x 768 @ 60 Hz
- Response time (typical): 12 ms
- Brightness: 220 cd/m²
- Contrast ratio (typical): 500:1
- Pixel pitch: 0.252x 0.252 mm
- Viewing angle: 90° (H) / 60° (V), @ C/R > 10
- Display colors: 262K
- Scanning Frequency: 30 -60 kHz (H) / 58 -62 Hz (V) sRGB

Connectivity

- Signal Input: VGA (Analog)
- Sync Input: Separate Sync, Sync on Green

Convenience

- User convenience: Power On/Off
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Turkish, Traditional Chinese, Ukrainian
- Other convenience: Kensington lock, VESA mount $(100 \times 100 \text{ mm})$
- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7

Stand

• Tilt: -3/10 degree





Power

- On mode: 6.97 W (typ.)
- Standby mode: 0.5 W
- Off mode: 0.5 W
- Power LED indicator: Operation White, Standby
- mode- White (blinking) • Power supply: Built-in, 100-240VAC, 50-60Hz

Dimensions

- Product with stand (mm): 375 x 300 x 141 mm
- Product without stand (mm): 375 x 233 x 47 mm
- Packaging in mm (WxHxD): 422 x 311 x 115 mm

Weight

- Product with stand (kg): 0.94 kg
- Product without stand (kg): 0.79 kg
- Product with packaging (kg): 1.77 kg

Operating conditions

- Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Non-
- operation: +40,000ft (12,192m)
- MTBF: 30,000 hour(s)

Sustainability

- · Environmental and energy: RoHS, Mercury Free
- Recyclable packaging material: 100 %

Compliance and standards

VESA Mount

• Regulatory Approvals: CCC, WEEE

Cabinet

Hg Free

- Color: Black
- Finish: Hairline (front bezel) / Texture (rear cover)





163V5LSB2/93

Highlights

LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of LCD backlight, resulting in super high contrast ratio. It also gives superior color reproduction thanks to consistent brightness across the screen.

Mercury Free

Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.