

Philips LED-backlit LCD monitor

E Line

24 (Viewable 23.6"/59.9 cm) 1920 x 1080 (Full HD)

247E6QDAD

# Vivid colours, crisp details

### in an elegant design

This brilliant IPS-ADS display offers stunning visuals wrapped in an elegance-inspired design for a light and fresh display in any home or office.

#### **Elegant Design**

- Elegant, slim design complements your home decor
- Superb black cherry glossy finish
- Modern Touch controls complement the design

### **Superb Picture Quality**

- SmartControl Lite: For quick and easy display tuning
- · SmartImage Lite for easy optimised image settings
- SmartContrast for deep black level details
- 16:9 Full HD display for crisp, detailed images
- · IPS-ADS wide-view technology for image and colour accuracy

### Experience immersive multimedia

- Built-in 3 x 2-watt RMS speakers
- · HDMI-ready for Full HD entertainment
- MHL technology for enjoying mobile content on a big screen



## Highlights

#### **IPS-ADS** technology



IPS-ADS displays use an advanced technology which gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS-ADS displays give you remarkably crisp images with vivid colours, making them ideal not only for photos, movies and web browsing, but also for professional applications which demand colour accuracy and consistent brightness at all times.

#### 16:9 Full HD display



The Full HD screen has the widescreen resolution of  $1920 \times 1080p$ . This is the highest resolution of HD sources for the best possible picture quality. It is fully future-proof as it supports 1080p signals from all sources, including the most recent sources such as Bluray and advanced HD game consoles. The signal processing is extensively upgraded to support this much higher signal quality and resolution. It produces brilliant flicker-free progressive scan pictures with superb brightness and colours.

#### **SmartImage Lite**

SmartImage Lite is an exclusive, leading edge Philips technology that analyses the content displayed on your screen. Based on a scenario you select, SmartImage Lite dynamically enhances the contrast, colour saturation and

sharpness of images and videos for ultimate display performance - all in real time with the press of a single button.

#### **SmartControl Lite**

SmartControl Lite is the next generation 3D icon-based GUI monitor control software. This allows the user to fine-tune most parameters of the monitor like Colour, Brightness, screen calibration, Multimedia, ID management etc. with the mouse.

#### **SmartContrast**



SmartContrast is a Philips technology that analyses the contents you are displaying, automatically adjusting colours and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

#### **Modern Touch controls**



Touch controls are intelligent, touch-sensitive icons that replace protruding buttons so the user can adjust the monitor to their requirements. Responding to your lightest touch, touch controls give the monitor a modern feel.

#### **MHL** technology



Mobile High Definition Link (MHL) is a mobile audio/video interface for directly connecting mobile phones and other portable devices to high-definition displays. An optional MHL cable allows you to simply connect your MHL capable mobile device to this large Philips MHL display, and watch your HD videos come to life with full digital sound. Now not only you can enjoy your mobile games, photos, movies or other apps on its big screen, you can simultaneously charge your mobile device so you never run out of power halfway.

#### **HDMI Ready**



HDMI-ready

An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. An HDMI cable enables high-quality digital video and audio to be transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

#### Built-in 3 x 2-watt RMS speaker

Now you can enjoy all your multimedia and social applications with stereo sound. These built-in speakers not only sound great, but also help you to get rid of external wire clutter and save valuable desktop space.



















### **Specifications**

#### Picture/Display

- Panel Size: 23.6 inch/59.9 cm
- Aspect ratio: 16:9
- LCD panel type: IPS-ADS LCD
- Backlight type: W-LED system
- Pixel pitch: 0.2715 x 0.2715 mm
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 250 cd/m<sup>2</sup>
- Display colours: 16.7 M
- Contrast ratio (typical): 1000:1
- SmartContrast: 20,000,000:1
- Response time (typical): 5 ms (Grey to Grey)\*
- Viewing angle: 178° (H)/178° (V), @ C/R > 10
- Picture enhancement: SmartImage Lite
- Effective viewing area: 521.28 (H) x 293.22 (V)
- Scanning Frequency: 30-83 kHz (H)/56-75 Hz (V)
- sRGB
- MHL: 1080P @ 60 Hz

#### **Connectivity**

- Signal Input: VGA (Analogue), DVI-D (digital, HDCP), MHL-HDMI (digital, HDCP)
- Sync Input: Separate Sync, Sync on Green
- Audio (In/Out): Headphone out, PC audio-in

#### Convenience

- Built-in Speakers:  $3 \text{ W} \times 2$
- · Plug and Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 7, Windows 8
- User convenience: Power On/Off, Menu, Volume, Input, SmartImage Lite
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
- Other convenience: Kensington lock

#### **Stand**

• Tilt: -5/20 degree

#### **Power**

- Power supply: External, 100–240 VAC, 50–60 Hz
- Off mode: 0.3 W (typ.)
- On mode: 16.23 W (typ.) (EnergyStar 6.0 test method)
- Standby mode: 0.5 W (typ.)
- · Power LED indicator: Operation White, Standby mode - White (flashing)

#### **Dimensions**

- Product with stand (mm): 561 x 429 x 212 mm
- Packaging in mm (W  $\times$  H  $\times$  D): 598  $\times$  490  $\times$  100 mm
- Product without stand (mm):  $561 \times 347 \times 43 \text{ mm}$

#### Weight

- Product with packaging (kg): 4.90 kg
- Product with stand (kg): 3.65 kg
- Product without stand (kg): 3.27 kg

#### **Operating conditions**

- Altitude: Operation: +12,000 ft (3658 m), Nonoperation: +40,000 ft (12,192 m)
- Temperature range (operation): 0°C to 40°C °C
- MTBF: 50,000 (excluding backlight) hour(s)
- Relative humidity: 20%-80 %
- Temperature range (storage): -20°C to 60°C °C

#### Sustainability

- Environmental and energy: EnergyStar 6.0, RoHS, Mercury Free
- Recyclable packaging material: 100 %

#### Compliance and standards

• Regulatory Approvals: BSMI, CE Mark, cETLus, FCC Class B, GOST, PSB, SASO, SEMKO, TUV/ ISO9241-307, WEEE

- · Colour: Black Cherry
- · Finish: Glossy



Issue date 2024-10-28

EAN: 87 12581 74184 6

Version: 2.0.1

© 2024 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

- \* This Philips display is MHL-certified. However, if your MHL device does not connect or work correctly, check with your MHL device FAQ or vendor directly for instructions. The policy of your device manufacturer may require you to purchase its brand-specific MHL cable or adapter in order for it to work
- \* Requires optional MHL-certified mobile device and MHL cable (not included). Please check with your MHL device vendor for compatibility.
  Standby/Off energy saving of ErP is not applicable for the MHL
- charging functionality
  For a complete list of MHL-enabled products, refer to www.mhlconsortium.org
  "IPS" word mark / trademark and related patents on technologies
- belong to their respective owners.

  \* Response time value equal to SmartResponse