

Philips LCD widescreen monitor

56 cm (22") w V-line Format 16:10

220V1SB

Widescreen display offering good value

With features like DVI and VGA inputs, SmartContrast and Energy efficiency, the 220V1 offers good value.

High-quality picture

- WSXGA+, wide format 1680 x 1050 resolution for sharper display
- 5 ms fast response time
- SmartContrast: For incredible rich black details

Great convenience

- Dual input accepts both analogue VGA and digital DVI signals
- Easy picture format control switching between wide and 4:3 formats
- · Screen tilts to your ideal, individualised viewing angle

Environmentally friendly green design

- Eco-friendly materials that meet international standards
- \bullet Complies with RoHS standards of care for the environment
- EPEAT Silver ensures lower impact on environment



Highlights

Eco-friendly materials

"Philips is committed to using sustainable, ecofriendly materials across its monitor range. All body plastic parts, metal chassis parts and packing materials use 100% recyclable materials. In some selected models we utilise up to 65% post-consumer recycled plastics. Strict adherence to RoHS standards ensures substantial reduction or elimination of toxic substances like lead, for example. Mercury content in monitors with CCFL backlights has been reduced significantly and eliminated completely in monitors with LED backlights. Visit Philips at http://www.asimpleswitch.com/global/ to learn more.

Dual input





DVI connector

Dual input provides connectors to accommodate input of both analogue VGA and digital DVI signals.

Easy picture format control





Philips easy picture format control on OSD switches from the 4:3 aspect ratio to the widescreen mode and back again to match the display's aspect ratio with your content; it allows you to work with wide documents without scrolling or viewing widescreen









© 2019 Koninklijke Philips N.V. Issue date 2019-05-10

Version: 5.0.7

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 000 53402 EAN: 87 12581 48655 6

www.philips.com

All Rights reserved.

Specifications

Picture/Display

media in the widescreen mode and gives you

Adjustable tilt

environment.

EPEAT Silver

status in your country.

distortion-free, native mode display of 4:3 ratio

Adjustable tilt is backward and forward movement of

a screen on its base to achieve custom positioning

for an ideal viewing angle and more comfort for

Philips designs and produces display products in

compliance with strict Restriction of Hazardous Substances (RoHS) standards that restrict lead and

Philips EPEAT Silver certified monitors ensure

EPEAT programme helps purchasers evaluate,

environmental criteria supported by the US EPA.

WSXGA+, wide format 1680 x 1050

5 ms on/off response time

Wide format, super extended graphics array is a

display specification that is capable of displaying 1680 x 1050 resolution or approximately 1.7 million

On-Off response time is the period required for a

measured in milliseconds. Faster is better: lower response time means faster transitions and,

(white) and back to active (black) again. It is

liquid crystal cell to go from active (black) to inactive

therefore, results in fewer visible image artefacts in

the display of transition of texts and graphics. On-Off

response time is a more important measure in the

display of business content like documents, graphs

EPEAT Silver is valid only where Philips registers the

product. Please visit www.epeat.net for registration

compare and select Monitors based on 51

protection for human health and the environment, and are highly energy efficient ensuring low

emissions of climate changing green house gases. The

people who spend long hours working on the

Compliant with RoHS standards

other toxic substances that can harm the

- LCD panel type: TFT-LCD
- Panel Size: 22 inch/55.9 cm
- Aspect ratio: 16:10
- Pixel pitch: 0.282 x 0.282
- Brightness: 250 cd/m²
- SmartContrast: 20000:1
- Contrast ratio (typical): 1000:1
- Response time (typical): 5 ms
- Optimum resolution: 1680 x 1050 @ 60 Hz
- Viewing angle: 176° (H)/170° (V), @ C/R > 5
- Display colours: 16.7 M
- Scanning Frequency: 30 83 kHz (H)/56 -75 Hz (V)

Connectivity

- Signal Input: VGA (Analogue), DVI-D
- · Sync Input: Separate Sync, Sync on Green

Convenience

- User convenience: Brightness, Menu, Input, Auto, Power On/Off
- OSD Languages: English, French, German, Spanish, Italian, Russian, Simplified Chinese, Portuguese,
- Other convenience: VESA mount (100 x 100 mm), Kensington lock
- Plug and Play Compatibility: DDC/CI, Windows 98/2000/XP/Vista, sRGB

Stand

• Tilt: -5/+20 degree

Power

- On mode: 29.8 W
- Standby mode: <0.5 W
- Off mode: < 0.5 W
- · Power LED indicator: Operation green, Standby/ sleep - Amber
- Power supply: Built-in, 100-240 VAC, 50/60 Hz

Dimensions

- Product with stand (mm): 506 x 403 x 205 mm
- Product without stand (mm): $506 \times 347 \times 62 \text{ mm}$
- Packaging in mm (W \times H \times D): 453 \times 570 \times 140 mm

Weight

- · Product with stand (kg): 4.53 kg
- Product without stand (kg): 4.17 kg
- Product with packaging (kg): 6.29 kg

Operating conditions

- Temperature range (operation): 0-40 °C
- Temperature range (storage): -20 to 60 °C
- Relative humidity: 20%–80% %
- MTBF: 50,000 hour(s)

Sustainability

- · Environmental and energy: EPEAT Silver, RoHS, EnergyStar 5.0
- Recyclable packaging material: 100 %

Compliance and standards

Regulatory Approvals: CE Mark, FCC, Class B, UL/

Cabinet

- · Colour: Black
- Finish: Texture

