

### Philips Signage Solutions Q-Line Display

**43"** Direct LED Backlight Ultra HD

# **Signage**Solutions



## 43BDL3511Q

# Stand out

# Easy-setup 18/7 display.

Inform and enthrall with a Philips Q-Line Professional Ultra HD Display. This reliable solution can be up and running as quickly as you need.

### Effortless setup. Total control.

- Operate, monitor and maintain with CMND & Control
- Schedule what you want, when you want with SmartPlayer

### **Cost-effective system solution**

- Energy-saving automatic backlight control
- Integrated media player. Easily schedule USB content
- FailOver ensures content is always playing
- Easy control. Remotely manage networked displays

### Superb picture. Ultra-high brightness.

• Ultra-HD. Rich images. Stunning contrast



# Highlights

#### **CMND & Control**



Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

#### FailOver



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs ensuring content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure your business is always on.

#### Integrated media player

Easily schedule content to play from USB. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback is done.

#### **SmartPlayer**



Turn your USB into a true cost effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display.Create your playlist and schedule your content via the on screen menu, and enjoy your own created playlists anytime, anywhere.





# Specifications

#### **Picture/Display**

- Diagonal screen size: 42.5 inch / 108 cm
- Panel resolution: 3840 x 2160
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 400 cd/m<sup>2</sup>
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Aspect ratio: 16:9
- Viewing angle (H / V): 178 / 178 degree
- Pixel pitch: 0.2451 x 0.2451 mm
- Display colors: 1.07 Billion
- Panel technology: IPS
- Contrast ratio (typical): 1200:1
- Clinical image: D-Image preset (dicom part 14 compatible)

Refresh rate 60, 67, 72, 75Hz

56, 60, 72, 75Hz

70Hz

75Hz 60, 70, 75Hz

75Hz

75Hz

60Hz

60Hz

60Hz

60Hz

60Hz

60Hz

60Hz

60Hz

60Hz

50Hz

50Hz

60Hz

30Hz

60Hz

50, 60Hz

50, 60Hz

• Video input: DVI-I (x 1), HDMI 2.0 (x2), USB 2.0

• External control: IR (in/out) 3.5 mm jack, R|45,

• Placement: Landscape (18/7), Portrait (18/7)

• Signal loop through: RS232, IR Loopthrough

· Energy saving functions: Smart Power

30. 60Hz

Refresh rate

• Haze: 1%

Resolution

640 x 480

720 x 400

 $800 \times 600$ 

832 x 624

1024 x 768

1152 x 864

1152 x 870

1280 x 720

1280 × 800

1280 x 1024

1600 x 1200

1680 x 1050

1920 x 1080

3840 x 2160

 Video formats Resolution

480i

480p

576p

576i

720p

1080i

1080p 3840 x 2160

(x2)

3840 x 2160

Connectivity

Convenience

Audio input: 3.5 mm jack

• Audio output: 3.5mm jack

RS232C (in/out) 2.5 mm jack

• Tiled Matrix: Up to 10 x 15

 $1440 \times 900$ 

## Supported Display Resolution Computer formats

- PowerConsumption (Typical): 105 W
- Consumption (Max): 155 W
- Standby power consumption: <0.5 W

Network controllable: RS232, RI45

• Remote control signal: Lockable

**Operating conditions** 

Altitude: 0 ~ 3000 m
MTBF: 50,000 hour(s)

(No condensation)

condensation)

on source

· Keyboard control: Hidden, Lockable

· Start-up: Switch on delay, Switch on status, Boot

Start-up window: enable / disable Philips logo

Temperature range (operation): 0 ~ 40 °C

• Temperature range (storage): -20 ~ 60 °C

• Humidity range (operation)[RH]: 20 ~ 80% RH

• Humidity range (storage) [RH]: 5 ~ 95% RH (No

- Mains power: 100 240V~, 50/60Hz
- Power Saving Features: Smart Power
- Energy Label Class: G

#### Sound

• Built-in speakers: 2 x 10W RMS

#### Accessories

- Stand: BM05922(optional)
- Included Accessories: IR sensor cable (1.8 m) (x1), Philips logo (x1), AC power cord, AC Switch Cover, Quick start guide (x1), Remote control & AAA batteries, RS232 daisy chain cable (x1), USB Cover and screw x1, Wire Clamper (x3)

#### **Miscellaneous**

- On-Screen Display Languages: Arabic, English, French, German, Italian, Japanese, Polish, Russian, Spanish, Simplified Chinese, Turkish, Traditional Chinese
- Regulatory approvals: CE, FCC, Class A, CB, BSMI, VCCI, CU, ETL, EMF, PSB
- Warranty: 3 year warranty

#### **Multimedia Applications**

- USB Playback Video: H.264, JPEG, MPEG, WMV3
- USB Playback Picture: BMP, JPEG, PNG
- USB Playback Audio: AAC, WMA, MPEG, HEAAC

#### Dimensions

- Set dimensions (W  $\times$  H  $\times$  D):
- 973.0 x 561.2 x 63.5 mm
- Set dimensions in inch (W x H x D): 38.31 x 22.09 x 2.50 inch
- Bezel width: 13.9 mm (Even bezel)
- Wall Mount: 200mm x 200mm , M6
- Product weight: 10.7 kg
- Product weight (lb): 23.59 lb

© 2023 Koninklijke Philips N.V.

or their respective owners.

www.philips.com



Version: 2.0.1

All Rights reserved. Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V.

12 NC: 8670 001 84548 EAN: 87 12581 79527 6

Issue date 2023-08-12

43BDL3511Q/75