PHILIPS

LCD monitor with SmoothTouch

B Line 22 (21.5"/54.6 cm diag.) 1920 x 1080 (Full HD)

222B1TC



Brilliant interactive display with SmoothTouch

A durable, anti-glare touchscreen for flexible use, with articulating stand to angle as you need. Advanced In-Cell Touch (AIT) offers a slimmer look, superior touch sensitivity for quick response, outstanding and clearer visibility.

Brilliant interactive display

- SmoothTouch display for natural, fluid touch response
- 16:9 Full HD display for crisp, detailed images
- EasyRead mode for a paper-like reading experience
- Less eye fatigue with Flicker-Free technology
- LowBlue Mode for easy-on-the-eyes productivity
- SmartContrast for rich black details

Easy to experience

- HDMI ensures universal digital connectivity
- DisplayPort connection for maximum visuals
- VESA mount allows for flexibility
- SmartStand with adjustable angles, boosts productivity

Highlights

SmoothTouch



This Philips display uses Projected capacitive 10point touch technology for fluid response. You can fully utilise the new capabilities of touchbased applications and bring your older applications to life. Touch-type with 10 fingers or play exciting interactive games with your friends. Collaborate with colleagues interactively at work or school environment and increase your productivity and efficiency.

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 x 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colours, expect a true-to-life picture.

SmartContrast



SmartContrast is a Philips technology that analyses the contents you are displaying, automatically adjusting colours and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave-length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, the Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

Flicker-Free technology



Due to the way brightness is controlled on LEDbacklit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-Free technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

SmartStand

Philips SmartStand allows for flexible adjustment of the screen. Its Z-type structure with smooth tilt, height adjustment and folding capabilities enables you to use it in various ergonomic positions. You can set the stand in upright position for better touch control or recline it backwards, making it easy for you to draw or annotate. It even allows you to put the screen almost flat on the table for some applications when required.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. An HDMI cable enables high-quality digital video and audio to be transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

DisplayPort connection



DisplayPort is a digital link from PC to monitor without any conversion. With higher capabilities than DVI standard, it is fully capable to support up to 15 metre cables and 10.8 Gbps/sec data transfer. With this high performance and zero latency, you get the fastest imaging and refresh rates — making DisplayPort the best choice for not only general office or home use, but also for the more demanding gaming and films, video editing and more. It also keeps interoperability in mind via the use of various adapters.















Specifications

Picture/Display Panel Size: 21.5 inch/54.6 cm Aspect ratio: 16:9 LCD panel type: IPS technology Backlight type: W-LED system Pixel pitch: 0.24795 x 0.24795 mm Brightness: 250 cd/m² Display colours: 16.7 M Colour gamut (typical): NTSC 85%*, sRGB 102%*, Adobe RGB 84%* Contrast ratio (typical): 1000:1 SmartContrast: 50,000,000:1 Response time (typical): 4 ms (Grey to Grey)* Viewing angle: 178° (H)/178° (V), @ C/R > 10 Picture enhancement: SmartImage Maximum resolution: 1920 x 1080 @ 75 Hz* Effective viewing area: 476.06 (H) x 267.79 (V) Scanning Frequency: VGA: 30 - 85 kHz (H)/48 -60 Hz (V); HDMI/DP: 30 - 85 kHz (H)/48 - 75 Hz (V) sRGB Flicker-free Pixel Density: 102 PPI LowBlue Mode Display Screen Coating: Anti-glare, 3H, Haze 25% EasyRead Adaptive sync

Touch

Operating system: Windows 10 Touch active area: 476.06 mm (H) x 267.79 mm (V) Touch interface: USB Touch method: Finger Touchpoints: 10 points Touch technology: Self capacitive Palm rejection area: >= 30 x 30 mm

Connectivity

Signal Input: VGA (Analogue), DisplayPort 1.2, HDMI 1.4 Sync Input: Separate Sync, Sync on Green

Audio (In/Out): PC audio-in, Headphone out USB:: USB 3.2 x 1 (Upstream); USB 3.2 x 3 (Downstream with 1 fast charge B.C 1.2)

Convenience

Built-in Speakers: 2 W x 2 Plug and Play Compatibility: DDC/CI, sRGB, Windows 10/8.1/8/7 User convenience: SmartImage, Input, Brightness, Menu, Power On/Off OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian Other convenience: Kensington lock, VESA mount (100 x 100 mm) Control software: SmartControl

Stand

Height adjustment: 184 (Horizontal), 85 (Vertical) mm Tilt: -5–90 degree Folding angle: 0–70 degrees

Power

ECO mode: 10.5 W (typ.) Power supply: Internal, 100–240 VAC, 50–60 Hz Off mode: Zero watts with Zero switch On mode: 13.1 W (typ.) (EnergyStar test method) Standby mode: 0.3 W (typ.) Power LED indicator: Operation - White, Standby mode - White (flashing) Energy Label Class: E

Dimensions

Packaging in mm (W x H x D): 585 x 400 x 138 mm Product without stand (mm): 489 x 294 x 52 mm Product with stand (max height): 489 x 384 x 227 mm

Weight

Product with packaging (kg): 8.27 kg Product with stand (kg): 6.13 kg Product without stand (kg): 2.79 kg

Operating conditions

Altitude: Operation: +12,000 ft (3658 m), Nonoperation: +40,000 ft (12,192 m) Temperature range (operation): 0°C to 40°C °C Relative humidity: 20%-80 % Temperature range (storage): -20°C to 60°C °C MTBF (demonstrated): 70,000 hrs (excluded backlight)



Environmental and energy: Energy Star 8.0, EPEAT*, TCO Certified Edge, RoHS Recyclable packaging material: 100 % Specific Substances: PVC/BFR free housing, Mercury free

Compliance and standards

Regulatory Approvals: CB, SEMKO, TUV/GS, TUV Ergo, CU-EAC, EAEU RoHS, CE Mark, ICES-003, FCC Class B, TUV Eye Comfort certified

Cabinet

Finish: Texture Foot: Black Front bezel: Black Rear cover: Black

What's in the box?

Cables: HDMI cable, DP cable, USB-A to B cable, Power cable Monitor with stand User Documentation

 \ast "IPS" word mark / trademark and related patents on

- technologies belong to their respective owners. * The maximum resolution works for either HDMI input or
- DP input.
- * Response time value equal to SmartResponse * NTSC Area based on CIE 1976
- * sRGB Area based on CIE 1976
- * Adobe RGB Coverage based on CIE 1931
- * Please refer to "SmoothTouch" in the user manual for more details on operating system support when using the touch function.
- * Fast charging complies with USB BC 1.2 standard
- * EPEAT rating is valid only where Philips registers the product. Please visit https://www.epeat.net/ for registration status in your country.
- * The monitor may look different from feature images.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

© 2025 Koninklijke Philips N.V.

All Rights reserved.

EAN: 87 12581 77677 0

Issue date 2025-05-29

Version: 2.2.1



