



**D-Line Display** 

Signage Solutions

75"

UHD (3840 x 2160)

500 cd/m<sup>2</sup>



75BDL4511D

# Say more

Smart, fast, 24/7 display.

Make it stand out with a fast Philips D-Line Professional 4K UHD display. Philips superb picture quality ensures true colours and intense contrast. You can effortlessly display content from multiple sources on a single screen.

# **Brilliant picture. Blazing processor speed.**

- Place in landscape or portrait orientation
- 4K UHD. Rich, deep images. Stunning contrast
- ADS wide-view panel display

# **Operational flexibility**

- Optional OPS Slot
- SmartPower for energy saving

# **Cost-effective system solution**

- Energy-saving automatic backlight control
- FailOver ensures that content is always playing

# **Effortless setup. Total control.**

- Operate, monitor and maintain with CMND and Control
- Schedule what you want, when you want with SmartPlayer

D-Line Display 75BDL4511D/00

# Highlights

# **ADS** wide-view panel display

Be seen from any angle with ADS wide-view technology. Advanced Super Dimension Switch delivers faster on-display picture processing for smoother content transitions, remarkable image accuracy and superior colour reproduction with 180 degree viewing.

## **CMND** and Control



Run your display network over a local (LAN) connection. CMND and Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

## **FailOver**



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips
Professional Display switch automatically between primary and secondary inputs, ensuring that content keeps playing even if the primary source goes down. Simply set a list of alternative inputs to be sure your business is always on.

#### **SmartPower**



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

# **SmartPlayer**



Turn your USB into a true cost-effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on-screen menu, and enjoy your own playlists anytime, anywhere.









D-Line Display 75BDL4511D/00

# Specifications

#### **Picture/Display**

Diagonal screen size (metric): 189.3 cm Diagonal screen size (inch): 74.5 inch

Aspect ratio: 16:9

Panel resolution: 3840 x 2160 Pixel pitch: 0.4296 x 0.429 6 mm

Optimum resolution: 3840 x 2160 @ 60 Hz

Brightness: 500 cd/m<sup>2</sup>
Display colours: 1.07 Billion
Contrast ratio (typical): 1200:1
Dynamic contrast ratio: 500,000:1
Response time (typical): 8 ms
Viewing angle (horizontal): 178 degree

Viewing angle (vertical): 178 degree

Panel technology: ADS

Haze: 25%

## **Connectivity**

Audio output: 3.5 mm jack

Video input: Display Port1.2 (x 1), DVI-I (x 1),

HDMI 2.0 (x 3), USB 2.0 (x 2) Audio input: 3.5 mm jack Other connections: OPS

Video output: DisplayPort 1.2 (x 1), HDMI 2.0

(x 1)

External control: IR (in/out) 3.5 mm jack, RJ45,

RS232C (in/out) 2.5 mm jack

## Convenience

Placement: Landscape (24/7), Portrait (24/7) Screen-saving functions: Pixel Shift, Low Bright

Keyboard control: Hidden, Lockable

Signal loop through: DisplayPort, RS232, HDMI,

IR Loop through

Energy-saving functions: Smart Power Network controllable: RS232, RJ45

## Sound

Built-in speakers: 2 x 10 W RMS

## Power

Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz Consumption (Typical): 185 W Consumption (Max): 345 W

Standby power consumption: <0.5 W

**Energy Label Class: G** 

## **Supported Display Resolution**

Computer formats: 640 x 480, 60 Hz, 800 x 600, 60 Hz, 1024 x 768, 60 Hz, 1280 x 720, 60 Hz, 1280 x 1024, 60 Hz, 1440 x 900, 60 Hz, 1600 x 900, 60 Hz, 1680 x 1050, 60 Hz, 1920 x 1080, 60 Hz, 3840 x 2160, 30, 60 Hz

Video formats: 480i, 60 Hz, 480p, 60 Hz, 576p, 50 Hz, 576i, 50 Hz, 720p, 50,60 Hz, 1080i, 50, 60 Hz, 1080p, 50, 60 Hz, 2160p, 24, 30, 60 Hz

#### **Dimensions**

Set Width: 1683.5 mm Product weight: 35.9 kg Set Height: 961.7 mm

Set Depth: 69.5 (@Wall mount)/

91.8 (@Handle) mm

Set Width (inch): 66.28 inch
Set Height (inch): 37.86 inch
Wall Mount: 600(H)x400(V) mm, M8
Set Depth (inch): 2.74 inch (wall mount)/

3.61 (@Handle) inch

Bezel width: 14.9 mm (Even bezel) Product weight (lb): 79.15 lb

## **Operating conditions**

Altitude: 0 ~ 3000 m

Temperature range (operation): 0 ~ 40 °C

MTBF: 50,000 hour(s)

Temperature range (storage): -20 ~ 60 °C Humidity range (operation)[RH]: 20–80% RH

(No condensation)

Humidity range (storage) [RH]: 5-95% RH (No

condensation)

## **Multimedia Applications**

USB Playback Video: H.263, H.264, H.265, MPEG USB Playback Picture: BMP, JPEG, PNG USB Playback Audio: AAC, MPEG, HEAAC

## Accessories

Included Accessories: AC Switch Cover, Philips logo (x 1), RS232 daisy-chain cable, AC power cord, IR sensor cable (1.8 m) (x 1), Quick start guide (x 1), Remote control and AAA batteries, RS232 cable, USB Cover and screw x 1, Wire Clamper (x 3)

#### Miscellaneous

On-Screen Display Languages: Arabic, Dutch, Danish, English, French, Finnish, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Simplified Chinese, Turkish, Traditional Chinese Warranty: 3 year warranty Regulatory approvals: CE, FCC, Class A, CCC, ROHS, CB, BSMI, EMF, VCCI, PSB, EnergyStar 8.0, ETL. CECP. EAC

© 2025 Koninklijke Philips N.V. All Rights reserved.

Issue date 2025-12-05

Version: 3.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 77868 2



www.philips.com