

Philips LCD monitor

**S Line** 24 (Viewable 23.6"/59.9 cm) Full HD (1920 x 1080)

243S5LSB

# Essential features, efficient performance

# for maximum productivity

The Philips LED display using PVC, BFR-free housing is ideal for eco-friendly productivity

### Vivid pictures every time

- LED technology for vivid colours
- SmartContrast for rich black details
- 16:9 Full HD display for crisp, detailed images

#### **Great choice**

- Compact design saves space
- Mercury Free eco-friendly display
- VESA mount allows for flexibility



#### 243S5LSB/00

#### LCD monitor S Line 24 (Viewable 23.6"/59.9 cm), Full HD (1920 x 1080)

# Highlights

#### LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content, which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of the LCD backlight, resulting in a super high contrast ratio. It also gives superior colour reproduction thanks to consistent brightness across the screen.

**SmartContrast** 



SmartContrast is a Philips technology that analyses the contents you are displaying,

automatically adjusting colours and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

### 16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 x 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colours, expect a true-to-life picture.

### **Mercury Free**

Philips monitors with LED backlighting are free from Mercury, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its lifecycle, from manufacturing to disposal.

### **Compact design saves space**

Compact design saves space

# **VESA** mount

VESA mount allows for flexibility















# Specifications

#### Connectivity

- Signal Input: VGA (Analogue), DVI-D (digital, HDCP)
- Sync Input: Separate Sync, Sync on Green

#### **Picture/Display**

- Panel Size: 23.6 inch/59.9 cm
- Aspect ratio: 16:9
- LCD panel type: TFT-LCD
- Backlight type: W-LED system
- Pixel pitch: 0.272 x 0.272 mm
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 250 cd/m<sup>2</sup>

Convenience

(100 x 100 mm)

• Tilt: -5/20 degree

• Off mode: 0.5 W (typ.)

Stand

Power

- Display colours: 16.7 M
- Contrast ratio (typical): 1000:1
- SmartContrast: 10,000,000:1
- Response time (typical): 5 ms
- Viewing angle: 170° (H)/160° (V), @ C/R > 10
- Effective viewing area: 521.28 (H) × 293.22 (V)
- Scanning Frequency: 30-83 kHz (H) / 56-76 Hz (V) sRGB

• Plug and Play Compatibility: DDC/Cl, Mac OS X,

• OSD Languages: Brazil Portuguese, Czech, Dutch,

Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian

• Other convenience: Kensington lock, VESA mount

• Power supply: Built-in, 100-240 VAC, 50-60 Hz

• On mode: 16.7 W (typ.) (EnergyStar 6.0 test

sRGB, Windows 7, Windows 8 • User convenience: Power On/Off, Menu/OK,

Brightness/Back, 4:3 Wide/Up, Auto/Down

Hungarian, Italian, Japanese, Korean, Polish,

English, Finnish, French, German, Greek,

- Relative humidity: 20%-80% %
  - Temperature range (storage): -20°C to 60°C °C

• Altitude: Operation: +12,000 ft (3658 m), Non-

Temperature range (operation): 0°C to 40°C °C

#### **Sustainability**

method)

**Dimensions** 

Weight

• Standby mode: 0.5 W (typ.)

mode - White (flashing)

· Power LED indicator: Operation - White, Standby

• Product with stand (mm): 551 x 420 x 220 mm

• Product with packaging (kg): 5.00 kg

• Product without stand (kg): 3.22 kg

operation: +40,000 ft (12,192 m)

• Product with stand (kg): 3.66 kg

**Operating conditions** 

• MTBF: 30,000 hour(s)

• Packaging in mm (W x H x D): 600 x 415 x 118 mm

• Product without stand (mm): 551 x 344 x 52 mm

- Environmental and energy: EnergyStar 6.0, RoHS,
- Mercury Free • Recyclable packaging material: 100 %

#### **Compliance and standards**

- Regulatory Approvals: CE Mark, FCC Class B, SEMKO, TCO Certified, cETLus, TUV/ISO9241-307, BSMI, PSB, RCM, UKRAINIAN, WEEE
- Cabinet
- Colour: Black • Finish: Hairline (front bezel)/Texture (rear cover)

#### What's in the box?

- · Cables: VGA, Power
- Monitor with stand
- User Documentation



Issue date 2024-04-26 Version: 3.0.1

All Rights reserved. Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

© 2024 Koninklijke Philips N.V.

EAN: 87 12581 74077 1 www.philips.com

## 3S5LSB/00