

Philips Brilliance AMVA LCD monitor, LED backlight

P Line 27" (68.6 cm) Full HD display

271P4QPJES

# Sustainable eco design display

with PowerSensor saves energy bills

The Philips PowerSensor AMVA LED display using 65% post consumer recycled plastics and PVC, BFR free housing is ideal for eco-friendly productivity.

### **Brilliant performance**

- · AMVA LED for wide-view super-high contrast, vivid images
- Built-in stereo speakers for multimedia
- · DisplayPort offers audio and video over a single, long cable
- · HDMI ensures universal digital connectivity

### **Designed for people**

- · Low bezel-to-table height for maximum reading comfort
- SmartErgoBase enables people-friendly ergonomic adjustments

# Sustainable Eco-design

- PVC-BFR free housing
- 65% post consumer recycled plastics with TCO Edge
- PowerSensor saves up to 80% energy costs
- Zero power consumption with 0 watt hard switch

### Easy to experience

• SmartImage presets for easy optimized image settings



# Highlights

### **PowerSensor**



PowerSensor is a built-in 'people sensor' that transmits and receives harmless infrared signals to determine if user is present and automatically reduces monitor brightness when user steps away from the desk, cutting energy costs by up to 80 percent and prolonging monitor life

### **AMVA LED** display



Philips AMVA LED display uses an advanced multi-domain vertical alignment technology which gives you super-high static contrast ratios for extra vivid and bright images. While standard office applications are handled with ease, it is especially suitable for photos, webbrowsing, movies, gaming, and demanding graphical applications. It's optimized pixel management technology gives you 178/178 degree extra wide viewing angle, resulting in crisp images even in 90 degree pivot mode

## **DisplayPort**

DisplayPort is a digital link from PC to Monitor without any conversion. With higher capabilities than DVI standard, it is fully capable to support up to 15meter cables and 10.8 Gbps/sec data transfer. With this high performance and zero latency, you get the fastest imaging and refresh rates - making DisplayPort the best choice for not only general office or home use, but also for the

demanding gaming and movies, video editing and more. It also keeps interoperability in mind via use of various adapters.

### **SmartImage**



SmartImage is an exclusive leading edge Philips technology that analyzes the content displayed on your screen and gives you optimized display performance. This user friendly interface allows you to select various modes like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, SmartImage dynamically optimizes the contrast, color saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time with the press of a single button!

### **SmartErgoBase**



The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base can swivel, tilt and rotate to various angles to ensure maximum comfort. The height adjustable stand guarantees the optimal viewing level, reducing the physical strains of a long workday, while cable management reduces cable clutter and keeps the workspace neat and professional.

### **HDMI Ready**



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables high-quality digital video and audio all transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

### **Built-in stereo speakers**



A pair of high quality stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

### Low bezel-to-table height



The Philips monitor, thanks to its advanced SmartErgoBase, can be lowered down almost to desk level for a comfortable viewing angle. Low bezel-to-table height is the perfect solution if you use bifocals, trifocals or progressive lens glasses for your computing work. Additionally, it allows for users with greatly different heights to use the monitor in their preferred angle and height settings, helping them reduce fatigue and strain.





















# Specifications

### **Connectivity**

- Signal Input: DisplayPort x 1, HDMI, DVI-D (digital, HDCP), VGA (Analog)
- USB: ÚSB 2.0 x 4
- Sync Input: Separate Sync, Sync on Green
- Audio (In/Out): PC audio-in, Headphone out

### Picture/Display

- Panel Size: 27 inch / 68.6 cm
- · Aspect ratio: 16:9
- LCD panel type: AMVA LCD
- Backlight type: W-LED system
- Pixel pitch: 0.311 x 0.311 mm
- Optimum resolution: 1920 x 1080 @ 60Hz
- Brightness: 300 cd/m<sup>2</sup>
- Display colors: 16.7 M
- Contrast ratio (typical): 5,000:1
- SmartContrast: 20,000,000 :1
- Response time (typical): 6 ms (Gray to Gray)\*
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- Picture enhancement: SmartImage
- Effective viewing area: 597.6 (H) x 336.15 (V)
- Scanning Frequency: 30 83 kHz (H) / 56 75 Hz
  (V)
- sRGB

### **Convenience**

- Built-in Speakers: 2Wx2
- Plug & Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 7/Vista/XP
- User convenience: SmartImage, Volume, PowerSensor, Menu, Power On/Off
- OSD Languages: English, French, German, Italian, Portuguese, Russian, Simplified Chinese, Spanish
- Other convenience: Kensington lock, VESA mount (100×100mm)
- Control software: SmartControl

### **Stand**

- · Height adjustment: 150 mm
- Pivot: 90 degree
- Swivel: -65/65 degree
- Tilt: -5/20 degree

### **Power**

- ECO mode: 23 W (typ.)
- Power supply: 100-240VAC, 50-60Hz, Built-in
- Off mode: Zero watts with Zero switch
- On mode: 43.2 W (typ.)
- Standby mode: 0.3 W (typ.)
- Power LED indicator: Operation White, Standby mode- White (blinking)

### **Dimensions**

- Product with stand (mm):  $639 \times 580 \times 242$  mm
- Packaging in mm (WxHxD):  $750 \times 234 \times 490$  mm
- Product without stand (mm):  $639 \times 405 \times 64$  mm

### Weight

- Product with packaging (kg): 10.35 kg
- Product with stand (kg): 7.50 kg
- Product without stand (kg): 5.10 kg

### **Operating conditions**

- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- Temperature range (operation): 0°C to 40°C °C
- MTBF: 30,000 hour(s)
- Relative humidity: 20%-80 %
- Temperature range (storage): -20°C to 60°C °C

### **Sustainability**

- Environmental and energy: PowerSensor, TCO Certified Edge, RoHS
- Post consumer recycled plastic: 65%
- Recyclable packaging material: 100 %
- Specific Substances: PVC / BFR free housing, Mercury free

### Compliance and standards

 Regulatory Approvals: BSMI, CE Mark, FCC Class B, GOST, SASO, SEMKO, TUV Ergo, TUV/GS, UL/ cUL, WEEE, TCO Certified Edge

## Cabinet

- Finish: Texture
- Foot: Black
- Front bezel: Silver
- Rear cover: Black



Issue date 2024-03-24

© 2024 Koninklijke Philips N.V. All Rights reserved.

Version: 7.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 65470 2

www.philips.com

st Response time value equal to SmartResponse