

Philips Signage Solutions
Q-Line Display

55"

Direct LED Backlight
Ultra HD

55BDL3010Q



Stand out

Easy-setup 18/7 display.

Inform and enthrall with a Philips Q-Line Professional 4K Ultra HD Display. This reliable solution can be up and running as quickly as you need-with no additional hardware.

Brilliant picture. Reliable performance

- Ultra-HD. Rich images. Stunning contrast

Cost-effective system solution

- Energy-saving automatic backlight control
- Integrated media player. Easily schedule USB content
- FailOver ensures content is always playing
- Easy control. Remotely manage networked displays

Effortless setup. Total control.

- Operate, monitor and maintain with CMND & Control

PHILIPS


Q-Line Display
55" Direct LED Backlight, Ultra HD

Highlights

Ultra-HD Resolution

Ultra-HD. Rich images. Stunning contrast

CMND & Control



Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

Integrated media player

Easily schedule content to play from USB. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback is done.

Energy-saving


Energy-saving automatic backlight control

Easy control

Easy control. Remotely manage networked displays

55BDL3010Q/00

FailOver



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs ensuring content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure your business is always on.

Specifications

Connectivity

- Audio output: Audio Left/Right (RCA)
- Video input: DVI-I (x 1), HDMI (x4), USB, VGA (via DVI)
- Audio input: 3.5 mm jack
- External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack

Picture/Display

- Diagonal screen size (metric): 138.7 cm
- Diagonal screen size (inch): 54.6 inch
- Aspect ratio: 16:9
- Panel resolution: 3840 x 2160
- Pixel pitch: 0.315 x 0.315 mm
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 350 cd/m²
- Display colors: 1.07 Billion
- Contrast ratio (typical): 4000:1
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Viewing angle (horizontal): 178 degree
- Viewing angle (vertical): 178 degree
- Clinical image: D-Image preset (dicom part 14 compatible)

Convenience

- Tiled Matrix: Up to 15 x 15
- Keyboard control: Lockable, Hidden
- Signal loop through: RS232, IR Loopthrough
- Energy saving functions: Smart Power
- Network controllable: RS232, RJ45
- Start-up: Switch on delay, Switch on status, Boot on source
- Start-up window: enable / disable Philips logo

Sound

- Built-in speakers: 2 x 10W RMS

Power

- Mains power: 100 ~ 240 VAC
- Consumption (On mode): 125 W
- Consumption (Typical): 140 W
- Consumption (Max): 180 W
- Standby power consumption: ≤ 0.5 W
- Energy Label Class: G

Supported Display Resolution

- Computer formats: 1920 x 1080, 60Hz, 1600 x 1200, 60Hz, 1440 x 900, 60Hz, 1280 x 1024, 60Hz,

- 1280 x 720, 60Hz, 1280 x 800, 60Hz, 1024 x 768, 60, 70, 75Hz, 720 x 400, 70Hz, 640 x 480, 60, 67, 72, 75Hz, 1152 x 870, 75Hz, 1680 x 1050, 60Hz, 800 x 600, 56, 60, 72, 75Hz
- Video formats: 3840 x 2160, 60Hz, 3840 x 2160, 30Hz, 1080i, 60Hz, 1080p, 60Hz, 720p, 60Hz, 480i, 60Hz, 480p, 60Hz, 1080i, 50Hz, 576i, 50Hz, 576p, 50Hz

- Regulatory approvals: CE, CB, FCC, Class B

Dimensions

- Set Width: 1239.2 mm
- Product weight: 15.82 kg
- Set Height: 711.6 mm
- Set Depth: 61.71 mm
- Set Width (inch): 48.79 inch
- Set Height (inch): 28.02 inch
- Wall Mount: 400 x 400 mm/400 x 200 mm, M6
- Set Depth (inch): 2.43 inch
- Bezel width: 12.9 (TLR) / 14.7 (B) mm
- Product weight (lb): 34.88 lb

Operating conditions

- Altitude: 0 ~ 3000 m
- Temperature range (operation): 5 ~ 40 °C
- MTBF: 50,000 hour(s)
- Temperature range (storage): -20 ~ 60 °C
- Humidity range (operation)[RH]: 20 ~ 80% RH (No condensation)
- Humidity range (storage) [RH]: 5 ~ 95% RH (No condensation)

Multimedia Applications

- USB Playback Video: MPEG, H.264, JPEG
- USB Playback Picture: JPEG, BMP, PNG
- USB Playback Audio: AAC, HEAAC, MPEG, WMA


Accessories

- Included accessories: AC Power Cord, RS232 cable, Remote Control, Batteries for remote control, Quick start guide
- Included Accessories: USB Cover and screw x1, IR sensor cable (1.8 m) (x1), RS232 daisy-chain cable
- Stand: Table stand (BM02542, BM05922)

Miscellaneous

- On-Screen Display Languages: English, French, German, Italian, Polish, Turkish, Russian, Simplified Chinese, Spanish, Traditional Chinese
- Warranty: 3 year warranty

Philips 55BDL3010Q
Version: 5.0
Release Date: 2018/1/06



Issue date 2024-03-24

Version: 5.0.1

EAN: 87 12581 75410 5

© 2024 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com