

Philips
LCD Touch monitor

140 cm (55")
multimedia
Full HD

BDT5571VX



More audience interaction

with the robust multi-touch screen

Deliver the message to your audience in startling clarity. Thanks to the capacitive touch screen, you can engage your customer in public spaces much more closely than ever before.

Lower total cost of ownership

- SmartPower for energy saving

High picture and video quality

- 120 Hz Panel

Operational flexibility

- Capacitive Touch
- 2 Touch Points
- Software Independent
- Designed for 24/7 operation
- One Wire
- RJ45
- Smart insert in the back cover to place a small PC
- Display Port for faster graphics support

PHILIPS

Highlights

120 Hz Panel

Enjoy stunningly clear video images thanks to the 120 Hz panel. Even fast moving action scenes can be seen without being blurred, which will enhance your viewing experience.

2 Touch Points

Enjoy the interactivity of multi-touch functionality. It has the advantages of a more robust touch screen combined with the multi-touch gestures for using more versatile touch software.

Capacitive Touch

This capacitive touch has 5-mm tempered glass. Therefore it is perfectly practical for public use and easy to clean.

Designed for 24/7 operation

Designed for 24/7 operation

Display Port for faster graphics support

Display Port for faster graphics support

One Wire

Take full control of your display by running all operational commands, as well as your video signal, through just one single HDMI cable. This unique feature makes it so much easier and more convenient to ensure the smooth running and maintenance of your display. Consumer Electronics Control (CEC) commands make finding out vital information about your display absolute child's play.

RJ45

Simple management of your display is available thanks to the introduction of a LAN (RJ45) port. You can configure each display or find out the status of each device quickly and conveniently via an RJ45 connection.

Smart insert

Professional PCs are part of most multi-user Touch Screen installations. Quite often they add additional depth to the public display and a lot of cable clutter. This Multi-user Touch Screen contains a Smart insert in the back cover that will fit many professional compact PCs. In addition, it offers provisions for efficient cable management.

SmartPower

The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

Software Independent

Our touch screens are software independent and work with most touch-screen software commercially available, including Windows XP/7 and Mac OS, Omnitapps – BMT1909/00. Connect via USB to a PC or laptop.



Specifications

Picture/Display

- Diagonal screen size: 55 inch / 140 cm
- Aspect ratio: 16:9
- Panel resolution: 1920 x 1080p
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 700 cd/m²
- Display colours: 1.06 Billion colours
- Contrast ratio (typical): 1300:1
- Response time (typical): 10 ms
- Viewing angle: 178° (H)/178° (V)
- Display technology: 120 Hz Panel

Connectivity

- PC: VGA-in D-Sub 15HD, VGA-out D-Sub 15HD, DVI-D x 1, RS232 D-Sub9, RS232 D-sub9 output, 3.5 mm PC audio input x 1
- AV input: HDMI x 1, Component (YPbPr) x 1, Composite (RCA) x 1, Composite (BNC) x 1, S-video x 1, Audio (L/R) x 2
- AV output: Optional DVI Out
- Other connections: AC-out, Display Port, External loudspeaker connector
- Touch Screen: USB

Convenience

- Placement: Portrait, Landscape
- Picture in picture: PBP, PIP, POP
- Screen-saving functions: Pixel shift, Low brightness
- Keyboard control: Hidden, Lockable
- Remote control signal: Lockable
- Ease of installation: AC Out, Carrying Handles, Smart Insert
- Energy-saving functions: Ambient light sensor, Smart Power
- Safety control functions: Heat Control, Temperature Sensor
- Picture performance: Advanced colour control
- Network controllable: RJ45, RS232

Sound

- Built-in speakers: 2 x 12 W (8 Ohm)

Power

- Mains power: 90-264 VAC, 50/60 Hz
- Consumption (On mode): Typical 214 W
- Standby power consumption: <1 W (Easylink and RS232 active)

Supported Display Resolution

- Computer formats: 640 x 480, 60, 67, 72, 75 Hz, 800 x 600, 56, 60, 72, 75 Hz, 1024 x 768, 60 Hz, 1280 x 768, 60 Hz, 1280 x 800, 60 Hz, 1280 x

- 1024, 60 Hz, 1360 x 768, 60 Hz, 1366 x 768, 60 Hz, 1440 x 900, 60 Hz, 1600 x 1200, 60 Hz, 1920 x 1080, 60 Hz, 1920 x 1200, 60 Hz
- Video formats: 480i, 60 Hz, 480p, 60 Hz, 576i, 50 Hz, 576p, 50 Hz, 720p, 50, 60 Hz, 1080i, 50, 60 Hz, 1080p, 50, 60 Hz

Dimensions

- Bezel thickness: 36.6 mm horizontal, 36.3 mm vertical
- Set dimensions (W x H x D): 1293 x 759 x 142.8 mm
- Smart Insert mount: 300 x 320 x 64 mm
- Product weight: 62 kg
- Wall Mount: 400 x 400 mm (Set). 100 x 100 mm (Smart insert)

Operating conditions

- Temperature range (operation): 0 - 40 °C
- MTBF: 60.000 hour(s)
- Relative humidity: 10-90 %

Accessories

- Included accessories: Remote Control, Batteries for remote control, AC Power Cord, VGA cable, User manual on CD-ROM, Owner's Manual, Touch Screen Driver
- Optional accessories: Fixed wall mount, Flexible wall mount, Ceiling mount, Electric Stand BMT1851/00, Multi User Touch SW, Software Omnitapps BMT1909/00

Miscellaneous

- Bezel: black, RAL 9005F13
- On-Screen Display Languages: English, French, German, Italian, Polish, Turkish, Russian, Simplified Chinese
- Warranty: Europe 3 years
- Regulatory approvals: CCC, CE, FCC, Class B, RoHS, UL/cUL

Packaging Data

- Packaging dimensions (W x H x D):: 1339 x 940 x 305 mm
- Tare weight: 8.5 kg
- Number of products included: 1
- Net weight: 35

Interactivity

- Multi-touch technology: 2 Touch Points simultaneously, Capacitive touch, USB connection, 5-mm safety glass

