[field not found 'leaflet_type'] (2021, May 20)



LCD monitor with SmartControl Lite

• V Line • 27" (68.6 cm)

273V5LHAB/56

Great LED images in vivid colors

with stereo speakers

Enjoy vivid LED pictures on this big Philips display. Equipped with HDMI and stereo speakers, it's a great choice!

Benefits

Vivid pictures every time

- LED technology for vivid colors
- Easy display performance tuning with SmartControl Lite
- SmartContrast for rich black details
- 16:9 Full HD display for best viewing experience

Experience multimedia

• Built-in stereo speakers for multimedia

• HDMI-ready for Full HD entertainment

Great choice

- Mercury Free eco-friendly display
- Compact design saves space
- VESA mount allows for flexibility



Features

LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of LCD backlight, resulting in super high contrast ratio. It also gives superior color reproduction thanks to consistent brightness across the screen.

Built-in stereo speakers



A pair of high quality stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

SmartControl Lite

SmartControl Lite is the next generation 3D icon based GUI monitor control software. This allows user to fine-tune most parameters of the monitor like Color, Brightness, screen calibration, Multi-media, ID management, etc with the mouse.

SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is

Specifications

[field not found 'disclaimer_text']

Picture/Display

LCD panel type Backlight type Panel Size Effective viewing area Aspect ratio Optimum resolution Response time (typical) SmartResponse (typical) Brightness SmartContrast Contrast ratio (typical) Pixel pitch Viewing angle Display colors

Scanning Frequency sRGB

Connectivity

Signal Input

TFT-L W-LE 27 inc 597.88 16.9 1920 5 ms 1 ms (300 co

10,000 1000:1

0.311× 170° (@ C/ 16.7 № 30 -83 Yes

VGA (Analog) DVI-D (digital, HDCP)

selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

16:9 Full HD



The Full HD screen has the widescreen resolution of 1920 x 1080p. This is the highest resolution of HD sources for the best possible picture quality. It is fully future proof as it supports 1080p signals from all sources, including the most recent like Blu-ray and advanced HD game consoles. The signal processing is extensively upgraded to support this much higher signal quality and resolution. It produces brilliant flicker-free progressive scan pictures with superb brightness and colors.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables highquality digital video and audio all transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

Mercury Free

Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.

LCD ED system ch / 68.6 cm 38 (H) × 336.31 (V)	Sync Input Audio (In/Out)	HDMI (digital, HDCP) Separate Sync Sync on Green PC audio-in Headphone out
× 1080 @ 60 Hz	Convenience	
(Gray to Gray)	Built-in Speakers User convenience	2W x 2 Auto/Down Brightness/Back
cd/m² 00,000:1		Menu/OK Power On/Off Volume/Up
:1 x 0.311 mm (H) / 160° (V) /R > 10 M /3 kHz (H) / 56 -75 Hz (V)	OSD Languages	Brazil Portuguese Czech Dutch English Finnish French German Greek Hungarian Italian
(Analog)		Japanese

data subject to change 2021, May 20

Korean

Russian Simplified Chinese Spanish Swedish Traditional Chinese Turkish Ukranian Other convenience Kensington lock VESA mount (100x100mm) DDC/CI Plug & Play Compati-Mac OS X sRGB Windows 7

-5/20 degree

Polish

Portuguese

Stand

Tilt

bility

Power

On mode	19.65 W (EnergyStar 6.0 test method)
Standby mode	0.5 W (typ.)
Off mode	0.3 W (typ.)
Power LED indicator	Operation - White
	Standby mode- White (blinking)
Power supply	Built-in
	100-240VAC, 50-60Hz

Dimensions

Product with stand (mm)	646 x 471 x 240 mm
Product without stand (mm)	646 x 398 x 57 mm
Packaging in mm (WxHxD)	698 x 482 x 139 mm

Weight

4.53 kg Product with stand (kg)

Windows 8

Product without 4.00 kg stand (kg) Product with pack-6.17 kg aging (kg)

0°C to 40°C °C

20%-80 %

30,000 hour(s)

EnergyStar 6.0

Mercury Free 100 %

RoHS

cETLus WEEE

-20°C to 60°C °C

Operation: +12,000ft (3,658m), Non-

operation: +40,000ft (12,192m)

Operating conditions

Temperature range (operation) Temperature range (storage) Relative humidity Altitude

MTBF

Sustainability

Environmental and energy Recyclable packaging material

Compliance and standards

Regulatory Approvals BSMI CE Mark FCC Class B GOST PSB SASO SEMKO TCO Certified TUV/ISO9241-307

Cabinet

Color Finish

Black Hairline (front bezel) /Texture (rear cover)

* Smart response time is the optimum value from either GtG or GtG (BW) tests.



data subject to change 2021, May 20 Version: 2.0.1

EAN: 8712581747275

© 2021 Koninklijke Philips N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com