PHILIPS LCD monitor with USB-C docking Monitor P Line 27" (68.6 cm) 3840 x 2160 (4K UHD)

279P1



Master every task in a crisp view

This Philips monitor offers 90W power delivery and a simple laptop docking solution. View UHD image, re-charge a laptop and Ethernet, all at the same time with a single USB-C cable. Eye comfort with TUV certification to reduce eye fatigue.

Single cable USB-C connection

- Built in RJ-45 ethernet gives data security
- USB-C enables laptop power charging directly from a monitor
- USB 3.2 high speed data transfer

Designed for the way you work

- SmartErgoBase enables people-friendly ergonomic adjustments
- Less eye fatigue with Flicker-free technology
- LowBlue Mode for easy on-the-eyes productivity
- EasyRead mode for a paper-like reading experience
- TUV Eye Comfort certified to reduce eye fatigue
- UltraClear 4K UHD (3840x2160) resolution for precision

Sustainable Eco-design

- PowerSensor saves up to 80% energy costs
- LightSensor for the perfect brightness with minimal power


Highlights

USB Type-C connection



This Philips display features a built-in USB type-C docking station with power delivery. With intelligent and flexible power management, you can power charge your compatible* laptop directly. Its slim, reversible USB-C connector allows for easy, one-cable docking. Simplify by connecting all your peripherals like keyboard, mouse and your RJ-45 Ethernet cable to the monitor's docking station. You can watch high resolution video and transfer data at a superspeed, while powering up and re-charging your notebook at the same time.

UltraClear 4K UHD Resolution



These Philips displays utilize high performance panels to deliver UltraClear, 4K UHD (3840 x 2160) resolution images. Whether you are demanding professional requiring extremely detailed images for CAD solutions, using 3D graphics applications or a financial wizard working on huge spreadsheets, Philips displays will make your images and graphics come alive.

TUV Rheinland Eye Comfort



Philips display meet TUV Rheinland Eye Comfort standard to prevent eye strain caused by prolonged computer use. With TUV Eye Comfort

certification, Philips displays ensure flicker-free, low blue mode, no disturbing reflections, wide viewing angle and less reduction of image quality from different angles and ergonomic stand designs for ideal viewing experience. Keep your eyes healthy and boost work productivity.

Flicker-free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-free Technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

EasyRead mode



EasyRead mode for a paper-like reading experience

SmartErgoBase



The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base can swivel, tilt and rotate to various angles to ensure maximum comfort. The height adjustable stand guarantees the optimal viewing level, reducing the physical strains of a long workday, while cable management reduces cable clutter and keeps the workspace neat and professional.

PowerSensor



PowerSensor is a built-in 'people sensor' that transmits and receives harmless infrared signals to determine if user is present and automatically reduces monitor brightness when user steps away from the desk, cutting energy costs by up to 80 percent and prolonging monitor life

LightSensor



LightSensor uses a smart sensor to adjust the picture brightness depending on the room light conditions for the perfect picture with minimal power usage.

















Specifications

Picture/Display

Panel Size: 27 inch / 68.6 cm

Aspect ratio: 16:9

LCD panel type: IPS technology Backlight type: W-LED system Pixel pitch: 0.1554 x 0.1554 mm

Brightness: 350 cd/m²

Display colors: Color support 1.07 billion colors Color gamut (typical): NTSC 103%*, sRGB 122%*

Contrast ratio (typical): 1000:1 SmartContrast: 50,000,000:1

Response time (typical): 4 ms (Gray to Gray)* Viewing angle: 178° (H) / 178° (V), @ C/R > 10

Picture enhancement: SmartImage

Maximum resolution: 3840 x 2160 @ 60 Hz* Effective viewing area: 596.736 (H) x 335.664 (V) Scanning Frequency: 30 - 140 kHz (H) / 23 - 60

Hz (V) sRGB

Delta E: < 2 (sRGB) Flicker-free

Pixel Density: 163 PPI LowBlue Mode

Display Screen Coating: Anti-Glare, 3H, Haze

SmartUniformity: 97 ~ 102%

EasyRead

Connectivity

Signal Input: DisplayPort 1.4 x 1, HDMI 2.0 x 2, USB-C 3.2 Gen 2 x 1 (upstream, power delivery up to 90 W)

Sync Input: Separate Sync Audio (In/Out): Audio out

RJ45: Ethernet LAN (10M/100M/1G)*, Wake on

LAN

USB:: USB-C x 1 (upstream), USB 3.2 x 4 (downstream with 1 fast charge B.C 1.2) HDCP: HDCP 2.2 (HDMI / DP / USB-C)

HBR3

USB

Power delivery: USB PD version 3.0 Super speed: Data and Video transfer DP: Built-in Display Port Alt mode

USB-C max. power delivery: Up to 90W (5V/3A; 7V/3A; 9V/3A; 10V/3A; 12V/3A; 15V/3A;

20V/4.5A)

USB-C: Reversible plug connector

Convenience

Built-in Speakers: 3 W x 2

Plug & Play Compatibility: DDC/CI, Mac OS X,

sRGB, Windows 10 / 8.1 / 8 / 7 User convenience: SmartImage, Input, PowerSensor, Menu, Power On/Off

OSD Languages: Brazil Portuguese, Czech, Dutch, English, French, Finnish, German, Greek, Hungarian, Italian, Japanese, Korean, Portuguese, Polish, Russian, Simplified Chinese,

Spanish, Swedish, Traditional Chinese, Turkish,

Ukrainian

Other convenience: Kensington lock, VESA

mount (100x100mm)

Control software: SmartControl

Height adjustment: 150 mm

Pivot: -/+90 degree Swivel: -/+180 degree Tilt: -5/35 degree

Power

ECO mode: 20.9 W (typ.)

Power supply: Built-in, 100-240VAC, 50-60Hz Off mode: Zero watts with Zero switch

On mode: 25.9 W (typ.) (EnergyStar test method)

Standby mode: 0.3 W

Power LED indicator: Operation - White, Standby

mode- White (blinking)

Dimensions

Packaging in mm (WxHxD): 730 x 471 x 193 mm Product without stand (mm): 613 x 366 x 54 mm Product with stand(max height): 613 x 537 x 225 mm

Weight

Product with packaging (kg): 11.20 kg Product with stand (kg): 7.52 kg Product without stand (kg): 5.73 kg

Operating conditions

Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)

Temperature range (operation): 0°C to 40°C °C Relative humidity: 20%-80 %

Temperature range (storage): -20°C to 60°C °C MTBF (demonstrated): 70,000 hrs (excluded backlight)

Sustainability

Environmental and energy: PowerSensor, LightSensor, EnergyStar 8.0, EPEAT*, TCO

Certified Edge, RoHS

Post consumer recycled plastic: 85% Recyclable packaging material: 100 %

Specific Substances: Mercury free, PVC / BFR free

housing

Compliance and standards

Regulatory Approvals: cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU RoHS, CE Mark, UKRAINIAN, FCC Class B, ICES-003, TUV Eye Comfort certified, RCM, MEPS

Cabinet

Finish: Texture Foot: Black Front bezel: Black Rear cover: Black

- * The maximum resolution works for either USB-C. DP or HDMI input
- * Response time value equal to SmartResponse
- * NTSC Area based on CIE1976
- * sRGB Area based on CIE1931
- * For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mode
- * Activities such as screen sharing, on-line streaming video and audio over the Internet can impact your network performance. Your hardware, network bandwidth and its performance will determine overall audio and video
- * For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more details.
- * If your Ethernet connection seems slow, please enter OSD menu and select USB 3.0 or higher version which can support the LAN speed to 1G.
- * EPEAT rating is valid only where Philips registers the product. Please visit https://www.epeat.net/ for registration status in your country
- * The monitor may look different from feature images.

© 2025 Koninklijke Philips N.V. All Rights reserved

Issue date 2025-02-26 Version: 5.0.3

EAN: 87 12581 77659 6

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

