

PHILIPS

3 inch work light -
flood

Ultinon Drive 5000

Off-road auxiliary lights

2450 lm, 73 m beam length

IP69K waterproof

Sturdy corrosion-free body

LUMUD5003CX1



Brilliant LED lighting for off-road adventures

Bright, durable gear for overland journeys

For drivers who demand the maximum of themselves and their machines, we offer Philips Ultinon Drive 5000 series LED work lights. Exceptionally rugged, with unsurpassed illumination and beam focus, advanced LED work lights can light the way.

Powerful brightness, rugged performance

- Long, bright beam for superior visibility

Durable equipment for challenging conditions

- Sturdy one-piece body for tough environments
- IP69K waterproof to master the elements
- Corrosion-free body, stainless-steel mounting brackets

Trouble-free installation

- Trouble-free installation

Ultinon Drive 5000

3 inch work light - flood

LUMUD5003CX1/10

Specifications

Product description

Boost mode activation: No
Break resistance
ECE R10: No
ECE R149: No
Impact protection rating (IK): IK07
Ingress protection rating (IP): IP68 & IP69K
Installation angle: 360°
Material: Aluminum die-cast
Number of LEDs: 4x 7W
Offroad boost: No
One-piece body design
Operating temperature: -40° C to 80° C
Range: Ultinon Drive 5000
Scratch resistant lens
Technology: LED
Width: 3 inch
Boost function installation: No
Accessories (optional): LUMUD1005WX1, LUMUD1006WX1
corrosion-free brackets: Yes, included
Parking position light: No
Plug type: 2-pin DT Connector with 0,5 m cable

ECE reference number: n/a
Cable length: 0,5 m
Compatible with: N/A
Fuse: No
Number of connector plug: 1
Relay: No
Switch On/Off: No
Storage temperature: -40° C to 80° C

Light characteristics

Color temperature: 6000 K K
Beam length 1 lux-m: 73 m
Effective lumen output: 2450 lumen
Raw lumen output: 3480 lumen
Effective lumen output (Boost mode): n/a
Beam length 3 lux: 42 m
Beam width 1 lux: 32 m

Electrical characteristics

Voltage: 9-48 Volt DC
Wattage: 25w

Ordering information

Order entry: UD5003CX1
GOC: 02428250

Packaging Data

EAN1: 8719018024282
EAN3: 8719018024299

Packed product information

MOQ (for professionals): 8
Box dimensions-L(mm): 150
Box dimensions-W(mm): 112
Box dimensions-H(mm): 88
Number of product in the box: 1
Gross weight box: 680 g
Net weight product: 590 g

Outerpack information

Length: 32 cm
Width: 24 cm
Height: 19,5 cm
Gross weight per carton: 6500 g

