



Enhanced durability and reliability

Reliable installation for long-lasting performance

Ensure smooth installation of a single Philips LED driving light, with automotive-grade cables and waterproof sealed components, for long-lasting LED light performance. Being RoHS-compliant**, this kit is gentler on the environment.

Enhanced durability and reliability

- Easy to install
- For a single LED lamp

Reliable Philips automotive quality

• Durable material for long-lasting performance

Ultinon Drive Accessory

Wiring harness kit for 1 LED lamp

LUMUD1005WX1/10

Specifications

Electrical characteristics

Voltage: 12V

Ordering information

GOC: 02436732

Order entry: UD1005WX1

Outerpack information

Gross weight per carton: 5700 g

Width (cm): 28 Height (cm): 26 Length (cm: 37,2

Packaging Data

EAN1: 8719018024367 EAN3: 8719018024374

Packed product information

box dimensions-L(mm): 88 box dimensions-W(mm): 60 box dimensions-H(mm): 354 Gross weight box: 430 g MOQ (for professionals): 12

Pack Quantity: 1

Product description

Cable length: 3m

Compatible with: UD5001L, UD5002L, UD5003L, UD5004L, UD5002C, UD5003C, UD2001R,

UD2002R

Fuse: 10A, 15A, 20A

Number of connector plug: 1 Parking position light wired: No

Plug type: 2pin DT connector female plug

Relay: Yes, 12V Switch On/Off Technology: LED

© 2025 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or

their respective owners.

Issue date 2025-05-14 Version: 2.2.1

EAN: 87 19018 02436 7





^{**}Compatible with: Philips Ultinon Drive UD5001LX1, UD5002LX1, UD5003LX1, UD5004LX1, UD5002CX1, UD5003CX1, UD2001R, UD2002R

^{* **}Exempt of Polyvinyl Chloride (PVC) and Brominated Flame Retardants (BFRs)