

PHILIPS

7 inch LED driving
light

Ultinon Drive 5100

Road-legal ECE R149 - 25

7100 lm, 333 m beam, 552 m
boost

Off-road light boost

Dual-colour position light

LUMUD5101RX1



Powerful brightness driving safety at the wheel

Bright, durable gear for overland journeys

The Philips UD5101R LED driving light has the power to keep you safer, wherever you're headed. Spot hazards up to 552 metres away with lighting that performs in the most hostile environments and gives your vehicle a touch of style.

Brilliance that makes you a safer driver

- Intense, far and wide illumination for superior visibility
- Enhanced safety off-road with boost function for more power

Dual-color position lights that get you noticed

- Choose your position-light colour

Designed to handle hostile environments

- Sturdy one-piece body for tough environments
- IP68 and IP69K waterproof to master the elements
- Corrosion-free body, stainless-steel mounting brackets

Road-legal auxiliary lights

- Powerful road-legal LED driving lights

Easy to install with flexible mounting options

- 4-pin superseal DT connector for easier installation

Ultinon Drive 5100

7 inch LED driving light

LUMUD5101RX1/10

Specifications

Product description

Boost mode activation

Break resistance

ECE R10

ECE R149

ECE reference number: 25

Impact protection rating (IK): IK07

Ingress protection rating (IP): IP68 and IP69K

Installation angle: 360°

Material: Aluminium extruded

Off-road boost

One-piece body design

Operating temperature: -40° C to 80°C

Range: Ultinon Drive 5100

Scratch-resistant lens

Technology: LED

Width: 7 inch

Accessories (optional): LUMUD1003W,
LUMUD1004W

corrosion-free brackets: U-shaped mounting
bracket

ECE R148

Parking position light: Yes, white or amber

Plug type: 4-pin DT Connector with 0.5 m cable

Light characteristics

Colour temperature: 6500 K K

Beam length 1 lux-m: 335 m

Effective lumen output: 2700 lumens

Raw lumen output: 20,400 lumens

Effective lumen output (Boost mode):

7100 lumens

Beam length 1 lux (boost): 552 m

Electrical characteristics

Voltage: 9-30 Volt DC

Ordering information

Order entry: UD5101RX1

GOC: 2515933

Packaging Data

EAN1: 8719018025159

EAN3: 8719018025166

Packed product information

MOQ (for professionals): 2

Box dimensions-L (mm): 220

Box dimensions-W (mm): 220

Box dimensions-H (mm): 200

Number of products in the box: 1

Gross weight box: 1980 g

Outer pack information

Length: 46 cm

Width: 24 cm

Height: 22 cm

