



# Enhanced durability and reliability

### Reliable installation for long-lasting performance

Ensure smooth installation of a single Philips LED driving light, with automotive-grade cables and waterproof sealed components, for long-lasting LED light performance. Being RoHS-compliant\*\*, this kit is gentler on the environment.

### **Optimal fit**

- · Easy to install
- For two LED lamps

### **Reliable Philips automotive quality**

• Durable material for long-lasting performance

### **Ultinon Drive Accessory**

Specifications

Wiring harness for 2 LED lamps

### LUMUD1006WX1/10

## **Electrical characteristics**

Voltage: 12V

### **Ordering information**

GOC: 02438132

Order entry: UD1006WX1

#### **Outerpack information**

Gross weight per carton: 8000 g

Width (cm): 28 Height (cm): 26 Length (cm: 37,2

### **Packaging Data**

EAN1: 8719018024381 EAN3: 8719018024398

#### **Packed product information**

box dimensions-L(mm): 88 box dimensions-W(mm): 60 box dimensions-H(mm): 354 Gross weight box: 610 g MOQ (for professionals): 12

Pack Quantity: 1

### **Product description**

Cable length: 3m

Compatible with: UD5001L, UD5002L, UD5003L, UD5004L, UD5002C, UD5003C, UD2001R,

UD2002R

Fuse: 15A, 25A, 30A

Number of connector plug: 2 Parking position light wired: No

Plug type: 2pin DT connector female plug

Relay: Yes, 12V Switch On/Off Technology: LED

© 2025 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or

their respective owners.

Issue date 2025-05-14 Version: 2.2.1

EAN: 87 19018 02438 1





<sup>\* \*</sup>Compatible with: Philips Ultinon Drive UD5001LX1, UD5002LX1, UD5003LX1, UD5004LX1, UD5002CX1, UD5003CX1, UD2001R, UD2002R

<sup>\* \*\*</sup>Exempt of Polyvinyl Chloride (PVC) and Brominated Flame Retardants (BFRs)