

# PHILIPS

Stereo dubbing  
cable

1.5 m (4.9 ft)

SWA4522S



## Ensure a reliable connection

with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

### **Protects against signal loss**

- Bare copper shielding

### **Enjoy good audio quality**

- High-purity copper conductor for reliable signal transfer
- Signal degradation is minimised with gold-plated connectors

### **Easy installation**

- Non-slip ergonomic grip for easy use

### **Enjoy extended durability**

- Moulded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

# Highlights

## Moulded plug

Moulded plugs ensure secure connections between components and offer extended durability.

## Flexible PVC Jacket

Flexible PVC jacket provides protection to the delicate core of the cable. It also offers extended durability and ease of installation.

## Rubber strain relief

Rubber strain relief provides a secure yet flexible juncture between the cable and the plug.

## Bare copper shielding

Bare copper shielding protects against signal loss.

## Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

## High-purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

## Gold-plated connectors

High-quality connectors that minimise signal loss.

# Specifications

## Outer Carton

EAN: 87 12581 51683 3

Length: 36.5 cm

Number of consumer packages: 24

Width: 26.5 cm

Gross weight: 3.44 kg

Height: 22 cm

Net weight: 2.040 kg

Tare weight: 1.400 kg

## Inner Carton

Length: 25 cm

Number of consumer packages: 4

Width: 10 cm

Height: 11 cm

Net weight: 0.340 kg

Gross weight: 0.51 kg

Tare weight: 0.170 kg

EAN: 87 12581 51687 1

## Packaging dimensions

Height: 24 cm

Packaging type: Blister

Type of shelf placement: Both

Width: 9 cm

Depth: 4.8 cm

Number of products included: 1

EAN: 87 12581 51688 8

Gross weight: 0.09 kg

Net weight: 0.085 kg

Tare weight: 0.005 kg

