

Philips  
Stereo dubbing cable

**3.0 m**  
3.5 mm (M) - 3.5 mm (M)  
Black

**SWA2533W**



## Ensure a reliable connection

with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

### **Enjoy good audio quality**

- High purity copper conductor for reliable signal transfer

### **Protects against signal loss**

- Bare copper shielding

### **Easy installation**

- Non-slip ergonomic grip for easy use

### **Enjoy extended durability**

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

# PHILIPS

Stereo dubbing cable  
3.0 m 3.5 mm (M) - 3.5 mm (M), Black

# Specifications

## Packaging dimensions

- EAN: 87 12581 38298 8
- Number of products included: 1
- Packaging type: Blister
- Type of shelf placement: Laying
- Packaging dimensions (W x H x D):  
9.5 x 23.5 x 2.1 cm
- Nett weight: 0.042 kg
- Gross weight: 0.069 kg
- Tare weight: 0.027 kg

## Outer Carton

- EAN: 87 12581 38300 8

- Number of consumer packagings: 24
- Outer carton (L x W x H): 32.3 x 26 x 22.2 cm
- Nett weight: 1.008 kg
- Gross weight: 2.315 kg
- Tare weight: 1.307 kg

## Inner Carton

- EAN: 87 12581 38299 5
- Number of consumer packagings: 4
- Inner carton (L x W x H): 24.7 x 10.4 x 9.8 cm
- Nett weight: 0.168 kg
- Gross weight: 0.324 kg
- Tare weight: 0.156 kg

SWA2533W/10

# Highlights

## Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

## Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

## Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

## Bare copper shielding

Bare copper shielding protects against signal loss.

## Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

## High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.



Issue date 2022-04-29

Version: 1.2.11

12 NC: 8670 000 35562  
EAN: 87 12581 38298 8

© 2022 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)