

Philips  
Stereo dubbing cable

1,5 m  
3.5 mm (M) - 3.5 mm (M)  
Coiled

SWA2529W



## Ensure a reliable connection

with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

### Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

### Protects against signal loss

- Bare copper shielding

### Easy installation

- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use

### Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

**PHILIPS**

Stereo dubbing cable  
1,5 m 3.5 mm (M) - 3.5 mm (M), Coiled

# Specifications

## Packaging Data

- Quantity: 1
- EAN/UPC/GTIN: 87 10895 99450 7
- Gross weight: 3 kg
- Net weight: 1 kg
- Tare weight: 2 kg

## Inner Carton

- EAN/UPC/GTIN: 87 10895 99848 2
- Quantity: 6
- Length: 245 mm
- Width: 150 mm
- Height: 105 mm
- Gross weight: 0.38 kg
- Net weight: 0.12 kg
- Tare weight: 0.26 kg

## Outer Carton

- EAN/UPC/GTIN: 87 10895 99849 9
- Quantity: 36
- Length: 340 mm
- Width: 340 mm
- Height: 265 mm
- Gross weight: 2.78 kg
- Net weight: 0.72 kg
- Tare weight: 2.06 kg

## Dimensions

- Product length: 23.5 cm
- Product dimensions (W x H): 95 x 22 mm
- Gross weight: 0.04 kg
- Net weight: 0.02 kg
- Tare weight: 0.02 kg

SWA2529W/10

# Highlights

## High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

## Bare copper shielding

Bare copper shielding protects against signal loss.

## Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

## Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

## Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

## Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

## Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2022-04-29

Version: 4.0.12

12 NC: 9082 100 09809  
EAN: 87 10895 99450 7

© 2022 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)