Philips USB wall charger

**Dual USB** 

USB A and Type-C charging port QC 3.0 and PD Foldable Prongs

DLP4314CW



# Wall charger USB A & Type-C port

### Maximum 18W Power Delivery

Charge your latest devices from this Type-C port to optimize the charging power and minimize the charging time. 3A output.

### **Top Performance**

- USB-C port with Power Delivery support
- 1 USB-A and 1 USB-C ports charge two devices simultaneously



## Specifications

### **Packaging dimensions**

- Number of products included: 1
- Packaging dimensions (W x H x D):  $9.5 \times 175 \times 3.5$  cm
- EAN: 48 95229 10761 8

### **Outer Carton**

- Number of consumer packagings: 24
- GTIN: 1 48 95229 10761 5

#### **Power**

- Output: USB-A QC3.0 & Type-C PD18W
- Power input: AC100 240V

#### **Product dimensions**

• Product dimensions (W  $\times$  H  $\times$  D):  $3.9 \times 6.3 \times 2.7$  cm

## Highlights

1 USB-A and 1 USB-C port 1 USB-A and 1 USB-C ports charge two devices simultaneosly. USB-A port works most of USBcharged devices while USB-C is the latet charging connector which is now adopted by mobile devices such as cell phones, outdoor cameras and tablets.

### **USB-C** port with PD

USB-C is the latet charging connector which is now adopted by mobile devices such as cell phones, outdoor cameras and tablets. PD (Power delivery) is the USB standard for power delivery which defines the standard for power delivery of 15W, 27W, 45W and up to 100W.



Issue date 2022-05-09

© 2022 Koninklijke Philips N.V. All Rights reserved.

Version: 1.0.3

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 66242

EAN: 48 95229 10761 8

www.philips.com