www.philips.com/welcome



# User Manual

## **PHILIPS**

## Warning:

- The product shall not be exposed to dripping or splashing and no objects filled with liquids, such as vases, shall be placed on the product.
- To completely disconnect the power input, the mains plug of the product shall be disconnected from the mains.
- The mains plug of the product should not be obstructed OR should be easily accessed during intended use.
   No paked flame sources such as lighted candles shall be placed.
- No naked flame sources, such as lighted candles, shall be placed on the products.

### Note:


- Make sure that the Multimedia Speakers are installed properly before using.
- You can see obvious color distortion if you place the Multimedia Speakers close to CRT display.

### System Requirements:


PC	Mac
Windows® 98SE, Windows® ME, Windows® 2000, Windows® XP, or Windows® Vista™,	Mac OS9/OS® X, or later
Windows 7	

#### Installation:


1 Insert the left speaker plug into TO LEFT SPEAKER socket on the right speaker.



 ${\bf 2}$   $\,$  Connect the audio input plug to the audio output of your computer.



- 3 Connect the AC power adaptor to:
  - the power socket at the back of the right speaker.
  - the wall socket



- 4 Turn the volume knob clockwise to switch on the Multimedia Speakers.
- 5 Adjust the volume by the volume knob, or by the computer application.
- 6 After use, switch off the speakers and unplug.


#### Optional function

#### To listen through a headphone:

Connect it to the  $\Omega$  socket on the right speaker.

#### To play music from an external audio device such as an MP3 player:

- 1 Connect an MP3 link cable (not supplied) to the AUX socket on the right speaker and the headphone socket on the device.
- 2 Play music on the device.



### Specifications

Amplifier	
Rated Output Power	2 X 20 W RMS
Frequency Response	60Hz - 16 KHz, -3 dB
Signal to Noise Ratio	>50 dB
Total Harmonic Distortion	<2%
MP3 link	600 mV
PC Input	600 mV

#### Speakers

Speaker 3	
Speaker Impedance	8 ohm
Speaker Driver	L/R 3"\>) Tweeter 1"\>) \\/\O\X 3"\>)

## General information

AC power	Model: AS360-180-Al200 (Philips); Input: 100-240V ~, 50/60 Hz, 1.2 A; Output: 18V === 2A
Operation Power Consumption	20W
Standby Power Consumption	<0.5W
Dimensions - Main Unit (W x H x D)	100 × 250 × 116.5 mm
Weight - With Packing - Main Unit	2.4 kg 2.0 kg

## Hearing safety





#### Caution

 To avoid hearing damage, limit the time you use the headphones at high volume and set the volume to a safe level. The louder the volume, the shorter is the safe listening time.

# Be sure to observe the following guidelines when using your headphones.

- Listen at reasonable volumes for reasonable periods of time.
- Be careful not to adjust the volume continuously upwards as your hearing adapts.
- Do not turn up the volume so high that you can't hear what's around you.
- You should use caution or temporarily discontinue use in potentially hazardous situations.
- Excessive sound pressure from earphones and headphones can cause hearing loss.



Your product is designed and manufactured with high quality materials and components, which can be recycled and reused. Please inform yourself about the local separate collection system for electrical and electronic products, including those marked by the crossed-out wheel bin symbol. Please act according to your local rules and do not dispose of your old products with your normal household waste.

























All registered and unregistered trademarks are property of their respective owners.

© 2012 Koninklijke Philips Electronics N.V.
All rights reserved.

SPA8210\_05\_UM\_V1.0