

car headlight bulb

# Ultinon Pro3100 SI

LED-White [≈P21W]

Number of bulbs: 2

12V, 6000 K daylight effect

Advanced automotive system



LUM11498CU31B2

# Stand out from the crowd

# Durable and vibrant LED signaling

For a stylish drive, upgrade to Philips Ultinon Pro3100 LED white [ $\approx$ P21W] for your reverse, stop, and rear fog signals. They are bright and look good so you can signal safely and stylishly.

# **Bright LED lights**

• Signal your intent with brighter exterior lighting

# **Good light distribution**

· Optimized for enhanced visibility

# **Long-lasting performance**

• Durable, long-lasting LED lighting

# Simple plug-and-play replacement

- Easy to install and compatible with many car models
- Easy to install on your car

# **Superior visibility for safer driving**

• Instant safety information for other drivers

# Specifications

# **Marketing specifications**

Product highlight: High brightness, Polarity-free,

Easy to install

**Expected benefits: Transform your lights** 

#### **Product description**

Application: Reverse lights, rear and front turn

indicators, stop lights, rear fog lights

Base: BA15s

Designation: LED-White [≈P21W]

Homologation ECE: NO Range: Ultinon Pro3100 Technology: LED

Type: LED-WHITE [~P21W]

### Lifetime

Life time: 3000 hrs

# **Light characteristics**

Lumens: 190

Color temperature: 6000 K

#### **Electrical characteristics**

Wattage: 2.2 W Voltage: 12V V

#### **Ordering information**

Order entry: 11498CU31B2 Ordering code: 72637330

# **Packaging Data**

EAN1: 6974260726373 EAN3: 6974260726380 Packaging type: B2

# **Packed product information**

Width: 1.5 cm Pack Quantity: 2

MOQ (for professionals): 10

Length [in]: 9.5 Height [in]: 13.5

#### **Outerpack information**

Gross weight per piece: 0.49 kg

Length [in]: 14.2 Width [in]: 12.1 Height [in]: 10.3

© 2025 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 69 74260 72637 3

Issue date 2025-05-14

Version: 4.4.1

