

car headlight bulb

# Ultinon Pro3100 SI

LED-Amber [≈WY21W]

Number of bulbs: 2

12V, Intense amber light

Advanced automotive system



LUM11071AU31B2

# Stand out from the crowd

# Durable and vibrant LED signaling

For a stylish drive, upgrade to Philips Ultinon Pro3100 LED amber [ $\approx$ WY21W] for your turn signals. They are bright, intense amber and look good so you can signal safely and stylishly.

# **Bright LED lights**

• Signal your intent with brighter exterior lighting

### **Good light distribution**

· Optimized for enhanced visibility

# **Long-lasting performance**

• Durable, long-lasting LED lighting

### Simple plug-and-play replacement

- Easy to install and compatible with many car models
- Easy to install on your car

#### **Superior visibility for safer driving**

• Instant safety information for other drivers

# Specifications

#### **Marketing specifications**

Product highlight: High brightness, Polarity-free,

Easy to install

**Expected benefits:** Transform your lights

#### **Product description**

**Application:** Rear and front turn indicators

Base: W3x16d

Designation: LED-Amber [≈WY21W]

Homologation ECE: NO Range: Ultinon Pro3100 Technology: LED

Type: LED-Amber [≈WY21W]

#### Lifetime

Life time: 3000 hrs

#### **Light characteristics**

Lumens: 140

Color temperature: Amber

#### **Electrical characteristics**

Wattage: 2.15 W Voltage: 12V V

#### **Ordering information**

Order entry: 11071AU31B2 Ordering code: 72649630

#### **Packaging Data**

EAN1: 6974260726496 EAN3: 6974260726502 Packaging type: B2

#### **Packed product information**

Width: 1.5 cm Pack Quantity: 2

MOQ (for professionals): 10

Length [in]: 9.5 Height [in]: 13.5

#### **Outerpack information**

Gross weight per piece: 0.49 kg

Length [in]: 14.2 Width [in]: 12.1 Height [in]: 10.3

© 2025 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change EAN: 69 7

without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

Issue date 2025-05-14 Version: 4.4.1

EAN: 69 74260 72649 6

