

PHILIPS

Stereo dubbing cable

1.5 m

3.5 mm (M) - 3.5 mm (M)

Coiled

SWA2529W



Ensure a reliable connection

with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

Protects against signal loss

- Bare copper shielding

Enjoy good audio quality

- High-purity copper conductor for reliable signal transfer

Easy installation

- Colour-coded connectors for instant recognition
- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Moulded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

Highlights

High-purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Bare copper shielding

Bare copper shielding protects against signal loss.

Colour-coded connectors

Colour-coded connections make it easy to install your cable into the correct inputs and outputs

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Moulded plug

Moulded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket

Flexible PVC jacket provides protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief

Rubber strain relief provides a secure yet flexible juncture between the cable and the plug.

Dimensions

Gross weight: 0.04 kg
Tare weight: 0.02 kg
Net weight: 0.02 kg
Product length: 23.5 cm
Product width: 95 mm
Product height: 22 mm

Packaging Data

EAN/UPC/GTIN: 87 10895 99450 7
Quantity: 1
Gross weight: 3 kg
Tare weight: 2 kg
Net weight: 1 kg

Outer Carton

Gross weight: 2.78 kg
Tare weight: 2.06 kg
Net weight: 0.72 kg
EAN/UPC/GTIN: 87 10895 99849 9
Height: 265 mm
Quantity: 36
Length: 340 mm
Width: 340 mm

Inner Carton

EAN/UPC/GTIN: 87 10895 99848 2
Quantity: 6
Gross weight: 0.38 kg
Length: 245 mm
Tare weight: 0.26 kg
Height: 105 mm
Width: 150 mm
Net weight: 0.12 kg

