



Philips
Stereo dubbing cable

0,75 m
3.5 mm (M) - 3.5 mm (M)
Black

SWA2532W

Ensure a reliable connection

with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Bare copper shielding

Easy installation

- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

Stereo dubbing cable
0,75 m 3.5 mm (M) - 3.5 mm (M), Black

SWA2532W/27

Specifications

Packaging dimensions

- Packaging dimensions (W x H x D): 9.5 x 23.5 x 2.1 cm
- Nett weight: 0.0184 kg
- Gross weight: 0.045 kg
- Tare weight: 0.0266 kg
- Packaging dimensions (W x H x D): 3.7 x 9.3 x 0.8 inch
- Gross weight: 0.099 lb
- Nett weight: 0.041 lb
- Number of products included: 1
- Packaging type: Blister
- Tare weight: 0.058 lb
- Type of shelf placement: Hanging
- UPC: 8 89446 00445 8

Outer Carton

- Outer carton (L x W x H): 32.1 x 25.7 x 22.2 cm
- Gross weight: 1.9 kg
- Tare weight: 1.4584 kg

- Gross weight: 4.189 lb
- GTIN: 1 08 89446 00445 5
- Outer carton (L x W x H): 12.6 x 10.1 x 8.7 inch
- Nett weight: 0.4416 kg
- Nett weight: 0.974 lb
- Number of consumer packagings: 24
- Tare weight: 3.215 lb

Inner Carton

- Inner carton (L x W x H): 24.4 x 10.2 x 9.8 cm
- Gross weight: 0.255 kg
- Tare weight: 0.1814 kg
- Gross weight: 0.562 lb
- GTIN: 2 08 89446 00445 2
- Inner carton (L x W x H): 9.6 x 4 x 3.9 inch
- Nett weight: 0.0736 kg
- Nett weight: 0.162 lb
- Number of consumer packagings: 4
- Tare weight: 0.4 lb

Highlights

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Bare copper shielding

Bare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.



Issue date 2015-06-02

Version: 1.0.2

12 NC: 8670 001 30995
UPC: 8 89446 00445 8

© 2015 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com