





# Ensure a reliable connection

# with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

# Enjoy good audio quality

- High purity copper conductor for reliable signal transfer
- Signal degradation is minimized with gold plated connectors

# **Protects against signal loss**

• Bare copper shielding

# **Easy installation**

• Non-slip ergonomic grip for easy use

# Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief



# Specifications

### **Packaging dimensions**

- Packaging dimensions (W x H x D): 9 x 24 x 4.8 cm
- Nett weight: 0.085 kg
- Gross weight: 0.09 kg
- Tare weight: 0.005 kg
- Number of products included: 1
- · Packaging type: Blister
- EAN: 87 12581 51688 8
- Type of shelf placement: Both

#### **Outer Carton**

• Outer carton (L x W x H): 36.5 x 26.5 x 22 cm

- Nett weight: 2.040 kg
- Gross weight: 3.44 kg
- Tare weight: 1.400 kg
- EAN: 87 12581 51683 3
- Number of consumer packagings: 24

### **Inner Carton**

- Inner carton (L x W x H):  $25 \times 10 \times 11$  cm
- Nett weight: 0.340 kg
- Gross weight: 0.51 kg
- Tare weight: 0.170 kg
- EAN: 87 12581 51687 1
- Number of consumer packagings: 4

# SWA<del>4</del>522S/10

# Highlights

### Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

## **Rubber strain relief**

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Bare copper shielding Bare copper shielding protects against signal loss.

### Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

#### **High purity copper**

This copper conductor provides high accuracy in signal transfer with minimal resistance.

#### **Gold plated connectors**

High quality connectors which minimize signal loss.



© 2022 Koninklijke Philips N.V. Issue date 2022-05-12 Version: 2.0.8

All Rights reserved. Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 000 58288 EAN: 87 12581 51688 8

www.philips.com