





# Ensure a reliable connection

## with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

### Enjoy good audio quality

- High purity copper conductor for reliable signal transfer
- Signal degradation is minimized with gold plated connectors

### **Protects against signal loss**

• Bare copper shielding

### **Easy installation**

• Non-slip ergonomic grip for easy use

### Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief



## Specifications

#### **Packaging dimensions**

- Type of shelf placement: Both
- Packaging dimensions (W x H x D):
- 8.9 x 24 x 2.6 cm
- Nett weight: 0.028 kg
- Gross weight: 0.053 kg
- Tare weight: 0.025 kg
- Number of products included: 1
- Packaging type: Blister
  EAN: 87 12581 51688 8

#### **Outer Carton**

• Outer carton (L x W x H): 31.2 x 26.2 x 24.5 cm

- Nett weight: 0.672 kg
- Gross weight: 1.98 kg
- Tare weight: 1.308 kg
- EAN: 87 12581 51683 3
- Number of consumer packagings: 24

#### **Inner Carton**

- Inner carton (L x W x H): 24.7 x 9.7 x 11.1 cm
- Nett weight: 0.112 kg
- Gross weight: 0.28 kg
- Tare weight: 0.168 kg
- EAN: 87 12581 51687 1
- Number of consumer packagings: 4

### WA4522S/10

## Highlights

#### Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

#### **Rubber strain relief**

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Bare copper shielding Bare copper shielding protects against signal loss.

#### Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

#### **High purity copper**

This copper conductor provides high accuracy in signal transfer with minimal resistance.

#### **Gold plated connectors**

High quality connectors which minimize signal loss.



Issue date 2021-09-17

© 2021 Koninklijke Philips N.V. All Rights reserved.

Version: 1.0.7

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 000 58288 EAN: 87 12581 51688 8

www.philips.com