



Philips 6000 series
Smart lever door lock

Slim body design

IP65-certified
C-grade lock cylinder

DDL608LKKBW

43mm* minimalist body

Suitable for narrow frame doors

Enjoy the safety and convenience brought by DDL608-5HWS! The 43mm minimalist body design allows it to fit narrow frame doors, such as aluminum alloy doors, bridge-cut-off doors, sliding doors, push-pull doors, framed doors, etc.

Secure protection, smart embedded

- Instantly push notifications to the App
- Instantly protect home security at all times

Craftsmanship ensures high quality

- Fit for multiple narrow frame doors
- Ready for preventing dust and water

Smart life "locked" with excellence

- Say goodbye to the key-only era

PHILIPS

Highlights

Slim lock body design



Designed with a 43mm narrow lock body, DDL608-5HWS can be installed on doors with a thickness of 35-120mm*, such as aluminum alloy doors, bridge-cut-off doors, sliding doors, push-pull doors, framed doors, etc. It is suitable for a variety of scenarios.

IP65-certified



DDL608-5HWS has passed the IP65 dustproof and waterproof test, effectively preventing dust and low-pressure water from damaging the door lock, which helps stabilize the product performance and extend the product life span.

Various ways of unlocking



Fingerprints, PIN codes, key tags, and mechanical keys are available unlocking methods, which can

meet the need of different users, perfect for the whole family.

Duress access methods to unlock



When encountering an abnormal condition, you can use the preset duress access methods (fingerprint, PIN code, and key tag available) to unlock. Then the lock will push the duress alarm information to the user and the user sharing the device in real-time, and the mobile App will synchronize the pop-up alarm to give security warning to help reduce the hidden danger of home security.

Multiple alerting



Featured with multiple alerts such as anti-dismantling, system locking, and low battery level, Philips DDL608-5HWS instantly safeguards your family and reminds you of the lock status, making you feel assured and secure.

Specifications

Design & Appearance

- Color: Black
- Handle: Lever handle
- Main Material: Aluminium alloy

Access Solution

- Fingerprint
- Password/PIN Code
- Temporary PIN code
- Card/Key Tag
- Mechanical Key

Power Specification

- Power Supply: 4 AAA batteries
- Battery Type: Alkaline Batteries
- Time of Use: 10 months*
- Emergency Power Supply: 5V power bank

Easy Operation

- Voice Guide: Human voice guide

Smart Lock Functions

- Mortise: C grade lock cylinder

Installation

- Door Thickness: 35-60mm, 45-70 mm, 55-80 mm, Other range*
- Door Opening Direction: Left inward opening, Left outward opening, Right inward opening, Right outward opening

* 43mm: data from actual measured size, and the tolerance should be less than ± 2 mm.

* 35-120mm: the attached installation kit is suitable for thickness of 35-60mm doors; if the door thickness is 60-120mm, please consult the Philips smart lock authorized consumer care centers or designated offline dealers.

* 10 months: this is internal test data; actual duration may vary with usage frequency.

* The digital keypad shown in the product photos may differ from the actual display. Please refer to the digital keypad's appearance during actual use.



Issue date 2024-10-12

Version: 4.4.1

© 2024 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com