PHILIPS

Dispenser

Bottom loading

Three nozzles

UV

ADD4970DGS

Bottle water redefined

UV kills 99.9% bacteria in the cold water tank**

This floor-standing bottled water dispenser comes with a UV-LED disinfection function which kills up to 99.9% bacteria in the cold water tank** to ensure the cleanness of water.

Cleaner water

- UV-LED kills 99.9% bacteria in the cold water tank**

Thoughtful design for your convenience

- Compressor cools water efficiently
- Wide dispensing area fits various sizes of containers
- Z-shape 304 stainless steel water pipe

Safeness assured

- Child lock to prevent hot water burns

Highlights

UV disinfection
Since there's no chlorine, bacteria tend to grow in the water that sits inside the bottle or the cold water tank. Therefore we have the advanced UV-LED light technology installed in the cold water tank which kills up to 99.9% becteria**. The UV-LED light activates for 1 hour once the dispenser is connected with power, and works for 1 hour for every 2 hours to make sure the water stay clean.

Compressor cooling
Compressor cooling produces cool water more efficienty and faster, compared to conventional thermoelectric cooling.

Wide water dispensing area
Wide dispensing area easily fits various sizes of cup, glass, bowl and even pot.

Z-shape water pipe
The 304 stainless steel water pipe is anti-rust, and the Z-shape helps to reach the bottom of the bottle so that there's no remaining water.

Child lock for hot water
Child lock for hot water keeps children safe from accidental hot water burns.

Specifications

General specifications
Voltage and frequency: 220V-240V~, 50Hz/60Hz
Cold water temperature: 10 °C
Hot water temperature: 90 °C

Power
Cooling: 85W
Heating: 500W

Country of origin
Water dispenser: China

© 2025 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

Issue date 2025-11-17
Version: 1.0.1

EAN: 48 95244 60392 8

www.philips.com

* *Tested by SGS under laboratory conditions.