

Philips OlfaPure  
Car Aroma Cartridge -  
Anti-V

Fresh, Aromatic

LUMAC109BLKX1



## Select your scent. Enhance your mood

Fragrances to enhance your driving experience

Specially designed to combine with odor molecules, like cigarette smoke or food, thus refreshing the air in your car.

**Broad portfolio of French designed fragrances**

- Choose the right aroma to enhance your mood

**Natural safe-to-use ingredients**

- Aromas comply with IFRA safety standards

# PHILIPS

# Specifications

## Marketing specifications

- Product highlight: Natural ingredients safe to use
- Expected benefits: Fresh, Aromatic

## Product description

- Color: Black
- Designation: Car Aroma Cartridge - Anti-V
- Range: OlfaPure

## Ordering information

- Order entry: AC109BLKX1
- Ordering code: 2104530

## Logistic data

- Quantity in box: 10
- EAN1: 8719018021045
- Ordering code (GOC): 2104530

## Weight and dimensions

- Box weight (incl. product) (g): 40
- Product weight (g): 24
- Box dimensions (LxWxH)(mm): 140x45x25
- Product dimensions (LxWxH)(mm): 22\*19\*105

## Packaging Data

- EAN1: 8719018021045
- EAN3: 8719018021052

## Packed product information

- Pack Quantity / MOQ: 10

## Outerpack information

- Length: 29 cm
- Width: 15 cm
- Height: 6 cm
- Gross weight per piece: 491.6 kg

# Highlights

## Fresh, Aromatic eucalyptus

Choose the right aroma to enhance your mood

## IFRA certified safe to breathe

The fragrances used by the OlfaPure 7100 have been tested to ensure compliance with the International Fragrance Association (IFRA) standards. This checks that the scent contains the correct volumes of essential oils, and that all ingredients are safe for use.



Issue date 2024-01-23

Version: 4.4.1

© 2024 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)

\* Anti-V helps neutralize airborne microbes, tested against airborne pathogens via quantitative suspension test in an independent lab, meeting French government Standard NF EN 14476.