



Brilliant interactive display with SmoothTouch

A sturdy, water and dust resistant touch screen monitor for flexible use anywhere, with articulating stand to fit angles you need. Offering simple and intuitive use across applications, greatly boosts up productivity.

Brilliant interactive display

- SmoothTouch display for natural, fluid touch response
- EasyRead mode for a paper-like reading experience
- LowBlue Mode for easy on-the-eyes productivity
- SmartContrast for rich black details
- Stylus for fluid and accurate performance with more control
- Monitor front surface meets IP65 for water & dust resistance

Easy to experience

- HDMI ensures universal digital connectivity
- DisplayPort connection for maximum visuals
- · VESA mount allows for flexibility
- USB 3.1 high speed data transfer
- · SmartStand with adjustable angles, boosts productivity

Highlights

SmoothTouch



This Philips display uses Projected capacitive 10 point touch technology for fluid response. You can fully utilize the new capabilities of touch based applications, and bring your older applications to life. Touch-type with 10 fingers, or play exciting interactive games with your friends. Collaborate with colleagues interactively at work or school environment and increase your productivity and efficiency.

Water and dust resistant



For less than perfect environments, you need a monitor that's designed to hold up to the splashes of water and dust that happen in the everyday world. Ingress Protection (IP) ratings defined in international standard IEC/EN 60529, are used to define levels of sealing effectiveness of electrical enclosures against intrusion from foreign bodies and moisture. This Philips display meets international the IP rating for water and dust resistance, it will hold up to water splashes and dust that happen in the everyday world.

SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

EasyRead mode



EasyRead mode for a paper-like reading experience

SmartStand

Philips SmartStand allows for flexible adjustment of the screen. Its Z type structure with smooth tilt, height adjustment and folding capabilities enables you to use it in various ergonomic positions. You can set the stand in upright position for better touch control, or recline it backwards, making it easy for you to draw or annotate. It even allows you to put the screen almost flat on the table for some applications when required.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables high-quality digital video and audio all transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

















Highlights

High speed data transfer

USB 3.1 high speed data transfer

DisplayPort connection



DisplayPort is a digital link from PC to Monitor without any conversion. With higher capabilities than DVI standard, it is fully capable to support

up to 15meter cables and 10.8 Gbps/sec data transfer. With this high performance and zero latency, you get the fastest imaging and refresh rates - making DisplayPort the best choice for not only general office or home use, but also for the demanding gaming and movies, video editing and more. It also keeps interoperability in mind via use of various adapters.

VESA mount

VESA mount allows for flexibility













Specifications

Picture/Display

Panel Size: 15.6 inch / 39.6 cm

Aspect ratio: 16:9

LCD panel type: TFT-LCD (TN) Backlight type: W-LED system Pixel pitch: 0.252 x 0.252 mm

Optimum resolution: 1366 x 768 @ 60Hz

Brightness: 220 cd/m² Display colors: 262 K

Color gamut (typical): NTSC 86%*, sRGB 100%*

Contrast ratio (typical): 500:1 SmartContrast: 20,000,000:1

Response time (typical): 4 ms (Gray to Gray)* Viewing angle: 90° (H) / 60° (V), @ C/R > 10

Picture enhancement: SmartImage Effective viewing area: 344.2 (H) x 193.5 (V) Scanning Frequency: 30 - 60 kHz (H) / 50 - 75 Hz

(V) sRGB

Pixel Density: 100 PPI LowBlue Mode **EasyRead**

Touch

Ingress protection: IP65 - front only Operating system: Windows 10 / 8.1 / 8 / 7; Android 7.1 / 7.0 / 6.0 / 5.0 / 4.4; certain Linux versions*

Sealability: Touchscreen sealed to bezel;

Touchscreen sealed to LCD

Touch active area: 344.2 mm (H) x 193.5 mm (V)

D

Touch glass hardness: 7 H Touch interface: USB

Bottom

USB UP

Touch method: Stylus, Finger, Glove*

Touch points: 10 point

Touch technology: Projected capacitive Palm rejection area: >= 25 x 25 mm

Touch glass coating: Glare

Connectivity

Signal Input: VGA (Analog), DVI-D (digital, HDCP),

DisplayPort 1.2, HDMI 1.4

USB: USB 3.1x2 (1 w/fast charging)* Sync Input: Separate Sync, Sync on Green Audio (In/Out): PC audio-in, Headphone out HDCP: HDCP: HDCP 1.4 (HDMI / DP / DVI)

Convenience

Built-in Speakers: 2 W x 2

Plug & Play Compatibility: DDC/CI, sRGB, Windows

10 / 8.1 / 8 / 7

User convenience: SmartImage, Input, Brightness,

Menu, Power On/Off

OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian Other convenience: Kensington lock, VESA mount (100x100mm)

Control software: SmartControl

Height adjustment: 184 (Horizontal), 105

(Vertical) mm Tilt: -5 ~ 90 degree

(O(....)O)

Folding angle: 0 ~ 70 degree

Power

ECO mode: 5.6 W (typ.)

Power supply: External, 100-240VAC, 50-60Hz

Off mode: 0.3 W (typ.)

On mode: 7.1 W (typ.) (EnergyStar test method)

Standby mode: 0.3 W (typ.)

Power LED indicator: Operation - White, Standby

mode-White (blinking) **Energy Label Class: E**

Dimensions

Packaging in mm (WxHxD): 445 x 388 x 159 mm Product without stand (mm): 378 x 241 x 42 mm Product with stand(max height): 378 x 347 x 227 mm

Weiaht

Product with packaging (kg): 6.31 kg Product with stand (kg): 5.00 kg Product without stand (kg): 2.01 kg

Operating conditions

Altitude: Operation: +12,000ft (3,658m), Non-

operation: +40,000ft (12,192m)

Temperature range (operation): 0°C to 40°C °C

Relative humidity: 20%-80 %

Temperature range (storage): -20°C to 60°C °C MTBF (demonstrated): 70,000 hrs (excluded backlight)

Sustainability

Environmental and energy: EnergyStar 8.0,

EPEAT*, RoHS, WEEE

Recyclable packaging material: 100 % Specific Substances: PVC / BFR free housing,

Mercury free

Compliance and standards

Regulatory Approvals: CB, CE Mark, FCC Class B, SEMKO, UKRAINIAN, ICES-003, TUV/GS, TUV Ergo, CU-EAC, EAEU ROHS

Cabinet

0

Finish: Texture Foot: Black Front bezel: Black

Rear cover: Black



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

Issue date 2025-04-06 Version: 1.0.3

DVI⊕

HDMI

UPC: 6.09585.25662.0

www.philips.com



AUDIO

- * Response time value equal to SmartResponse
- * NTSC Area based on CIE1976
- * sRGB Area based on CIF1931
- * Glove material and thickness: Nitrile (0.15 mm), Cotton (0.31 mm). CPE (0.03 mm), PVC (0.12 mm)
- * Please refer to "SmoothTouch" in user manual for more details of operating systems support in touch function.
- * Fast charging complies with USB BC 1.2 standard
- * EPEAT rating is valid only where Philips registers the product. Please visit https://www.epeat.net/ for registration status in
- * The monitor may look different from feature images.