



Q-Line Display

- 43"
- Direct LED Backlight
- Ultra HD

43BDL3650Q/00

Stand out from the crowd

Your versatile and easy-to-set-up 18/7 display

Inform and enthrall with a Philips Q-Line 4K Ultra HD digital display. This reliable, easy-to-install, Android powered signage solution is Wave-ready for remote management, putting you in full control, any time, anywhere.

Benefits

Effortless setup. Total control.

- Optional Interact for wireless screen share
- Catch the Wave for revolutionary results

Cost-effective system solution

- Easy control. Remotely manage networked displays
- Easily schedule content from USB or internal memory

Smart and powerful

- Connect and control your content via the cloud
- Android SoC processor. Native and web apps
- WiFi connection made easy with optional CRD22 module

Versatile system solution

- Ultra-HD. Rich images. Stunning contrast
- FailOver. Ensure your display never goes blank

Features

SmartBrowser

Connect and control your content via the cloud with the integrated HTML5 browser. Using the Chromium based browser, design your content online and connect a single display, or your complete network. Show content in both landscape and portrait mode, with fullHD resolution. Simply connect the

display to the internet using WiFi or with an RJ45 cable, and enjoy your own created playlists.

PHILIPS

FailOver

Critical for demanding commercial applications, FailOver is a revolutionary technology that automatically plays back-up content on screen in the unlikely event of an input source or application failure. Simply select a primary input connection and a FailOver connection and you are ready for instant content protection.

Integrated media player

Easily schedule content to play from USB or from internal memory. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback is done.

Interact (optional)

Wirelessly screen share using your existing Wi-Fi network to instantly and securely connect devices, or use our optional HDMI Interact dongle to cast directly onto the screen without connecting into the secured network.

Specifications

[field not found 'disclaimer_text']

Picture/Display

Diagonal screen size (metric)	108 cm
Diagonal screen size (inch)	42.5 inch
Panel resolution	3840 x 2160
Optimum resolution	3840 x 2160 @ 60 Hz
Brightness	400 cd/m ²
Contrast ratio (typical)	1200:1
Dynamic contrast ratio	500,000:1
Response time (typical)	8 ms
Aspect ratio	16:9
Viewing angle (horizontal)	178 degree
Viewing angle (vertical)	178 degree
Pixel pitch	0.2451 x 0.2451 mm
Display colors	1.07 Billion
Panel technology	ADS
Picture enhancement	3/2 - 2/2 motion pull down Dynamic contrast enhancement Progressive scan
Operating system	Android 10
Haze	2%

Supported Display Resolution

Computer formats	1024 x 768, 60, 70, 75Hz
	1280 x 1024, 60Hz
Video formats	1280 x 720, 60Hz
	1280 x 800, 60Hz
	1440 x 900, 60Hz
	1600 x 1200, 60Hz
	1680 x 1050, 60Hz
	1920 x 1080, 60Hz
	3840 x 2160, 60Hz
	1080p, 50, 60Hz
	1080i, 50, 60Hz
	720p, 50, 60 Hz
	2160p, 50, 60Hz

Connectivity

Video input	HDMI 2.0 (x2)
	USB 2.0 (x2)
	DVI-I (x 1)
	USB 3.0 (x1)
Audio input	3.5 mm jack
Audio output	3.5mm jack
External control	RJ45
	RS232C (in/out) 2.5 mm jack
	IR (in/out) 3.5 mm jack

Powered by Android 10

Powered by our Android 10 SoC platform, these hard-working Philips professional displays are optimised for native Android apps, and you can install web apps directly onto the display too. Flexible and secure, ensuring display specs stay up to the moment for longer.

PPDS Wave

Unlock the power, versatility and intelligence inside your Philips Q-Line displays remotely with Wave. This evolutionary cloud platform puts you fully in control, with simplified installation and set-up, monitoring and controlling displays, upgrading firmware, managing playlists and setting power schedules. Saving you time, energy and environmental impact.

Other connections	micro SD
-------------------	----------

Convenience

Energy saving functions	Smart Power
Tiled Matrix	Up to 3 x 3
Keyboard control	Lockable Hidden
Network controllable	RS232 RJ45
Signal loop through	RS232 IR Loophrough
Placement	Landscape (18/7) Portrait (18/7)
Remote control signal	Lockable

Dimensions

Bezel width	13.9 mm (Even bezel)
Set Width	973.0 mm
Set Height	561.2 mm
Set Depth	63.5 mm mm
Set Width (inch)	38.31 inch
Set Height (inch)	22.09 inch
Set Depth (inch)	2.50 inch
Wall Mount	200 mm x 200 mm, M6
Product weight	11.29 kg
Product weight (lb)	24.91 lb

Operating conditions

Temperature range (operation)	0 ~ 40 °C
Temperature range (storage)	-20 ~ 60 °C
MTBF	50,000 hour(s)
Humidity range (operation)[RH]	20 ~ 80% RH (No condensation)
Humidity range (storage) [RH]	5 ~ 95% RH (No condensation)
Altitude	0 ~ 3000 m

Power

Mains power	100 - 240V~, 50/60Hz
Standby power consumption	<0.5 W
Consumption (Max)	170 W
Consumption (Typical)	96 W
Power Saving Features	Smart Power
Energy Label Class	G

Sound

Built-in speakers 2 x 10W RMS

Multimedia Applications

USB Playback Video H.264
MPEG
H.263
H.265
AVI
MP4
VP8
USB Playback Picture BMP
JPEG
PNG
USB Playback Audio AAC
HEAAC
MPEG

Accessories

Included Accessories IR sensor cable (1.8 m) (x1)
RS232 daisy-chain cable
Philips logo (x1)
AC Power Cord
AC Switch Cover
Quick start guide
Remote control & AAA batteries
RS232 cable
USB cover and screws
Wire Clamper (x3)

Miscellaneous

Warranty 3 year warranty
On-Screen Display Languages English
French
German
Italian
Polish
Russian
Spanish
Turkish
Simplified Chinese
Traditional Chinese
Arabic
Japanese
Regulatory approvals CE
CB
FCC, Class A
VCCI
RoHS
UL

Internal Player

CPU Quad Core Cortex A55
GPU G52 MC1
Memory 16GB
3GB DDR



data subject to change
2023, August 16

Version: 2.0.1
EAN: 8712581799298

© 2023 Koninklijke Philips N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com