

PHILIPS



Collaboration
Display

Signage Solutions

65"

Powered by Android

Multi-touch



65BDL3152E

Interactive display

Featuring multi-touch technology

This interactive display maximises engagement and inspires collaboration with up to 40 touchpoints. Powered by Android 13 and with toughened anti-glare and anti-reflection glass, it's made to withstand heavy daily use in busy environments.

Smart and powerful

- OPS slot allows PC embedding without cabling
- Android SoC for seamless software and app integration
- PPDS Wave-ready for remote display management and control
- Built-in ambient light sensor

Style and safety built in

- Cast directly from any device
- Anti-glare toughened glass
- Palm rejection

Interactive and collaborative

- Wireless presentations
- Whiteboard application
- Multi-touch technology capable of 40 touchpoints
- Advanced IR touch

Highlights

OPS slot

Integrate a full-power PC or Android-powered CRD module directly into your Philips Professional Display. The OPS slot contains all of the connections you need to run your slot-in solution, including a power supply.

Powered by Android

Our integrated Android 13 OS has been specially developed to bring a next-level secure professional System on Chip. Save your favourite apps and software directly into the display or choose from the large library of Android apps.

Anti-glare toughened glass

Anti-glare, anti-reflection, 7 MoH hardness.

PPDS Wave ready

Your PPDS Wave-ready display enables you to manage and maintain this device remotely, wherever you are, whenever you choose. This evolutionary cloud platform puts you fully in control, with simplified installation and setup, monitoring and controlling displays, upgrading

firmware, managing central content needs and setting power schedules — saving you time, energy and environmental impact.

Built-in ambient light sensor

Built-in ambient light sensors contribute to energy savings by automatically adjusting the screen brightness to the surrounding lighting conditions.

Palm rejection

Palm rejection for enhanced precision.

Multi-touch technology

Create a memorable interactive experience with up to 40 touchpoints at the same time for slick, agile lessons or brainstorming sessions. Perfect for collaborative and co-creation applications, this display connects your audience with any content. Offering enhanced user friendliness with eraser functionality, palm rejection and tip-size recognition.

Wireless presentations

Philips ScreenShare makes it easy for teachers and students to wirelessly share their screens from their own device, whatever the operating system, via the browser or their favourite apps, onto the Philips Collaboration display.

Whiteboard application

The embedded whiteboard application enables seamless collaboration and brainstorming directly on the display.

Advanced IR touch

Advanced 0-gap IR touch with smaller, shallower bezels.

Cast directly from any device

Teachers, students or employees can cast directly from their device with AirPlay, Google Cast and Miracast.

Specifications

Picture/Display

Diagonal screen size (metric): 163.9 cm

Diagonal screen size (inch): 65 inch

Aspect ratio: 16:9

Panel resolution: 3840 x 2160

Pixel pitch: 0.372 (H) x 0.372 (V) [mm]

Optimum resolution: 3840 x 2160 @ 60 Hz

Brightness: 400 cd/m²

Display colours: 1.07 B

Contrast ratio (typical): 5000:1

Response time (typical): 6.5 ms

Viewing angle (horizontal): 178 degree

Viewing angle (vertical): 178 degree

Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, Progressive scan, 3D MA deinterlacing, Dynamic contrast enhancement

Panel technology: VA

Operating system: Android 13

OS UI resolution: 1920 x 1080 @ 60 Hz

Connectivity

Audio output: 3.5 mm Mini Jack (x 1), SPDIF

Video input: VGA (Analogue D-Sub) (x 1), USB-C (up to 65 W), HDMI 2.0 (x 3), USB 2.0 (x 1), USB 3.0 (x 4)

Audio input: 3.5 mm mini jack (x 1)

Other connections: OPS, USB-B (x 2)

External control: RS232C (in) D-Sub9, RJ45 x 2

Bluetooth: BT5.2

Convenience

Placement: Landscape (16/7)

Screen-saving functions: Pixel Shift, Low Brightness

Keyboard control: Lockable

Remote control signal: Lockable

Other convenience: Carrying handles

Network controllable: RS232, RJ45

Sound

Built-in speakers: 2 x 16 W

Power

Mains power: 100 ~ 240 VAC, 50/60 Hz

Consumption (Typical): 140 W

Standby power consumption: <0.5 W

Power Saving Features: Smart Power

Energy Label Class: F

Supported Display Resolution

Video formats: 480i, 60 Hz, 480p, 60 Hz, 720p, 50, 60 Hz, 1080i, 50, 60 Hz, 1080p, 50, 60 Hz, 2160p, 30, 60 Hz

Dimensions

Set Width: 1488.4 mm

Set Height: 896.6 mm

Weight: 35.45 kg

Set Depth: 86.2 mm

Set Width (inch): 58.6 inch

Set Height (inch): 35.28 inch

Wall Mount: 600 x 400 mm, M8

Set Depth (inch): 3.40 inch

Bezel width: 16.6mm(L/F/R) / 45.0 mm(B)

Bezel width (L/R, T/B): 16.6 mm (L/F/R)/45.0 mm (B)

Weight

Product with packaging (kg): 47 kg

Product with packaging (lb): 103.62 lb

Product without stand (kg): 35.45 kg

Product without stand (lb): 78.15 lb

Operating conditions

Altitude: 0 ~ 5000 m

Temperature range (operation): 0 ~ 40 °C

MTBF: 50,000 hour(s)

Temperature range (storage): -20~60 °C

Humidity range (operation)[RH]: 10~90% (without condensation)

Humidity range (storage) [RH]: 10~90% (without condensation)

Multimedia Applications

USB Playback Video: H.263, H.264, H.265,

MPEG1/2, MPEG4, VP8

USB Playback Picture: BMP, JPEG, PNG

USB Playback Audio: AAC, MPEG, HEAAC

Internal Player

CPU: Quad-Core Cortex A55

GPU: Multi-Core Mali-G52

Memory: 4 GB RAM

Storage: 32 GB eMMC

Wi-Fi: 2.4/5 GHz

Accessories

Accessories: Power code (US, UK, EU), HDMI cable, USB-A to B, Remote control and AAA batteries, 2 pcs stylus, Quick start guide, Wall mount

Miscellaneous

On-Screen Display Languages: Arabic, Dutch, Danish, English, French, Finnish, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Simplified Chinese, Turkish, Traditional Chinese

Warranty: 5-year warranty

Regulatory approvals: CE, FCC, Class A, RoHS, CB, EAC, EMF, ETL, Energy Star 8.0

Interactivity

Multi-touch technology: 0-gap Infrared touch

Touchpoints: 50 simultaneous touch points(depending on application)

Plug and play: HID compliant

Protection glass: Anti-Glare, Tempered safety glass 7 MOHS

