

C-Line Display

- 86"
- Powered by Windows
- 350cd/m²

86BDL8051C/00

Interactive meeting display

high-end capacitive multi-touch technology

Maximise engagement and inspire collaboration with an interactive Philips C-Line display. These Windows powered displays are made to withstand heavy daily usage, and feature up to 10 touchpoints, edge-to-edge glass and flush design.

Benefits

Interactive and collaborative

- Wireless screen sharing & advanced collaboration
- HID Capacitive Touch with USB Plug & Play
- Operate, monitor and maintain with CMND & Control
- Works with iOS, Android, Windows, Mac

Smart and powerful

• Powered by Windows 10

- Whiteboard mode built-in
- Fast and easy video conferencing
- Crestron Connected certified
- Anti-glare toughened glass
- Install and use your preferred apps and features
- Annotate over any source and save screenshots



Features

Wireless screen sharing

Display four feeds on the one screen. Use your existing Wi-Fi network to instantly and securely connect devices, or use the two included HDMI dongles to cast directly to the screen without needing to connect to your secured/ protected network.

HID Capacitive Touch

Capacitive Touch gives you the cutting edge appearance of edge to edge glass with a bezel width of just 1.5 mm! Create a memorable interactive experience with up to 10 touchpoints at the same time. Perfect for collaborative and competitive applications, this display connects your audience with any content - making it ideal for education, public venues, corporate, hospitality, and retail settings.

Powered by Windows 10

Powerful Core i7 processor with nVidia GPU. Runs all your favorite apps like Zoom, Skype (included) and MS Teams, MS Office, (not included)

Whiteboard mode built-in

Inspire agile collaboration with whiteboard mode. Simply activate this feature to turn your display into a blank canvas that can be drawn on by multiple users by hand or with dedicated display markers. Everything on screen can then be captured for easy printing or file sharing.

Fast and easy video conference

Ready to use video conferencing software makes one-to-one or group video calls easier than ever. Simply use your own camera or add the optional Logitech Meetup bundle for an all-in-one ConferenceCam solution.

Crestron Connected certified

Integrate this Philips Professional Display to your Crestron network for full remote control via your laptop, desktop or mobile device. Switch the display on and off, schedule content, manage settings, and easily connect external devices. Crestron Connected® provides a fast, reliable and secure enterprise level solution for for system control.

CMND & Control



Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

Specifications

[field not found 'disclaimer_text']

Picture/Display DisplayPort 1.2 (x1) Video output Diagonal screen size DVÍ - D (x1) 85.6 inch HDMI 2.0 (x2) (inch) Diagonal screen size 217.42 cm Audio input 3.5mm Jack (x1) Audio output 3.5mm Jack (x2) micro SD 3840×2160 Other connections 3840x 2160 @ 60Hz OPS 350 cd/m² External control **RJ45** 1000:1 RS232C (in/out) 2.5 mm jack IR (in/out) 3.5 mm jack 500,000:1

Supported Display Resolution

1920 x 1200, 60Hz Computer formats 1920 x 1080, 60Hz 1680 x 1050, 60Hz 1600 x 1200, 60Hz 1600 x 900, 60Hz 1440 x 1050, 60Hz 1440 x 900, 60, 75Hz 1400 x 1050 ,60, 75Hz 1366 x 768, 60Hz 1360 x 768, 60Hz 1280×1024, 60,67,75Hz 1280 x 960, 60Hz 1280 x 800, 60,75Hz 1280 x 768, 60Hz, 75Hz 1280 x 720, 60,70Hz 1152 x 900, 66Hz 1152 x 864, 60, 70, 75Hz 1024x768, 60,70Hz 960x720, 75Hz 848 x 480, 60Hz 832 x 624, 75Hz

> 800×600 , 56, 60, 72, 75Hz $720 \times 400, 70Hz$

(metric) Panel resolution Optimum resolution Brightness Contrast ratio (typical) Dynamic contrast ratio Aspect ratio 16:9 Response time 8 ms (typical) 0.4935 (H) x 0.4935 (V) mm Pixel pitch Display colors 1.07 billion Viewing angle (hori-178 degree zontal) 178 degree Viewing angle (vertical) Picture enhancement 3/2 - 2/2 motion pull down Motion compens. deinterlacing 3D MA deinterlacing Dynamic contrast enhancement Progressive scan Operating system Windows 10 Connectivity Video input Display Port1.2 (x1) HDMI 2.0 (x4) DVI-I (x 1)

USB 2.0 (x2)

USB 3.0 (x2)

USB-C

640 x 350, 70Hz IR sensor cable (1.8 m) (x1) 640 x 480, 60, 67, 72, 75Hz M2 Screw (x2) Video formats 1080p, 50, 60Hz M3 screw (x2) 576p, 50Hz Power cable (x3) 480p, 60Hz Touch Pen (x2) USB A to B cable (3m) (x1) 1080i, 50, 60Hz 4K x 2K, 50,60Hz USB Cover (x1) 720p, 50, 60Hz AAA batteries (x1) 480i, 60Hz Quick start guide (x1) **UHD** Formats 3840 x 2160, 24, 25, 30, 60 Hz Remote control (x1) 3840 x 2160, 50 Hz RS232 cable (3 m) (x1) Multimedia Applications **Dimensions** 1949 mm Set Width USB Playback Audio AAC M4A Set Height 1120.00 mm Set Depth 77.50(@wall mount), 93.00(@max) MP3 WMA mm Set Width (inch) 76.73 inch USB Playback Picture **BMP** Set Height (inch) 44.09 inch **JPEG** 3.05(@wall mount), 3.66(@max) inch Set Depth (inch) JPG Bezel width 1.50 mm(even) PNG Product weight (lb) 175.27 lb USB Playback Video ASF 79.5 kg Product weight AVI 600(H)x400(V) mm, M8 Wall Mount **FLV** Smart Insert mount 6*M4*L6, 100mm pitch, Max. Size: MKV 300mmx180mm MP4 MPEG MPG Convenience TS **Placement** Landscape VOB Landscape (18/7) **WEBM** Keyboard control Hidden WMV Lockable DAT RS232 Signal loop through IR Loopthrough Miscellaneous Network controllable RJ45 RS232 On-Screen Display English Energy saving func-Smart Power Languages French German tions Pixel Shift, Low Bright Spanish Screen saving func-Polish tions Ease of installation Smart Insert Turkish DPMS power saving Russian system Italian Simplified Chinese Power Traditional Chinese Arabic <0.5 W Standby power Japanese consumption Danish Mains power 100 ~ 240 VAC, 50 ~ 60 Hz Dutch Consumption 300 W **Finnish** (Typical) Norwegian Consumption (Max) 460 W Portuguese **Energy Label Class** G Swedish CF Regulatory approvals Operating conditions RoHS Temperature range 0 ~ 40 °C CB (operation) CU Temperature range -20 ~ 60 °C **EMF** FCC, Class A (storage) 20 ~ 80%(operating),5 ~95%(storage) Relative humidity ETL **PSB** 0 ~ 3000 m Altitude Warranty 3 year warranty **MTBF** 50,000 hour(s) Internal Player CPU Intel Core i7

Sound

Built-in speakers 2 x 20W RMS

Accessories

Included Accessories Philips logo (x1)

RS232 Daisy chain cable (x1) Cleaning cloth (x1)
DVI - I Cable (1.8m) (x1) HDMI Cable (3m) (x1) HDMI transmitter (x2)

Multi-touch Interactivity

Storage GPU

RAM

Touch points 10 simultaneous touch points

256GB eMMc

Nvidia GT730

8GB DDR4

