

# PHILIPS

Powerful battery  
jump starter

Car Jump Starter

Comprehensive safety features

Long-lasting design

Overheating protection

Multi-function travel tool

LUMJS3210X1



## Bring car batteries back to life

Instantly jump start a drained car battery

The Philips Jump Starter JS3210 is an emergency lifeline for a dead battery. Its powerful lithium battery instantly starts 12V vehicles, up to 4.0L gas and 3.0L diesel engines\*1. Plus, it comes with a handy 3-mode torch and USB ports.

### Compact yet powerful jump start capability

- Easily start up to 4.0L gasoline and 3.0L diesel engines \*1
- Compact design makes it easy to move and store

### Comprehensive safety features

- Safe to use with 8 safety features protecting you
- Dual temperature sensors protect device from overheating

### Multi-function device

- 2 USB ports for charging devices and 3-mode LED torch

### Built-to-last automotive grade quality

- Impact resistant and anti-fire housing design
- Lasts on standby for up to 2.5 years from one charge\*4
- Manufactured to automotive-grade standards
- Corrosion resistant clamps ensure good contact with battery

# Car Jump Starter

Powerful battery jump starter

LUMJS3210X1/40

## Specifications

### Product description

Operating Temperature: -20° C to 55° C  
LED flashlight mode: SOS, Spotlight, Strobe  
Battery status indicator: LED  
Impact resistance: 1 meter  
Life circle: 1000 circles  
Jump cable length: 40cm

### Electrical characteristics

Power source: 3.7V/9900mAh  
Battery charging time: 4.5h hour(s)  
Battery capacity: 9900 mAh  
Battery type: Li-ion battery  
USB output: 5V/1A, 5V/2.4A  
USB input: Type-C 5V/2A

Jump start port: CP3500 12V  
Start current: 250A  
Peak current: 600A  
Self consumption: <20μA

### Ordering information

Order entry: LUMJS3210X1  
Ordering code: 72829230  
EAN1: 6974260728292  
EAN3: 6974260728308

### Packed product information

Length: 22 cm  
Width: 20.5 cm  
Height: 5 cm

Product dimensions (L x W x H): 18cm x 8.9cm x 3.3cm

Pack quantity / MOQ: 10  
Box weight (incl. product): 680g  
Product weight: 465g

### Outerpack information

Length: 45.5 cm  
Width: 27 cm  
Height: 23 cm

© 2025 Koninklijke Philips N.V.  
All Rights reserved.

Issue date 2025-05-14  
Version: 11.11.2

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 69 74260 72829 2

[www.philips.com](http://www.philips.com)



\* \*1 Monitor the start ability for the 12V vehicle engine up to gasoline 4.0L with full charged product. Tested by inhouse lab at 25°C/50RH, with removing vehicle battery connection. The age of the battery and the thickness of the oxide layer on the pole surface can affect the start-up performance

\* \*2 Monitor the jump start quantity for 2.4T 12V vehicle with fully charged product. Tested by inhouse lab at 25°C/50RH, with removing vehicle battery connection. The age of the battery and the thickness of the oxide layer on the pole surface can affect the start-up performance

\* \*3 Tested by inhouse lab with an environment temperature at 25°C/50RH Set the drop height to 1.0M, and the drop floor surface is cement floor; Drop the 4 corners and 6 sides of the product separately, and the number of falls is 1 time each.

\* \*4 Tested by inhouse lab at 25°C/50RH, monitoring the battery and PCB consumption, and theoretically calculates the maximum standby time of 2.7 years. Different temperatures and humidity can affect standby time. The age of the battery and the thickness of the oxide layer on the pole surface can affect the start-up performance