



Philips Brilliance
LCD widescreen monitor

51 cm (20")
WSXGA

200W6CS

your best choice for big, widescreen productivity

Get more done with true digital display: The big, wide screen 200W6 is your best choice for great, sharp front-of-screen performance, the widest viewing angle, productivity-enhancing remote asset management and lead-free design.

Maximum comfort for maximum productivity

- Designed for 'just-right' height and angle adjustment
- Display more images and content without scrolling
- SmartManage compatibility enables LAN-based asset management
- Built-in speakers for audio without desktop clutter
- Stand-alone audio for efficient net conferencing

Outstanding front of screen performance

- Fast 8ms On/off response time: Great text & graphics display
- WSXGA+, wide format 1680x1050 resolution for sharper display
- Dual input accepts both analog VGA and digital DVI signals
- Widest viewing angle up to 176 degrees

Great convenience

- USB port for convenient peripheral connections
- Embedded power supply eliminates external power adaptors
- Easy plug-and-play DVI for a true digital experience

PHILIPS

Highlights

WSXGA+, wide format 1680x1050

Wide format, super extended graphics array is a display specification that is capable of displaying 1680 x 1050 resolution or approximately 1.7 million pixels.

8ms response time (On/Off)

On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and, therefore, results in fewer visible image artifacts in the display of transition of text and graphics. On-Off response time is a more important measure in the display of business content like documents, graphs and photos.

Widest viewing angle

The widest viewing angle up to 176 degree provides the clearest display from any angle.

Dual input



VGA connector



DVI connector

Dual input provides connectors to accommodate input of both analog VGA and digital DVI signals.

SmartManage enabled

SmartManage is a system for monitoring, managing and checking status of display devices as well as delivering remote support to users who experience difficulties - all accomplished over a LAN.

Large viewing area

Viewing area is the visible portion of a monitor screen available for displaying data.

Built-in speakers

A pair of stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

Stand-Alone audio function

Built-in advanced firmware that delivers audio output even if there is no video input.

Ergonomics design

Ergonomic design makes Philips monitors 'people friendly' with tilt, swivel and height adjustment so each user can position the monitor for maximum viewing comfort and efficiency.

USB 2.0 port



USB port allows user to conveniently connect their plug and play multimedia devices such as USB memory devices, camera, portable HDD, Web camera, PDA, Printer and many other devices which has USB connection available. The conveniently located USB 2.0 port on the monitor allows USB 2.0 signals to pass thru to the computer. Note that many devices like cameras and HDD may need to be powered On independently, as they have higher power requirements than the monitor USB port can provide

In-box DVI cable

A DVI cable is shipped with the product to provide high quality digital display.

Embedded power supply

An embedded power supply is a power adaptor built into the body of a display device that replaces a bulky external power adaptor.



Specifications

Connectivity

- Audio output: Stereo Audio (3.5 mm jack) 1x
- Signal Input: VGA (Analog), DVI-D, PC Audio in
- USB: USB 2.0
- Sync Input: Composite Sync, Separate Sync, Sync on Green

Picture/Display

- Panel Size: 20.1"/ 51 cm
- Aspect ratio: 16:10
- LCD panel type: 1680 x 1050 pixels, Anti-glare polarizer, RGB vertical stripe
- Pixel pitch: 0.258 x 0.258 mm
- Optimum resolution: 1680 x 1050 @ 60Hz
- Brightness (nits): 300 nit
- Display colors: 16.7 M
- Contrast ratio (typical): 800:1
- Response time (typical): 8 (grey to grey) ms
- Viewing angle: @ C/R > 10
- Viewing angle (horizontal): 176 degree
- Viewing angle (vertical): 176 degree
- Horizontal Scanning Frequency: 30 - 93 kHz
- Vertical Scanning Frequency: 56 - 85 Hz
- Maximum Resolution: 1680 x 1050 @ 75Hz
- Effective viewing area: 433.4 x 270.9 mm
- Factory Preset Modes: 15 modes
- sRGB
- User definable modes: 39 modes
- Video Dot Rate: 165 MHz
- White Chromaticity, 6500K: x = 0.313 / y = 0.329
- White Chromaticity, 9300K: x = 0.283 / y = 0.297

Convenience

- Plug & Play Compatibility: DDC/CI, sRGB, Windows 98/ME/2000/XP
- Built-in Audio: 2W RMS x 2 stereo speakers
- User convenience: On-screen Display,

- SmartManage enabled
- Monitor Controls: Auto, Brightness Control, Left/Right, Menu (OK), Power On/Off, Up/Down, Volume control, Input, Size
- Regulatory approvals: CE Mark, FCC-B, UL, CSA, SEMKO, TCO '03, TÜV/GS, TÜV Ergo
- OSD Languages: English, French, German, Italian, Simplified Chinese, Spanish
- Other convenience: Kensington lock compatible
- Swivel: +/- 125°
- Tilt: -5° to 20°
- VESA Mount: 100 x 100 mm

Power

- Power supply: Built-in, 90-264 VAC, 50/60 Hz
- Consumption (On mode): 50 W (Typical)
- Power LED indicator: Operation - green, Stand by/sleep - Amber
- Complies with: NUTEK
- Consumption (Off Mode): 1.5 W or < 1.5 W

Dimensions

- Height adjustment range: 45 mm
- Weight: 7.6 kg
- Temperature range (operation): 5°C to 35°C
- Temperature range (storage): -20°C to 60°C
- Relative humidity: 20% - 80%
- MTBF: 50,000 hrs
- Depth (with base): 235 mm
- Height (with base): 423.5 mm
- Width (with base): 478 mm

Accessories

- Included accessories: AC Power Cord, DVI cable, PC audio cable, USB cable, VGA cable
- User Manual
- Optional accessories: Super Ergo Base

