

Philips Gaming Monitor Full HD Curved LCD display

Momentum 32 (31.5" / 80 cm diag.) 1920 x 1080 (Full HD)

322M8CP

# Get in the moment

This Philips curved momentum monitor combines a 240Hz refresh rate with AMD FreeSync Premium. Gaming features for lifelike visuals, tear-free, and low latency gameplay while delivering wide viewing angles. Best for the most intense games.

# **Built for fast action**

- AMD FreeSync™ Premium; tear free, stutter free, fluid gaming
- SmartImage game mode optimized for gamers
- · Low input lag reduces time delay between devices to monitor
- Ultra-fast 240 Hz refresh rate for virtually lag-free gaming
- 0.5 ms ultra-fast speed for crisp image and smooth gameplay

# **Superb Picture Quality**

- · VA display delivers awesome images with wide viewing angles
- Ultra Wide-Color wider range of colors for a vivid picture

## Design to enhance the senses

· Curved display design for more immersive experience

# Get comfortable

- · Less eye fatigue with Flicker-free technology
- · LowBlue Mode for easy on-the-eyes productivity



# Highlights

# **Curved display design**



Desktop monitors offer a personal user experience, which suits a curve design very well. The curved screen provides a pleasant yet subtle immersion effect, which focuses on you at the center of your desk.

# **AMD FreeSync™ Premium**



AMD FreeSyne

Gaming shouldn't be a choice between choppy gameplay or broken frames. AMD FreeSync™ Premium equips serious gamers with a fluid, tear-free gameplay experience at peak performance. There are no compromises, game confidently with a high refresh rate, low framerate compensation, and low latency.

# Ultra-fast 240 Hz refresh rate



While playing the most intense engaging action-oriented games, ultra-fast 240 Hz refresh rate enhances an ultra-smooth, lag-free gaming experience. This Philips display redraws the screen image up-to 240 times per second, effectively faster than a standard display. Especially for fast-paced games like FPS and

racing games, 240 Hz gives a superior motion and clarity visuals. With Philips 240 Hz display, action sequences in gameplay look judder-free and ghost-free. You will experience deeper immersion and feeling alive in game.

# Low Input Lag



Input lag is the amount of time that elapses between performing an action with connected devices and seeing the result on screen. Low input lag reduces the time delay between entering a command from your devices to monitor, greatly improve on playing twitchsensitive video games, particularly important to whom plays fast-paced, competitive games.

# SmartImage Game mode



The new Philips gaming display has quick access OSD fine tuned for gamers, offering you multiple options. "FPS" mode (First person shooting) improves dark themes in games, allowing you to see hidden objects in dark areas. "Racing" mode adapts display with fastest response time, high color, along with image adjustments. "RTS" mode (Real time strategy) has a special SmartFrame mode which enables highlighting of specific area and allows for size and image adjustments. Gamer 1 and Gamer 2 enable you to save personal customized settings based on different games, ensuring best performance.

## 0.5 ms MPRT fast response

322M8CP/89



Philips Momentum display with 0.5 ms MPRT effectively eliminates smearing and motion blur, delivers shaper and precise visuals to enhance gaming experience. Fast-moving action and dramatic transitions will be rendered smoothly. Best choice for playing thrilling and twitch-sensitive games.

# Ultra Wide-Color Technology



Ultra Wide-Color Technology delivers a wider spectrum of colors for a more brilliant picture. Ultra Wide-Color wider "color gamut" produces more natural-looking greens, vivid reds and deeper blues. Bring, media entertainment, images, and even productivity more alive and vivid colors from Ultra Wide-Color Technology.

# Flicker-free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-free Technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

























# Specifications

### **Picture/Display**

- Panel Size: 31.5 inch / 80 cm
- Aspect ratio: 16:9
- LCD panel type: VA LCD
- Backlight type: W-LED system
- Pixel pitch: 0.364 x 0.364 mm
- Brightness: 250 cd/m<sup>2</sup>
- Display colors: 16.7 M
- Color gamut (typical): NTSC 100%\*, sRGB 120%\*
- Contrast ratio (typical): 4000:1
- SmartContrast: Mega Infinity DCR
- Response time (typical): 4 ms (Gray to Gray)\*
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- Maximum resolution: 1920 x 1080 @ 240 Hz\* • Effective viewing area: 698.4 (H) x 392.9 (V) mm -
- at a 1500R curvature\* • Scanning Frequency: 30 - 255 kHz (H) / 48 - 240 Hz
- (V)
- sRGB
- Flicker-free
- Pixel Density: 70 PPI
- LowBlue Mode
- Display Screen Coating: Anti-Glare, 3H, Haze 25% • MPRT: 0.5 ms
- Low Input Lag
- AMD FreeSync™ technology: Premium
- Connectivity
- Signal Input: DisplayPort x 1, HDMI x 2
- Sync Input: Separate Sync
- Audio (In/Out): Audio out

### Convenience

- Plug & Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7
- User convenience: Power On/Off, Menu/OK, Brightness/UP, Input/Down, SmartImage game/ Back
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian
- · Other convenience: Kensington lock, VESA mount (100x100mm)

# Stand

• Tilt: -5/20 degree

### Power

- Power supply: Built-in, 100-240VAC, 50-60Hz
- Off mode: 0.3 W (typ.)
- On mode: 40.72 W (typ.)
- Standby mode: 0.5 W (typ.)
- · Power LED indicator: Operation White, Standby mode- White (blinking)

### **Dimensions**

- Packaging in mm (WxHxD): 790 x 619 x 297 mm
- Product without stand (mm): 709 x 425 x 88 mm
- Product with stand(max height): 709 x 526 x
- 245 mm

#### Weight

- Product with packaging (kg): 9.93 kg
- Product with stand (kg): 6.84 kg
- Product without stand (kg): 5.93 kg

#### **Operating conditions**

- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- Temperature range (operation): 0°C to 40 °C
- MTBF: 50,000 (Excluded backlight) hour(s)
- Relative humidity: 20%-80 %
- Temperature range (storage): -20°C to 60 °C

### **Sustainability**

- · Environmental and energy: RoHS
- Recyclable packaging material: 100 %
- · Specific Substances: Mercury free, PVC / BFR free housing

#### **Compliance and standards**

ICES-003

#### Cabinet

#### <sup>k</sup> Radius of the arc of the display curvature in mm

- \* The maximum resolution works for either HDMI input or DP input.
  \* For best output performance, please always ensure that your graphic card is capable of achieving the maximum resolution and refresh rate of this Philips display.
- \* Response time value equal to SmartResponse
   \* MPRT is to adjust brightness for blur reduction, so cannot adjust brightness while MPRT is turned on. To reduce motion blur, LED backlight will strobe synchronously with screen refresh, which may
- Cause noticeable brightness change.
   \* MPRT is gaming-optimized mode. Turn on MPRT may cause noticeable screen flickering. It is recommended to turn off when you
- are not using the gaming function. \* NTSC Area based on CIE1976 \* sRGB Area based on CIE1931
- \* 2020 Advanced Micro Devices, Inc. All rights reserved. AMD, the AMD Arrow logo, AMD FreeSync<sup>™</sup> and combinations thereof are trademarks of Advanced Micro Devices, Inc. Other product names used in this publication are for identification purposes only and may be trademarks of their respective companies





Issue date 2024-11-25

Version: 2.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 79637 2

© 2024 Koninklijke Philips N.V. All Rights reserved.

www.philips.com

• Regulatory Approvals: CB, CE Mark, FCC Class B,

- · Color: Black
- Finish: Textured

22M8CP/89