

PHILIPS

Peripheral Vascular

Intravascular
ultrasound

See clearly.
Treat optimally.




Diagnose and treat peripheral vascular disease

Assessing and delivering the right therapy at the right time for the right patient is imperative to improving outcomes. Clinicians need technology that's diverse and adaptable in order to deliver with optimal precision and efficacy.

Choose your catheter based on imaging diameter and wire compatibility needed.


IVUS allows assessment of the following:

- % Stenosis
- Calcium and thrombus
- Real time vessel diameter and lesion morphology
- Length of stenosis
- Dissection
- Position of wire in true or false lumen
- Location of side branches (without using contrast)
- Venous compression
- Completeness of treatment




A full line of IVUS catheters to help guide your treatment strategies

Our peripheral imaging catheters help assess the location of the disease and lesion morphology, including calcium and thrombus. IVUS can also be used to appropriately size stents and confirm completeness of treatment.




Visions PV .035 OTW

- Includes centimeter markers
- 0.038" maximum guide wire compatible
- 60 mm max imaging diameter
- 90 cm working length




Reconnaissance PV .018 OTW

- 0.014" and 0.018" guide wire compatible
- 20 mm max imaging diameter
- 150 cm working length




Visions PV .018 RX

- 0.014" and 0.018" guide wire compatible
- 24 mm max imaging diameter
- 135 cm working length



Visions PV .014P RX

- 0.014" guide wire compatible
- 20 mm max imaging diameter
- 150 cm working length




Pioneer Plus re-entry

- 0.014" guide wire compatible
- 20 mm max imaging diameter
- 120 cm working length

Ordering information and technical specifications


Visions PV .035 OTW

Minimum sheath 8.5 F
88901




Reconnaissance PV .018 OTW

Minimum sheath 5 F
0180TW




Visions PV .018 RX

Minimum sheath 6 F
86700



Visions PV .014P RX

Minimum sheath 5 F
014R



Pioneer Plus re-entry

Minimum sheath 6 F
PPLUS120

