	SANDV	VICHES		Contraction of the local division of the loc
	Beef Cheese	5.10 4.40		
	Chicken	4.30		
	Tuna	4.60		AN/
- 11	Avocado	4.90		
	Turkey	4.95		124
Philips Signage S P-Line Display		5.20	PHILUSS	

55" Powered by Android 450cd/m²



55BDL5055P

Chasing innovation

powered by Android

Amaze your guests with a smarter, faster, signage display. With integrated WiFi and designed for running Android apps, it's the next evolution in signage solutions.

Innovative solutions for any signage application

- Save and play content with internal memory
- Android: Run your own app or choose your favorite app to run
- Integrated WiFi
- Enhance your connectivity with an integrated mPCIe slot.

Maximizing the impact of your message

- CMND: Take control of your displays
- Connect and control your content via the cloud
- Manage settings of multiple displays with CMND & Control
- Create and update content with CMND & Create

Care about you, your business and your audience

- SmartPower for energy saving
- Keep your content up and running with FailOver
- Ensure your content is running with automatic screenshots



Highlights

Powered by Android

With Android OS integrated into the display, you can work with the most developed OS on the planet and save your own app directly into the display. Or, choose from the large library of Android apps and play content from there. With the built-in scheduler, you can daypart your apps and content based on your customer and time of day and with the auto orientation feature, showing content in portrait or landscape is as simple as turning the display.

PCI Slot

With an integrated PCI slot, you can connect a WiFI/bluetooth or 4G LTE module, allowing for even greater communication with the display. Machine to machine communication is also enhanced, with numerous configurations available for customers to use, such as the ability to expand product features or signalhandling capability.

Internal Memory



Save and play content with internal memory. Upload your media into the display and playback content immediately. Working in conjunction with the internal browser, it also serves as a memory cache when streaming online content. If the network ever fails, the internal memory keeps content running by playing a cached version of the content, ensuring that your media stays up even if the network goes down.

Proof of Play

Content is king, and with the automatic screenshot feauture, you can make sure that your content is up and running at all times. Screenshots are taken throughout the day, which are then stored in the FTP server. From there, the screenshots can be viewed no matter when, or where you are.

FailOver



Keeping your content up and running is critical for demanding commercial applications. While it is unlikely you will face a content disaster, FailOver provides content protection with a revolutionary technology that plays back-up content on screen in the event of a media player failure. FailOver automatically kicks in when the primary input fails. Simply select a primary input connection and a FailOver connection and your ready for instant protection.

SmartPower



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

CMND



A robust display management platform, CMND puts the power back into your hands. Update and manage content with CMND & Create or control your settings with CMND & Control. It's all possible with CMND.

CMND & Control



With CMND & Control, easily manage multiple displays in a central location. With real time display monitoring, setting and software updates from a remote location, and the ability to customize and configure multiple displays at once, such as video wall or menu board displays, controlling your suite of displays has never been easier.

CMND & Create



Design and create compelling content with CMND & Create, a powerful authoring tool. With a drag and drop interface, preloaded templates, and integrated widgets, you'll be able to amaze your customers with compelling content. Available in portrait and landscape mode.

SmartBrowser



Connect and control your content via the cloud with the integrated HTML5 browser. Using the Chromium based browser, design your content online and connect a single display, or your complete network. Show content in both landscape and portrait mode, with fullHD resolution. Streaming content can also be shown in a PIP (picture-in-picture) window. Simply connect the display to the internet using WiFi or with an RJ45 cable, and enjoy your own created playlists



✓ SmartPower





📃 Smart**Browser**

Specifications

Connectivity

- Audio output: 3.5mm jack
- Video input: Display Port1.2 (x1), DVI-I (x 1), HDMI 1.4 (x2), USB 2.0 (x2), USB 2.0 (x1)
- Audio input: 3.5 mm jack
 Other connections: Micro SD (x1), Micro USB(type B)x1, OPS
- Video output: DisplayPort (x1), DVI-I (x1) • External control: R|45, RS232C (in/out) 2.5 mm
- jack, IR (in/out) 3.5 mm jack Optional WiFi functionality: requires WiFi module and external antennas

Picture/Display

- Diagonal screen size (metric): 138.8 cm
- Diagonal screen size (inch): 54.64 inch
- Aspect ratio: 16:9
- Panel resolution: 1920x1080p
- Pixel pitch: 0.63 x 0.63 mm
- Optimum resolution: 1920 x 1080 @ 60Hz
- Brightness: 1.07 billion cd/m²
- Display colors: 1.0737 billion
- Contrast ratio (typical): 1300:1
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Viewing angle (horizontal): 178 degree
- Viewing angle (vertical): 178 degree
- Operating system: Android 5.1.1

Convenience

- Placement: Landscape, Portrait
- Tiled Matrix: Up to 15 x 15
- · Screen saving functions: Pixel Shift, Low Bright
- · Keyboard control: Hidden, Lockable
- Signal loop through: DVI, VGA, RS232, IR
- Loopthrough, DisplayPort · Ease of installation: AC Out, Carrying Handles, Smart Insert
- · Energy saving functions: Smart Power
- Other convenience: G sensor
- Network controllable: RJ45, RS232, HDMI (One Wire)


Sound

• Built-in speakers: 2 x 10W RMS

Power

DHIID

- Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz
- Consumption (Typical): 110 W



- Standby power consumption: <0.5 W
- Consumption (EPA 7.0): 90.93 W

Supported Display Resolution

- Computer formats: 1920 x 1080, 60Hz, 1360 x 768, 60Hz, 1280 x 800, 60Hz, 1280 x 768, 60Hz, 1024 × 768, 60, 75Hz, 1280 × 1024, 60Hz, 1600 × 1200, 60Hz, 640 x 480, 60, 72, 75Hz, 720 x 400, 70Hz, 800 x 600, 60, 75Hz
- Video formats: 1080p, 50, 60Hz, 720p, 50, 60Hz, 576p, 50Hz, 480p, 60Hz, 1080i, 25, 30Hz, 480l, 30Hz, 576i, 25Hz

Dimensions

- Set Width: 1228.6 mm
- Product weight: 25.2 kg
- Set Height: 699.4 mm
- Set Depth: 56.8 mm
- Set Width (inch): 48.4 inch
- Set Height (inch): 27.6 inch
- Wall Mount: 400 x 400 mm, M6
- Set Depth (inch): 2.3 inch
- · Bezel width: 6.5 mm
- Product weight (lb): 55.6 lb

Operating conditions

- Altitude: 0 ~ 3000 m Temperature range (operation): 0 ~ 40 °C
- MTBF: 60,000 hour(s)
- Relative humidity: 20 ~ 80 %
- Temperature range (storage): -20 ~ 60 °C

Multimedia Applications


- USB Playback Video: MKV, MP4, MPG, TS, VOB, 3GP, AVI, DAT, FLV, MOV, WEBM
- USB Playback Picture: BMP, GIF, JPEG, JPG, PNG
- USB Playback Audio: AAC, M4A, MP3, WMA, MP1, MP2

Internal Player

- CPU: Octacore Cortex A53 1.5GHz
- GPU: PowerVR SGX6110
- Memory: 2GB DDR3
- Storage: 16GB EMMC

Accessories

• Included accessories: Remote Control, Batteries for remote control, Quick start guide, AC Power Cord, RS232 cable





© 2024 Koninklijke Philips N.V. All Rights reserved.

Version: 5.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 74226 3 www.philips.com 55BDL5055P/75

- Included Accessories: Edge Alignment Kit (1)-2pcs, Edge Alignment Kit (2)-1pcs, Philips logo (x1), Power cable (3m), RS232 Cable (3m), RS232 Daisy chain cable (x1), Thumbscrew (8pcs), RS232 daisy-chain cable
- Stand: BM04642/00(Optional)

Miscellaneous

- · On-Screen Display Languages: English, French, German, Spanish, Polish, Turkish, Russian, Italian, Simplified Chinese, Traditional Chinese, Arabic, Japanese, Danish, Dutch, Finnish, Norwegian,
- Portuguese, Swedish • Warranty: 3 year warranty
- Regulatory approvals: EnergyStar 7.0, CE, FCC, Class B, CCC, RoHS, BSMI, CB, J-Moss, PSE, VCCI, CECP, EAC, PSB, UL