

**Quad HD monitor** 

# **Monitor**

1000 series

27" (68.6 cm)

2560 x 1440 (Quad HD)

27E2N1500





# **Built for precision**

This monitor is packed with features that allow you to work with absolute precision. Its Quad HD resolution, along with an overclockable 120Hz refresh rate and 1ms MPRT, this monitor showcases detailed imagery with the utmost definition.

## **Good for Gaming**

• 120Hz refresh rates for ultra-smooth, brilliant images

# **Features designed for you**

- EasyRead mode for a paper-like reading experience
- LowBlue mode and Flicker-free easy-on-the eyes viewing

# **Easy to experience**

- VESA mount for convenience
- HDMI ensures universal digital connectivity

# **Superb Picture Quality**

- SmartContrast for deep black level details
- IPS LED wide view technology for image and color accuracy
- Crystalclear images with Quad HD 2560 x 1440 pixels
- Effortlessly smooth action with Adaptive-Sync technology
- 1ms (MPRT) fast response for crisp image and smooth gameplay

Quad HD monitor 27E2N1500/69

# Highlights

#### Overclockable 120Hz refresh rate




With an overclockable 120 Hz refresh rate, less skipped frames are ensured. You can easily target the enemy in ultra-clear, smooth motion.

## **Crystalclear images**



These Philips screens deliver Crystalclear, Quad HD 2560x1440 or 2560x1080 pixel images. Utilizing high performance panels with high density pixel count, enabled by high bandwidth sources, these new displays will make your images and graphics come alive. Whether you are demanding professional requiring extremely detailed information for CAD-CAM solutions, using 3D graphic applications or a financial wizard working on huge spreadsheets, Philips displays will give you Crystalclear images.

# **IPS technology**



IPS displays use an advanced technology which gives you extra wide viewing angles of 178/178 degree, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colors, making it ideal not only for Photos, movies and web browsing, but also for professional applications which demand color accuracy and consistent brightness at all times.

# **Adaptive-Sync technology**



Gaming shouldn't be a choice between choppy gameplay or broken frames. Get fluid, artifact-free performance at virtually any framerate with Adaptive-Sync technology, smooth quick refresh and ultra-fast response time.

## **SmartContrast**



SmartContrast is a Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

#### **1ms MPRT fast response**



MPRT (motion picture response time) is more intuitive way to describe the response time, which directly refers the duration from seeing blurry noise to clean and crisp images. Philips gaming monitor with 1 ms MPRT effectively eliminates smearing and motion blur, delivers shaper and precise visuals to enhance gaming experience. Best choice for playing thrilling and twitch-sensitive games.

## **LowBlue Mode & Flicker-free**



Our LowBlue Mode and Flicker-free technology have been developed to reduce eye strain and fatigue often caused by long hours in front of a monitor.

















Quad HD monitor 27E2N1500/69

# Highlights

# **EasyRead mode**



EasyRead mode for a paper-like reading experience

# **HDMI Ready**



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables high-quality digital video and audio all

transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

# **VESA** mount for convenience



VESA mount for convenience













**Ouad HD monitor** 27E2N1500/69

# **Specifications**

#### **Picture/Display**

Panel Size: 27"/68.6cm Aspect ratio: 16:9

LCD panel type: IPS technology Backlight type: W-LED system Pixel pitch: 0.2331 x 0.2331 mm

Brightness: 250 cd/m<sup>2</sup> Display colors: 16.7 M (8 bits) Contrast ratio (typical): 1000:1 SmartContrast: Mega Infinity DCR

Response time (typical): 4 ms (Gray to Gray)\* Viewing angle:  $178^{\circ}$  (H) /  $178^{\circ}$  (V), @ C/R > 10

Picture enhancement: SmartImage

Maximum resolution: 2560 x 1440 @ 120 Hz

(Overclock)\*

Effective viewing area: 596.736 (H) x 335.664 (V) Scanning Frequency: 30 KHz - 190 KHz (H) / 48

Hz - 120 Hz (V) sRGB Flicker-free

Pixel Density: 108.79 PPI

LowBlue Mode

Display Screen Coating: Anti-Glare, 3H, Haze

25% MPRT: 1 ms EasyRead Adaptive sync HDR: HDR 10

#### **Connectivity**

Signal Input: DP1.2 x 1, HDMI 2.0 x 1

Sync Input: Separate Sync

HDCP: HDCP 1.4 (HDMI / DisplayPort), HDCP 2.2

(HDMI / DisplayPort)

#### **Convenience**

Plug & Play Compatibility: DDC/CI, Mac OS,

sRGB. Windows 11 / 10

User convenience: Power On/Off, Menu, Input,

SmartImage, Brightness

OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian Other convenience: Kensington lock, VESA

mount (100x100mm)

#### **Stand**

Tilt: -5/20 degree

Power supply: External, 100-240VAC, 50-60Hz

Off mode: 0.3 W (typ.) On mode: 25.6 W (typ.) Standby mode: 0.5 W (typ.)

Power LED indicator: Operation - White, Standby

mode-White (blinking)

#### **Dimensions**

Packaging in mm (WxHxD): 690 x 480 x124 mm Product without stand (mm): 614 x 363 x 35 mm Product with stand(max height): 614 x 457 x 200 mm

#### Weight

Product with packaging (kg): 5.6 kg Product with stand (kg): 3.18 kg Product without stand (kg): 2.81 kg

#### **Operating conditions**

Altitude: Operation: +12,000ft (3,658m), Non-

operation: +40,000ft (12,192m)

Temperature range (operation): 0 to 40 °C MTBF: 50,000 hrs (excluding backlight) hour(s)

Relative humidity: 20%-80 %

Temperature range (storage): -20 to 60 °C

# **Sustainability**

Environmental and energy: RoHS Recyclable packaging material: 100 %

Specific Substances: Mercury free, PVC / BFR free

# **Compliance and standards**

Regulatory Approvals: CB, CE Mark, CEL, CCC, CECP, UKCA, EMF, FCC, ICES-003, ETL, CEC

## **Cabinet**

Color: Black Finish: Textured

© 2025 Koninklijke Philips N.V. All Rights reserved

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

Issue date 2025-03-17 Version: 7.7.1

EAN: 87 21038 00326 0



- \* For best output performance, please always ensure that your graphic card is capable of achieving the maximum resolution and refresh rate of this Philips display.
- \* Response time value equal to SmartResponse.
- \* This maximum resolution works for HDMI input only.
- \* The Overclock function increases the native refresh rate, however, it does have some associated risks along with it. If the screen is displayed abnormally after rebooting, please switch off the Overclock setting located in the monitor's OSD menu
- \* MPRT is to adjust brightness for blur reduction, so cannot adjust brightness while MPRT is turned on. To reduce motion blur, LED backlight will strobe synchronously with screen refresh, which may cause noticeable brightness
- \* MPRT is gaming-optimized mode. Turn on MPRT may cause noticeable screen flickering. It is recommended to turn off when you are not using the gaming function.
- \* The monitor may look different from feature images.
- \* The products and accessories listed on this leaflet may differ by country and region.