

Philips Unite LED 5000 Panels

Signage Solutions LED Display

27"

Flip chip COB

Low power consumption



27HDL5112IP

Philips Unite LED 5000 Series Panels

Quality. Style. Accessibility. Without compromise.

The Philips LED Unite 5000 Series is your essential range of investment-friendly flip chip COB panels that deliver on high quality, resolution, reliability and efficiency. So reliability, efficiency.

Supports HDR10+ video standard

• Crystal clear content with vivid colours and brightness.

Flip chip COB dvLED panels

• Greater stability and reliability, plus higher definition.

Prewired cabinets for faster installation

• Prewired for power, with loop through for data included.

Low power consumption

• Supporting sustainability and energy savings.

Three year warranty as standard

• Activated out of the box for hassle free peace of mind.

27HDL5112IP/00

Specifications

Picture/Display

Brightness (nits): 600 nit Brightness Uniformity: >=97% Calibration(brightness/color): Color and Briahtness

Color temperature adjust range: 3000-10000 Color temperature default: 6500K±500

Contrast ratio (typical): 5000:1 Viewing angle (horizontal): 160 degree Viewing angle (vertical): 160 degree

Bit-depth(bit): 13

Viewing angle (°) H/V: 160°

Frame frequency (Hz): 50-60 Refresh rate(Hz): 1920-3840 Hz Colour temperature (K) adjust range (by software): 3000-10000

Power

Input voltage: AC100~240V (50 & 60Hz) Black screen power cons. (W): <16.7 Max cabinets power daisy chain: 16

BTU/M2 (BC): 1267 BTU/M2 (AC): 1036

Cabinet Max Power consumption (W) (BC): <75 Cabinet Max Power consumption (W) (AC):: <59 Cabinet Typical Power consumption (W) (AC):

Power consumption/M2 (W)(BC): 371,5 Power consumption/M2 (W)(AC): 303,75

Operating conditions

Temperature range (operation): -10 - 45 °C Temperature range (storage): -40 - 60 °C Humidity range (operation)[RH]: 10%-90%RH Humidity range (storage) [RH]: 10%-70%RH Working environment (indoor/outdoor): Indoor

Cabinet

Cabinet area (m2): 0.2052 Cabinet pixels (Dot): 129,600

Cabinet resolution (W x H): 480x270 mm

Data connector: RJ45

Power connector: 3 pin connector Receiving card quantity: 1pcs Receving card brand: Novastar A8S-N Weight (KG): 4.7±0.2

Cabinet diagonal (inch): 27.1" Cabinet construction: Die cast

Cabinet Size (WxHxD in mm): 600x337.5x33.6

Module

LED type: COB

Pixel constitution: 1R1G1B Flip Chip Module resolution (WxH pixels): 120x135

Pixel pitch (mm): 1.25

Module size (WxH in mm): 150x168.75 LED Pole type: Common cathode

Weight(KG): 0.14

Black screen power saving LED part number: HCP 1.25

LED Lifetime (Hrs, half brightness): 100,000

Accessories

LAN cable (type/length): RJ45 75cm/RJ45 15cm Screws (type / length mm): Hex M6, 22mm QSG (Quick Start Guide): Printed on carton

Miscellaneous

Warranty: 36 months

Regulatory approvals: CCC, CE, ETL, FCC, SASO,

UKCA, RoHS

Packaging Data

Dimension of packaging (mm): 822x461x99

Gross weight (KG): 5.8±0.2

Highlights

Flip chip COB dvLED panels

Delivering on greater stability, reliability and visual performance, as well as enabling smaller pixel pitches for darker blacks, higher brightness, higher contrast and higher definition.

Cool low power consumption

Common cathode technology boosts the energy efficiency of the P0.78, P0.93, P1.25, P1.5 and P1.875 Philips LED Unite 5000 Series panels, optimising power consumption without compromising on performance. This cool LED technology enables precise control over each cathode, minimising heat output, to ensure the display is more energy conscious and, ultimately, more environmentally friendly.

Stylish exterior and finishing

The Philips LED Unite 5000 Series comes with a rolling ripple exterior cabinet design and prewired for power for the tidiest cable management. Optional edge finishing is available in brushed anodised aluminium, with easy click functionality for fast installation.

12-bit colours and HDR10+

Supporting 12-bit colours and HDR10+ resolution, Philips LED Unite 5000 Series panels deliver crystal clear content with near perfect colour and brightness accuracy, delivering the deepest visual experiences.

© 2025 Koninklijke Philips N.V. All Rights reserved

Issue date 2025-09-15 Version: 9.9.1

EAN: 87 21038 10037 2



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com