



Philips Ultinon Drive  
5011R  
7 inch Round Driving Light

**Sturdy one-piece body**

IP69K waterproof  
Corrosion-free stainless steel  
Trouble-free operation

**LUMUD5011RX1**

## Brilliant LED lighting for off-road adventures

### Bright, long beam for superior visibility

For drivers who demand the maximum of themselves and their machines, we offer Philips Ultinon Drive 5000 series LED driving lights. Exceptionally rugged, with unsurpassed illumination and beam focus, advanced.

**Easy installation**

- Trouble-free operation

**Off-road auxiliary lights**

- Offering a mid-day color temperature up to 6500K

**Powerful brightness, Rugged performance**

- Bright, long beam for superior visibility

**Durable equipment for challenging conditions**

- Corrosion-free, stainless-steel mounting brackets
- IP69K waterproof to master the elements

# PHILIPS

## 7 inch Round Driving Light

Sturdy one-piece body IP69K waterproof, Corrosion-free stainless steel, Trouble-free operation

# Specifications

### Product description

- Break resistance
- Corrosion-free brackets: Yes, included
- ECE R10: No
- ECE R149: No
- ECE reference number: No
- Heat sink: N/A
- Impact protection rating (IK): IK07
- Ingress protection rating (IP): IP68 & IP69K
- Installation angle: 360°
- Material: Aluminum die-cast
- Number of LED's: 21x 5W
- Offroad boost: No
- One-piece body design
- Operating temperature: -40° F to 176° F
- Plug type: Connector with 0.5m cable
- Scratch resistant lens
- Storage Temperature: -40° F to 176° F
- Technology: LED
- Accessories (optional): Additional brackets

### Light characteristics

- Color temperature: 6500 K
- Beam length 1 lux: 1280 ft.
- Beam length 1 lux (boost): N/A
- Beam length 3 lux: 574 ft.
- Beam length 3 lux (boost): N/A
- Beam width 1 lux: 131 ft.

- Beam width 3 lux: 82 ft.
- Light output (effective lumen): 4200
- Light output in Boost mode: N/A

### Electrical characteristics

- Voltage: 9-30 Volt DC

### Ordering information

- Order entry: UD5011RX1
- GOC: 78004099

### Packaging Data

- EAN1: 046678004094
- EAN3: 50046678004099

### Packed product information

- Width: 3.08 in.
- Height: 7.09 in.
- Gross weight box: 3.96 lb.
- Net weight product: 3.40 lb.
- MOQ (for professionals): 2
- Length: 7.87 in.

### Outerpack information

- Length [in]: 8.66 in.
- Width [in]: 7.87 in.
- Height [in]: 8.66 in.

LUMUD5011RX1/50

# Highlights

### Superior visibility

Up to 1279 feet of down road and up to 131 feet in width make this a powerful addition to your high beam headlights.

### Unsurpassed illumination

High Power LEDs offer 4200 effective lumens with up to 6500K bright white light.

### Corrosion-free brackets

Thick Aluminum faceplate, stainless steel brackets help achieve an IK07 shock protection rating.

### Waterproof for durable light

Tested for close range high pressure, high temperature water rated IP68 and IP69K.

### Trouble-free

Trouble-free operation



Issue date 2024-11-12

Version: 1.0.1

© 2024 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)