



Q-Line Display

Signage Solutions

55"

Direct LED Backlight

Ultra HD



55BDL3650Q

Stand out from the crowd

Your versatile and easy-to-set-up 18/7 display

Inform and enthral with a Philips Q-Line 4K Ultra HD digital display. This reliable, easy-to-install, Android powered signage solution is Wave-ready for remote management, putting you in full control, any time, anywhere.

Cost-effective system solution

- Easy control. Remotely manage networked displays
- Easily schedule content from USB or internal memory

Effortless setup. Total control.

- Optional Interact for wireless screen share
- Catch the Wave for revolutionary results

Smart and powerful

- Connect and control your content via the cloud
- Android SoC processor. Native and web apps
- WiFi connection made easy with optional CRD22 module

Versatile system solution

- Ultra-HD. Rich images. Stunning contrast
- FailOver. Ensure your display never goes blank

Q-Line Display 55BDL3650Q/75

Highlights

SmartBrowser

Connect and control your content via the cloud with the integrated HTML5 browser. Using the Chromium based browser, design your content online and connect a single display, or your complete network. Show content in both landscape and portrait mode, with fullHD resolution. Simply connect the display to the internet using WiFi or with an RJ45 cable, and enjoy your own created playlists.

FailOver

Critical for demanding commercial applications, FailOver is a revolutionary technology that automatically plays back-up content on screen in the unlikely event of an input source or application failure. Simply select a primary input connection and a FailOver connection and you are ready for instant content protection.

Integrated media player

Easily schedule content to play from USB or from internal memory. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback is done.

Interact (optional)

Wirelessly screen share using your existing Wi-Fi network to instantly and securely connect devices, or use our optional HDMI Interact dongle to cast directly onto the screen without connecting into the secured network.

Powered by Android 10

Powered by our Android 10 SoC platform, these hard-working Philips professional displays are optimised for native Android apps, and you can install web apps directly onto the display too. Flexible and secure, ensuring display specs stay up to the moment for longer.

PPDS Wave

Unlock the power, versatility and intelligence inside your Philips Q-Line displays remotely with Wave. This evolutionary cloud platform puts you fully in control, with simplified installation and setup, monitoring and controlling displays, upgrading firmware, managing playlists and setting power schedules. Saving you time, energy and environmental impact.











Q-Line Display 55BDL3650Q/75

Specifications

Picture/Display

Diagonal screen size (metric): 138.7 cm Diagonal screen size (inch): 54.6 inch

Aspect ratio: 16:9

Panel resolution: 3840 x 2160 Pixel pitch: 0.315 x 0.315 mm

Optimum resolution: 3840 x 2160 @ 60 Hz

Brightness: 400 cd/m² Display colors: 1.07 Billion Contrast ratio (typical): 1300:1 Dynamic contrast ratio: 500,000:1 Response time (typical): 9 ms

Viewing angle (horizontal): 178 degree Viewing angle (vertical): 178 degree

Picture enhancement: 3/2 - 2/2 motion pull down, Dynamic contrast enhancement, Progressive scan

Panel technology: ADS Operating system: Android 10

Haze: 2%

Connectivity

Audio output: 3.5mm jack

Video input: HDMI 2.0 (x2), USB 2.0 (x2), DVI-I (x 1),

USB 3.0 (x1)

Audio input: 3.5 mm jack Other connections: micro SD

External control: RJ45, RS232C (in/out) 2.5 mm

jack, IR (in/out) 3.5 mm jack

Convenience

Placement: Landscape (18/7), Portrait (18/7)

Tiled Matrix: Up to 3 x 3

Keyboard control: Lockable, Hidden Remote control signal: Lockable

Signal loop through: RS232, IR Loopthrough **Energy saving functions: Smart Power** Network controllable: RS232, RJ45

Sound

Built-in speakers: 2 x 10W RMS

Power

Mains power: 100 ~ 240 VAC Consumption (Typical): 130 W Consumption (Max): 200 W

Standby power consumption: <0.5 W **Power Saving Features: Smart Power**

Energy Label Class: G

Supported Display Resolution

Computer formats: 1920 x 1080, 60Hz, 1600 x 1200, 60Hz, 1440 x 900, 60Hz, 1280 x 1024, 60Hz, 1280 x 720, 60Hz, 1280 x 800, 60Hz, 1024 x 768, 60, 70, 75Hz, 1680 x 1050, 60Hz, 3840 x 2160, 60Hz

Miscellaneous

Arabic, Japanese

RoHS, UL

Warranty: 3 year warranty

On-Screen Display Languages: English, French,

Simplified Chinese, Spanish, Traditional Chinese,

Regulatory approvals: CE, CB, FCC, Class A, VCCI,

German, Italian, Polish, Turkish, Russian,

Video formats: 1080p, 50, 60Hz, 1080i, 50, 60Hz,

720p, 50,60 Hz, 2160p, 50, 60Hz

Dimensions

Set Width: 1241.8 mm Product weight: 16.6 kg Set Height: 712.6 mm Set Depth: 63.6 mm Set Width (inch): 48.89 inch Set Height (inch): 28.06 inch Wall Mount: 400 mm x 400 mm, M6 Set Depth (inch): 2.50 inch

Bezel width: 13.9 mm (Even bezel) Product weight (lb): 36.60 lb

Operating conditions

Altitude: 0 ~ 3000 m

Temperature range (operation): 0 ~ 40 °C

MTBF: 50,000 hour(s)

Temperature range (storage): -20 ~ 60 °C Humidity range (operation)[RH]: 20 ~ 80% RH

(No condensation)

Humidity range (storage) [RH]: 5 ~ 95% RH (No

condensation)

Multimedia Applications

USB Playback Video: MPEG, H.264, H.263, H.265,

AVI, MP4, VP8

USB Playback Picture: JPEG, BMP, PNG USB Playback Audio: AAC, HEAAC, MPEG

Internal Player

CPU: Quad Core Cortex A55

GPU: G52 MC1

Memory: 16GB, 3GB DDR

Accessories

Included Accessories: IR sensor cable (1.8 m) (x1), RS232 daisy-chain cable, Philips logo (x1), AC Power Cord, AC Switch Cover, Quick start guide, Remote control & AAA batteries, RS232 cable, USB

cover and screws, Wire Clamper (x3)

© 2024 Koninkliike Philips N.V. All Rights reserved.

Issue date 2024-12-09 Version: 2.2.1

FAN: 87 12581 80484 8

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.



www.philips.com