# **PHILIPS**



**D-Line Display** 

**Signage Solutions** 

32"

Powered by Android

400cd/m<sup>2</sup>



32BDL4650D

# Smart and modular for an even longer lifetime

powered by Android

Philips D-Line is designed to engage your audience and delight customers. Powered by Android 11 for easy software integrations, this versatile display is suitable for impact in any setting.

### **Expand your viewing experience**

• ADS wide-view panel display

## Innovative solutions for any signage application

- Save and play content with internal memory
- Android SoC processor. Native and web apps

# Care about you, your business and your audience

- 4G/LTE optional module for reliable connection
- Modularity longer product lifetime
- FailOver. Ensure your display never goes blank

## **Maximizing the impact of your message**

- Catch the Wave for revolutionary results
- Connect and control your content via the cloud

D-Line Display 32BDL4650D/75

# Highlights

### **Internal Memory**



Save and play content with internal memory. Upload your media into the display and playback content immediately. Working in conjunction with the internal browser, it also serves as a memory cache when streaming online content. If the network ever fails, the internal memory keeps content running by playing a cached version of the content, ensuring that your media stays up even if the network goes down.

### **ADS wide-view panel display**

Be seen from any angle with ADS wide-view technology. Advanced Super Dimension Switch delivers faster on-display picture processing for smoother content transitions, remarkable image accuracy, and superior colour reproduction with 180 degree viewing.

### **FailOver**

Critical for demanding commercial applications, FailOver is a revolutionary technology that automatically plays back-up content on screen in the unlikely event of a media player failure. Simply select a primary input connection and a FailOver connection and you are ready for instant content protection.

### **Modularity**

Extend your display into the future with our modular approach. Bringing opportunities for longer product lifetime with easily detached and replaced components, and a firm focus on sustainability, with reduced WEEE disposal.

### **Powered by Android 11**

Powered by Android 11, your Philips D-Line delivers the ultimate, most secure and connected display experience. Optimised for native Android

apps, and enabling you to install web apps and software directly onto the display, eliminating the need for an external media player.

#### **SmartBrowser**

Connect and control your content via the cloud with our integrated HTML5, Chromium-based browser. Design your content online and connect a single display, or your entire network, either landscape or portrait. Simply connect to the internet via an RJ45 cable.

#### **PPDS Wave**

Unlock the power, versatility and intelligence inside your Philips D-Line displays remotely with Wave. This evolutionary cloud platform puts you fully in control, with simplified installation and set-up, monitoring and controlling displays, upgrading firmware, managing playlists and setting power schedules. Saving you time, energy and environmental impact.



D-Line Display 32BDL4650D/75

# Specifications

### **Picture/Display**

Diagonal screen size (metric): 81.28 cm Diagonal screen size (inch): 32 inch

Aspect ratio: 16:9

Panel resolution: 1920x1080p

Pixel pitch: 0.36375 (H) x 0.36375 (V) mm Optimum resolution: 1920 x 1080 @ 60Hz

Brightness: 400 cd/m²
Display colors: 16.7 Million
Contrast ratio (typical): 1200:1
Dynamic contrast ratio: 500,000:1
Response time (typical): 8 ms
Viewing angle (horizontal): 178 degree
Viewing angle (vertical): 178 degree
Picture enhancement: 3/2 - 2/2 motion pull
down, Motion compens. deinterlacing, Dynamic contrast enhancement, Progressive scan

Panel technology: ADS
Operating system: Android 11

Haze: 25%

### Connectivity

Audio output: 3.5mm jack

Video input: DVI-I (x 1), DisplayPort 1.4 (x1), HDMI 2.0 (x2), USB 3.0 (x2), VGA (via DVI)

Audio input: 3.5 mm jack

Other connections: 4G/LTE antenna connectors,

Micro USB (x1) (OTG), USB 2.0 (x1) Video output: DisplayPort 1.4 (x1)

External control: RJ45, RS232C (in/out) 2.5 mm

jack, IR (in/out) 3.5 mm jack

### Convenience

Placement: Landscape (24/7), Portrait (24/7)

Tiled Matrix: Up to 10 x 15 Screen saving functions: Pixel Shift Keyboard control: Hidden, Lockable

Signal loop through: RS232, IR Loopthrough,

DisplayPort

**Energy saving functions: Smart Power** 

Network controllable: RS232, External 4G mPCle

slot, RJ45

### Sound

Built-in speakers: 2 x 10W RMS

### **Power**

Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz Consumption (Typical): TBD W Consumption (Max): TBD

Standby power consumption: <0.5 W

Energy Label Class: G

### **Supported Display Resolution**

Computer formats: 1920 x 1080, 60Hz, 1024 x 768, 60Hz, 1280 x 1024, 60Hz, 1280 x 720, 60Hz, 1440 x 900, 60 Hz, 1600 x 900, 60Hz, 1680 x 1050, 60Hz, 640 x 480, 60Hz, 800 x 600, 60Hz Video formats: 1080i, 50, 60Hz, 576i, 50Hz, 576p, 50Hz, 480p, 60Hz, 480i, 60Hz, 1080p, 50, 60Hz, 720p, 50,60 Hz

### **Dimensions**

Set Width: 726.5 mm Product weight: 5.7 kg Set Height: 425.4 mm

Set Depth: 65.1(@Wal mount)/69.1(@AC) mm

Set Width (inch): 28.60 inch Set Height (inch): 16.75 inch

Wall Mount: 100(H) x 100(V) mm / 200(H) x

200(V) mm, M4

Set Depth (inch): 2.56(@Wall mount)/2.72(@AC) inch

Bezel width: 11.9 mm (T/L/R), 17.2 mm (B)

Product weight (lb): 12.57 lb

### **Operating conditions**

Altitude: 0 ~ 3000 m

Temperature range (operation): 0 ~ 40 °C

MTBF: 50,000 hour(s)

Temperature range (storage): -20 ~ 60 °C Humidity range (operation)[RH]: 20 - 80% RH

(No condensation)

Humidity range (storage) [RH]: 5 - 95% RH (No

condensation)

### **Multimedia Applications**

USB Playback Video: MPEG, H.263, H.264, H.265, AVI, MP4, MPEG4, VP8, VP9, WEBM USB Playback Picture: BMP, JPEG, PNG USB Playback Audio: AAC, HEAAC, MPEG

### **Internal Player**

CPU: 2x A72 + 4x A53 GPU: ARM Mali-T860 MP4 Memory: 4GB RAM Storage: 32 GB eMMc

### **Accessories**

Included Accessories: RS232 daisy-chain cable, Philips logo (x1), USB Cover (x1), Screws, AC Power Cord, AC Switch Cover, IR sensor cable (1.8 m) (x1), Quick start guide, Remote control & AAA batteries, RS232 cable, Wire Clamper (x3)

#### Miscellaneous

On-Screen Display Languages: English, French, German, Spanish, Polish, Turkish, Russian, Italian, Simplified Chinese, Traditional Chinese, Arabic, Japanese, Danish, Dutch, Finnish, Norwegian, Portuguese, Swedish

Warranty: 3 year warranty

Regulatory approvals: CE, CCC, RoHS, CB, EMF,

FCC, Class A, EnergyStar 8.0, UL

© 2025 Koninklijke Philips N.V. All Rights reserved.

Issue date 2025-02-06

Version: 2.2.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 80466 4



www.philips.com